



# HOISTS

## ShopStar Electric Hoists

- Rugged construction and compact design makes this unit ideal for a variety of commercial and industrial applications
- The H4 duty cycle rating allows the hoist to be used in production and maintenance environments
- Rugged cast aluminum alloy hoist frame
- Fully enclosed non-ventilated hoist frame protects motor from environmental contamination
- Includes a standard protector overload device
- 6 1/2' power cord molded 3-prong plug on 115 V units
- Gear train lifetime lubricated with non-oxidizing grease
- 10-pocket oblique lay liftwheel provides longer chain wear
- Alloy load chain • Standard lift: 10'
- Hook mount suspension
- Epoxy powder coat finish
- Lifetime warranty
- cUL approved and meets ASME B30.16

Model No.	Lift Speed FPM	Voltage	Phase	Capacity lbs.	Weight lbs.	Price /Each
LT598	16	115	1	250	28	
LT599	16	115	1	300	28	
LT600	8	115	1	500	34	
LT601	8	115	1	600	34	
LT602	6	115	1	1000	34	
LT603	24	575	3	250	28	
LT604	16	575	3	300	34	
LT605	16	575	3	500	28	
LT606	12	575	3	600	34	
LT607	20	575	3	600	32	

**Note:** Additional lifts & capacities available on request

## ShopAir Chain Hoists

- Rugged cast aluminum alloy hoist frame and industrial-duty air motor makes this unit an ideal hoist for a workstation and/or production line
- Includes a standard protector overload device
- Fully enclosed non-ventilated hoist frame protects motor from environmental contamination
- 10-pocket, oblique lay liftwheel provides longer chain life
- Hook mount suspension
- Variable flow, two lever pendant for precise load spotting
- Gear train lifetime lubricated with non-oxidizing grease
- Hardened forged steel, latch-type lower hook rotates 360°
- Alloy load chain • Standard lift: 10'
- Epoxy powder coat finish provides a durable exterior
- Lifetime warranty
- Meets ASME B30.16

Model No.	Lift Speed FPM	Headroom"	Capacity lbs.	Weight lbs.	Price /Each
LT608	16	11-15/16"	500	32	
LT609	31	10-7/8"	300	28	
LT610	16	10-7/8"	600	30	
LT611	21	10-7/8"	500	34	
LT612	11	11-15/16"	1000	45	

**Note:** Additional lifts & capacities available on request

## Electric Chain Hoist

- Multi-disc magnetic brake for positive load holding and spotting
- Adjustable upper and lower limit switches
- Overload limiting clutch and latch-type ridged top hook
- 24-volt pushbutton station fits easily in your hand to allow thumb, trigger or two-handed operation
- Made in the USA
- 5 year warranty
- Max Lift Speed (ft./min): 16 FPM
- Min Lift Speed (ft./min): 16 FPM
- Voltage: 115V/230V
- Chain Material: Steel
- Phase: 1

Model No.	Mfg No.	Lift'	Capacity	Price /Each
TEA071	9560	10	1000 lbs. (0.5 tons)	
TEA072	9561	15	1000 lbs. (0.5 tons)	
TEA073	9562	20	1000 lbs. (0.5 tons)	
TEA074	9565	10	2000 lbs. (1 tons)	
TEA075	9566	10	2000 lbs. (1 tons)	
TEA076	9567	15	2000 lbs. (1 tons)	
TEA077	9568	20	2000 lbs. (1 tons)	
TEA078	9570	10	4000 lbs. (2 tons)	
TEA079	9571	10	4000 lbs. (2 tons)	
TEA080	9572	15	4000 lbs. (2 tons)	
TEA081	9573	20	4000 lbs. (2 tons)	



## Lodestar Electric Chain Hoists

- Features quiet operation, an environment friendly design, easy access to components, high duty cycles, along with less maintenance and enhanced safety features
- Lifetime grease-lubricated gear box
- 5-pocket liftwheel • Zinc-plated chain
- Clutch is located outside the load path, preventing slipping of the load in an overload condition when the brake is not powered
- Fabric chain container and rigid hook suspension standard on every Lodestar
- Hook mount standard, lug mount available upon request
- Standard lift: 10' • Lifetime warranty
- CSA approved and meets ASME B30.16 • Precision gears
- AC electrical brake or double DC brake available
- Variable speed drive (VFD) or traditional 2 speeds available

Model No.	Lift Speed FPM	Voltage	Phase	Capacity lbs.	Weight lbs.	Price /Each
LT615	16	115	1	500	53	
LT616	32	115	1	500	61	
LT617	8	115	1	1000	71	
LT618	16	115	1	1000	61	
LT619	8	115	1	2000	72	
LT620	16	115	1	2000	113	
LT621	8	115	1	4000	131	
LT624	16	575	3	500	61	P.O.A.
LT625	32	575	3	500	64	P.O.A.
LT626	8	575	3	1000	69	P.O.A.
LT627	16	575	3	1000	65	P.O.A.
LT628	16	575	3	2000	110	P.O.A.
LT629	32	575	3	2000	117	P.O.A.
LT630	8	575	3	4000	130	P.O.A.
LT631	16	575	3	4000	135	P.O.A.
LT632	5.5	575	3	6000	158	P.O.A.
LT633	11	575	3	6000	162	P.O.A.

**Note:** Additional lifts & capacities available on request



## Adjustable Trolleys

- Easily adjusts to fit various flanges, I-beams and H-beams
- Use on straight or curved track
- Can be installed or removed at any position on the beam
- Heavy-duty cast iron wheels
- Deep width flange provides superior contact with the beam
- Geared trolleys include two geared wheels operated by hand chain
- Safety plate included
- Meets ASME B30.16

Model No.	Fits I beams"	Cap. lbs.	Wt. lbs.	Price /Each
LS551	2 11/16 - 5 3/8	1000	10	
LS552	3 1/8 - 6 1/4	2000	17	
LS553	3 1/8 - 6 1/4	4000	28	
LS554	3 7/16 - 7 3/8	6000	46	
LS555	4 13/16 - 9 9/16	10000	73	

Model No.	Fits I beams"	Cap. lbs.	Wt. lbs.	Price /Each
LS556	2 11/16 - 5 1/4	1000	18	
LS557	3 1/8 - 5 15/16	2000	25	
LS558	3 1/8 - 7 1/16	4000	36	
LS559	3 7/16 - 7 3/8	6000	54	
LS560	4 3/4 - 7 3/4	10000	81	

## CBT Adjustable Trolleys

- Adjustable trolleys are available in plain and geared to fit most applications up to 8.7" beam flange widths
- Dual tread wheels will fit either tapered or flat beam flanges and include permanently lubricated, shielded ball bearings for long life and reduced maintenance
- Lifetime warranty

Model No.	Stand Beam Height"	Stand Beam Width"	Wt. lbs.	Capacity Tons lbs.	Price /Each
LT296	4-24	2.0-8.7	19	1/2 1000	
LT297	5-24	2.3-8.7	26	1 2000	
LT299	6-24	2.3-8.7	46	2 4000	
LT300	8-24	3.0-8.7	86	3 6000	
LT301	10-24	3.5-8.7	130	5 10000	

Model No.	Stand Beam Height"	Stand Beam Width"	Wt. lbs.	Capacity Tons lbs.	Price /Each
LT302	5-24	2.3-8.7	26	1 2000	
LT304	6-24	2.3-8.7	46	2 4000	
LT305	8-24	3.0-8.7	86	3 6000	
LT306	10-24	3.5-8.7	130	5 10000	



Adjustable Plain Trolley



Adjustable Geared Trolley

