



Snow Blowers (Two stage 300 Series)

- Snow is fed into the housing by an auger and then discharged through the chute by an impeller
- Infinitely variable hydrostatic drive system provides convenient driving with optimum control
- Convenient trigger-control power steering allows superior maneuverability in adverse conditions
- Robust and durable auger housing gives sturdy operation, efficient snow clearing and long product lifetime



Husqvarna®

FEATURES

- Electric starter
- Power steering
- Variable drive speed
- Heated handles
- Heavy duty auger
- Heavy duty auger housing
- Premium control cables
- Remote chute deflector
- Remote chute rotator
- High speed impeller
- Feed screw with ball bearings
- LED headlights
- Drift cutter for snow banks
- Heavy-tread tires
- 10-Year cast iron auger gearbox warranty
- 5-Year engine warranty



NL978



NL971

SPECIFICATIONS	ST 330P	ST 327P	ST 327T	ST 324P
Transmission	Hydrostatic 2	Hydrostatic 2	Hydrostatic 2	Hydrostatic 2
Cylinder displacement, cc	369	291	369	254
Net power, ft-lb, Gross torque	17.00	14.50	17.00	12.50
Fuel tank volume, gallons / litres	0.95 / 3.6	0.95 / 3.6	0.95 / 3.6	0.71 / 2.7
Working width, in.	30	27	27	24
Intake height, in.	23	23	23	23
Auger diameter, in.	14.0	14.0	14.0	14.0
Impeller vanes	4	4	4	4
Tire size, single axle, in.	16	15	Track drive	15
Model No.	NL971	NL968	NL978	NL965
Mfg. No.	961 93 00-94	961 93 00-92	961 93 00-93	961 93 00-91
Price/Each	\$	\$	\$	\$

Snow Blowers (Two stage 200 Series)

- Snow is fed into the housing by an auger and then discharged through the chute by an impeller
- Adjustable handle height for improved ergonomics
- Friction disc transmission for easy speed changes depending on snow conditions
- Convenient trigger-control power steering allows superior maneuverability in adverse conditions



Husqvarna®

FEATURES

- Power steering
- Electric starter
- Variable drive speed
- Adjustable handles (4 positions)
- Heated handles
- Heavy duty ribbon auger
- Heavy duty auger housing
- Premium control cables
- Remote chute deflector
- Remote chute rotator
- High speed impeller
- Feed screw with ball bearings
- Dual LED headlights
- Drift cutter for snow banks
- Heavy-tread tires
- Optional chute extension
- Optional weight bar
- 5-Year engine warranty



NL960



NL964

SPECIFICATIONS	ST 230P	ST 227P	ST 224P	ST 224
Transmission	Friction Disc	Friction Disc	Friction Disc	Friction Disc
Cylinder displacement, cc	291	254	208	208
Net power, ft-lb, Gross torque	14.5	12.5	9.5	9.5
Fuel tank volume, gallons / litres	0.95 / 3.6	0.71 / 2.7	0.71 / 2.7	0.71 / 2.7
Working width, in.	30	27	24	24
Intake height, in.	23	23	23	23
Auger diameter, in.	12.0	12.0	12.0	12.0
Impeller vanes	3	3	3	3
Tire size, single axle, in.	16	15	15	15
Model No.	NL964	NL960	NL957	NM819
Mfg. No.	961 93 01-01	961 93 00-97	961 93 01-22	961 93 00-96
Price/Each	\$	\$	\$	\$