

Dynastraight® Air Powered Abrasive Finishing Tools

Ideal set-up for Dynacushion® wheel (not included)

Threaded arbor (5/8" -11) for exclusive use with Dynacushion® pneumatic wheel

Shown with optional pneumatic wheel

Model No. **TGY774** 13505 Mfg. No.

15-1/2" long x 3-1/2" wide **Abrasive Information:**

Dynacushion

belts (394 mm x 89 mm) Air Flow Rate @ 90 PSI: 44 SCFM 88 dB (A) Sound Level: 1.00 HP Horsepower: 3400 RPM Free Speed: Air Pressure: 90 PSI Air Inlet Thread: 3/8 NPT Hose Size (I.D.): 3/8" (10 mm) Threaded Arbor: 5/8" - 11 male **Tool Spindle Thread:** 1/2" - 20 male 14 7/8" (378 mm) Lenath: 17/8" (48 mm) Height:

4 lbs. (1.82 kg) Weight: Price/Each:

TGZ172



Dynisher® Finishing Tools

Excellent for blending and finishing stainless steel and most other metals, leaving an in-line pattern

Includes: 3/4" dia. arbor for mounting a variety of abrasives & accessories

Shown with optional Dynacushion® pneumatic wheel not included

TGY767 Mfg. No.

3-1/2"(84 mm) x 15-1/2"(394 mm) **Abrasive Information:**

abrasive belts 4" dia. (102 mm) Abrasive

Air Flow Rate @ 90 PSI: 80 dB (A) Sound Level: Horsepower: 100 HP 2800 RPM Free Speed:

Air Pressure: **90 PSI** Air Inlet Thread: 3/8 NPT Hose Size (I.D.): 3/8" (10 mm) Max. SFPM: 3665 SFPM **Arbor Information:** 3/4" x 2 5/16"

(19 mm x 59.5 mm) 15" (381 mm) Length: Heiaht: 7" (178 mm) Weight: 5.7 lbs. (2.59 kg)

Price/Each:



Die Grinders Straight & Offset (7°)


Gearless motor reduces downtime and lessens repair expense compared to geared tools

Governor-controlled to maintain RPM under heavy load



Model No.	TGZ172	TGZ174	TGZ175	TGZ073
Mfg. No.	52666	52668	52669	48205
Head type	Straight	Straight	Straight	7°
Collet Insert Size:	1/4"	1/4"	1/4"	1/4"
Free Speed (RPM):	12 000	18 000	20 000	25 000
HP (W):	1.0 (746)	1.0 (746)	1.0 (746)	0.4 (224)
Motor Characteristic:	Gearless	Gearless	Gearless	Gearless
Exhaust Type:	Rear	Rear	Rear	Rear
Wt. lbs.:	2.3	2.4	2.4	1.5
Price/Each:		_		

4" Lightweight Dyninger® Finishing Tools (1/4" Collet)



Tool includes air-flow control Dynaswivel® fitting for maximum tool manoeuvrability and control

Eliminates raised grain and removes loose fibres when whitewood sanding as well as scuffing sealer coats

Model No **TGY792** Mfg. No. Abrasive Information:

Order Separately: 3/4", 1", 1-1/2", 2", 3", & 4", dia. sanding stars

(19, 25, 38, 51, 76, & 102 mm) Air Flow Rate @ 90 PSI: 21 SCFM

Sound Level: 81 dB (A) 0.40 HP Horsepower: 0 to 3200 RPM Free Speed: Air Pressure: 90 PSI 1/4 NPT Air Inlet Thread: Hose Size (I.D.): 1/4" (6 mm) Max. SFPM: 3350 SFPM **Tool Spindle Thread:** 3/8"- 24 male Length: 8 3/4" (222 mm) **Height Diameter:** 23/8" (60 mm) Weight: 2.2 lbs. (1 kg) Price/Each:



DYNABRADE

Pencil Grinders 60000 RPM

High-speed air motor, controlled with patented governor, provides constant speed under load

Precision, high-tolerance, low run-out collet. Run-out is a true 0.0002 @ 1" (25 mm) from face

Super flexible hose for maximum agility

Model No.	TGZ034
Mfg. No.	51700
Collet Insert Size:	1/8"
Air Flow Rate @ 90 PSI:	8 SCFM
Sound Level:	66 dB(A)
Motor Characteristic:	Oil-Less Turbine
Free Speed:	60 000 RPM
Bearing Type:	Metal
Exhaust Type:	Rear
Weight:	0.6 lbs.
Packaged Weight:	1.6 lbs.
Price/Each:	\$



Electric Dynisher® Finishing Tools 3/4" (19 mm) dia. arbor; pneumatic tire

and abrasive sold separately

Variable speed On/Off switch 5/8" - 11 spindle and 3/4" arbor

Model No THZ358 Mfg. No. 51585 Max. RPM: 0-3000 RPM 120 V (AC) Phase: 1 Voltage: **Current:** 11 A, 60 Hz Frequency Length: 17" (468 mm) Height: 8" (468 mm) Weight: 9.5 lbs. (3.8 kg) Price/Each:

