



### 14" x 40" Gearhead Metal Lathes

- Safety guard automatically shuts lathe off when lifted
- Full length spindle foot brake incorporated in the cabinet stand for easy operation and reliable safety
- Includes: 7"-3 jaw chuck, 8"-4 jaw chuck, imperial and metric gears, quick change tool posts, steady rest, follow rest, 12" D1-5 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, MT#6-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex keys and cabinet stand (with foot brake incorporated)



<b>Distance between centers:</b>	40"
<b>Swing over bed:</b>	14"
<b>Swing over gap:</b>	20 1/4"
<b>Spindle bore:</b>	2"
<b>Swing over cross slide:</b>	8 5/8"
<b>Taper in headstock:</b>	MT#6
<b>Taper in tailstock:</b>	MT#3
<b>Width of bedways:</b>	7 5/16"
<b>Total travel of cross slide:</b>	6 3/16"
<b>Total travel of top slide:</b>	3 1/2"
<b>Spindle speeds:</b>	8 (70-2000 RPM)
<b>Thread cutting range:</b>	34 (4-56 TPI) 26 (.4-7 MM)
<b>Motor:</b>	2 HP, 11 A, 1 phase, 60 Hz
<b>Voltage:</b>	240 V
<b>Dimensions:</b>	75" L x 32" W x 53" H
<b>Weight:</b>	2025 lbs.
<b>w/o Taper Attachment</b>	
<b>Model No.</b>	<b>TEB022</b>
<b>Mfg. No.</b>	KC-1440ML
<b>Price/Each</b>	\$
<b>w/Taper Attachment</b>	
<b>Model No.</b>	<b>TMA039</b>
<b>Mfg. No.</b>	KC-1440ML/KM-054
<b>Price/Each</b>	\$

### Box & Pan Brakes

- Constructed with welded steel plate
- Spring-loaded handle allows for fast and easy action
- Heavy truss rods and braces designed for stability and strength
- Includes: extension handles, cast iron counter weight (only TCW450), apron stop and replaceable bushings



<b>Model No.</b>	<b>TCW450</b>
<b>Mfg. No.</b>	KC-BP4816
<b>Capacity (mild steel):</b>	16 gauge
<b>Bending length:</b>	48"
<b>Max. lift of beam:</b>	1-1/2"
<b>Min. reverse bend:</b>	1/2"
<b>Min. flange in capacity material:</b>	5/16"
<b>Max. depth of box:</b>	3"
<b>Finger widths:</b>	5 x 2", 6 x 3", 5 x 4"
<b>Dimensions (less counterweight):</b>	72" L x 15" W x 28-3/4" H
<b>Weight:</b>	315 lbs.
<b>Price/Each</b>	\$

### Live Centres

- Very accurate
- Fitted with taper roller bearings
- Use: Metal lathe



<b>Model No.</b>	<b>TZ825</b>	<b>TZ826</b>
<b>Mfg. No.</b>	KLC-2M	KLC-3M
<b>Taper shank:</b>	MT#2	MT#3
<b>Price/Each</b>	\$	\$



Contact us now to receive our latest flyers

