

Silver Galvanizing Compounds

- Sacrificial coating that inhibits corrosion on ferrous metals
- Excellent touch-up for repair of galvanized substrates
- Produces a dry coating with the bright finish of hot-dip galvanizing
- Recommended dry film thickness of 1.5 to 3.0 mils VOC-compliant
- Dries to touch in 30 minutes
- May be recoated after 2-16 hours, or after 36 hours
- For automotive plants, refineries, nuclear facilities, power plants and transmission towers, fences, gutters, bridges, structural steel, wrought iron, farm equipment, damaged galvanized surfaces, highway maintenance and marine applications







Model	Mfg.		Price	(Qty Price	
No.	No.	Size	/Each	Qty	/Each	
ΔΔ185	(00739000	14 07				

E-Weld Nozzle Anti-Spatter

- Maximum Operating Temperature: 1832°F (1000°C)
- Ceramic anti-spatter that protects welding nozzles
- Provides unrivaled protection of welding nozzles in manual, semi-automated and fully-automated MIG welding applications
- Reduces downtime by extending nozzle life
- Protects welding nozzles for 8 hours
- At least 125 uses with applicator



No.	No.	Size	Description	/Each	Qty
AF017	53F512	400 ml	-		7
VV928	53L121	-	Applicator		
VV929	53F912	-	Aerosol		-
			9. Applicator Vit		

Welder's Stainless Steel Protective Coating

- Provides maximum corrosion resistance on metal, chrome, ceramic and copper surfaces
- Formulated with 100% Type 316L stainless steel pigment
- Dries quickly to a satin sheen
- Hardens overnight and cures in just a few days
- Use to cover discolouration in weld areas
- For exhaust and steam pipes, mufflers, radiators, production equipment, engines, furnaces, plumbing fixtures, chemical processing equipment





Model	Mfg.		Price	Qty Price		
No.	No.	Size	/Each	Qty	/Each	
AA027	C00738000	12 oz.				

WL941 Dry Weld **Spatter Protectant**

- dries to a white film
- Prevents spatter from sticking to metal surfaces during welding
- Just brush or wipe off residue after welding
- Does not contain silicone
- Surface may be painted after use
- Formulation does not contain Methylene Chloride
- Uses: All types of maintenance and production welding, construction and body shops





Model	Mfg.	Price		Qty Price
No.	No.	Size	/Each	Qty /Each
AE835	C00941000	15.5 oz.		

WL542 MC Wet **Weld Spatter Protectant**

- Liquid anti-spatter that keeps welding tips & nozzles clean and prevents weld spatter adhesion
- Does not contain silicone and will not interfere with post-decorating
- Uses: Contact tips, weldments, electrode holders, fixtures, resistance welding tips and wheels



Model	Mfg.		Price	Qty Price		
No.	No.	Size	/Each	Qty /Each		
AE826	C00542000	15.5 oz.				

Anti-Spatter

- Safe, water-based formula
- **Excellent spatter protection**
- Non-toxic
- Non-flammable
- Does not contain suspect carcinogens such as methylene chloride
- Does not contain silicone
- Paint compatible
- Accepted for use in Canadian food processing facilities





Model	Mfg.	Price		Qty Price
No.	No.	Size	/Each	Qty /Each
AA816	C02116	13 oz.		•

E-Weld Weld Spatter Release Emulsions

- Effectively protects work pieces and welding equipment (such as torches, robots and jigs) eliminating costly spatter removal work
- Best for general purpose welding
- Contains temporary corrosion inhibitors Prevents weld spatter from sticking
- Ultrafine spray for complete coverage
- Will not harm painted surfaces
- Can be used on all weldable metals
- Green colour for a better view on work piece





Model No.	Mfg. No.	Description	Metric	Imperial	Price /Each	Qty Prio
AA903	53-F 002	Aerosol	400 ml	13.5 fl.oz.	/ Lucii	Qty /Euc
AC300	53-F 203	Trigger Spray	500 ml	16.9 fl.oz.		
AA475	53-F 207	Liquid	20 L	5.2 gal		
AC301	53-F 208	Liquid	208 L	55 gal		

E-Weld 3 Weld Spatter Release Solutions

- Unique, high performing anti-spatter solution that protects work pieces from adherence of high energy spatter and eliminates costly spatter removal operations
- Can also be used to clean and degrease surfaces prior to welding
- Formulated to prevent spatter adhesion for high temperature welding applications such as: stainless steel welding, multiple pass welding, thin sheet welding and welding pre-heated work pieces
- For MIG and Arc welding applications, as well as plasma cutting
- Water base formulation biodegradable, non-flammable, odourless
- Compatible with aluminum, steel and stainless steel
- · VOC free, solvent free and silicone free
- Contains corrosion inhibitors for short term corrosion protection
- Excellent paint adhesion properties no special cleaning required for post welding coating operations



Model	Mfg.		Price	Qty Price			
No.	No.	Description	Metric	Imperial	/Each	Qty	/Each
AA506	53-F 253	Trigger Spray	500 ml	16.9 fl.oz.			
AA508	53-F 257	Liquid	20 L	5.2 gal			
AC309	53-F 258	Liquid	208 L	55 gal			