



## Canadian Wire Connector Kits

### 450 PIECES

- A variety of connectors to fit a large range of wire sizes
- Great for servicing technicians
- Convenient and durable carrying case
- Reusable packaging
- Made in Canada
- UL Listed and CSA Certified
- Kit Components:
  - 20 x WingTwist® Wire Connector - Blue 14-6 AWG (WT 54 - Rated 600V)
  - 20 x Canadian Wire Twist™ - Red 18-14 AWG (C6 - Rated 600V)
  - 85 x Can-Twist™ 22-8 AWG (007 - Rated 600V)
  - 50 x Canadian Wire Twist™ - Yellow 18-10 AWG (C4 - Rated 600V)
  - 50 x Can-Twist Extreme™ 22-12 AWG (007XT - Rated 600V)
  - 100 x WireTwist® Wire Connector - Blue 22-14 AWG (WT2 - Rated 300V)
  - 50 x WireTwist™ Wire Connector - Gray 22-14 AWG (WT1 - Rated 300V)
  - 75 x Canadian Wire Twist™ - Orange 18-14 AWG (C3 - Rated 600V)



Model No.	Mfg. No.	Connection Type	Wire Range (AWG)	Voltage	Colour	Price /Each
XE850	30-2088	Twist	26-6	Mixed	Mixed	

## Can-Twist™ Wire Connectors

- Exceptional wire-range capacity - handles wire combinations from 22 to 8 AWG solid and/or stranded wires
- Easily removed for repeat usage
- Flexible walls show when wires are firmly connected
- Spring threads are heat-set, making them more reliable
- Extended skirt length provides over-strip protection
- Smaller size makes it easier to work in tight spaces
- Wide mouth and square springs deliver quicker pick-up
- Swept wings provide added gripping power
- Easier to twist: only a few turns are necessary to achieve torque
- Wire Combination Range: 600V #22 thru 8 AWG, Min.3 #22 Max.3 #10
- CSA 22.2#188 Certified



Model No.	Mfg. No.	Quantity /Pkg.	Price /Pkg.
XC085	30-1071	175	
XC086	30-3071	475	

## Cable Tracers

- All components are fully fuse protected and intrinsically safe
- Model R2000 Receiver has two detectors in its tip which are tuned to pick up the electromagnetic signals or electrostatic signals
- LEDs and sensitivity settings indicate the relative signal strength
- Model S2600 Load Signal Generator, when connected to an energized line, will draw a rapidly fluctuating current pulse from the source, causing the power line to emit an electromagnetic signal
- Model T2200 Transmitter injects a signal into an unenergized conductor R2000
- Model A2201 Inductive Clamp when clamped around the energized line and plugged into the T2200 will induce a signal onto the downstream (load) side
- Includes: Receiver, load signal generator, transmitter, clamp-on transmitter accessory, cordsets and adapter



Model No.	Mfg. No.	Description	Price/Each
HD909	AT-2004	Cable Tracing System	

## Yellow 77® Wire Pulling Lubricant

- Wax-based formula provides superior lubricity
- Safe to use with most cable types except low-density polyethylene and semi-conducting jackets
- Clings to cable through long pulls
- Environmentally safe - non-toxic, non-flammable, non-corrosive
- Dries to a thin, non-conductive film that won't clog conduit



Model No.	Description	Price /Each
AB488	1 qt. Squeeze Bottle	
AB489	1 gal. Tub	

## VoltAlert™ Voltage Detector

- Small, rugged and reliable, the VoltAlert™ is designed for ease of use – if the tip glows red and the unit beeps when touching a terminal strip, outlet, or cord, there is voltage
- IA156 continually tests its battery and its circuit integrity with a periodic double flash visual indication using Fluke Voltbeat™ technology
- Voltage detection of 90 to 1000 VAC, as well as a 24 to 90 VAC control circuit model
- Cat. IV – 1000 V overvoltage category rating for added user protection
- **Covered by a two-year warranty**



IA216



Model No.	Mfg. No.	Description	Price /Each
IA156	1-AC-AT-II	ACV Detector, 90-1000 V	
IA216	1LAC-A-II	Low Voltage Detector, 20-90 VAC	