

HX081

Portable Electronic Balances

- Scout SPX is a portable balance designed to meet the most common weighing equipments
- Features a large LCD display
- Removable stainless steel pan
- Weight display in g, kg, oz., lbs., lb:oz.; and Troy ounce or pennyweight units for weighing precious materials
- Powered by four AA batteries (not included) or included AC adapter pack
- Dimensions: 6.0" W x 6.3" D x 2.2" H
- Weight: 1.8 lbs.
- 2-year warranty on parts and labour



MULTIPLE WEIGHING MODES:

- Parts counting
- % weighing
- Display hold for shipping applications





NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	Graduation	Pan Size"	Price /Each
HX216*	SPX222	220 g	0.01 g	4.7 diameter	
HX217*	SPX422	420 g	0.01 g	4.7 diameter	
IA550*	SPX622	620 g	0.01 g	4.7 diameter	
HX218*	SPX421	420 g	0.1 g	4.7 diameter	
HM315*	SPX621	620 g	0.1 q	5.5 x 6.7	
IA551	SPX2201	2200 g	0.1 g	5.5 x 6.7	
IA553	SPX6201	6200 g	0.1 g	5.5 x 6.7	
IA554	SPX8200	8200 a	1 a	5.5 x 6.7	

^{*} Span calibration mass included

Portion Control Scales

- Large LCD display 5/8" high
- Removable stainless steel platform
- Tare weighing function
- 800-hours of battery life
- 2-mode function metric and imperial
- AC adaptor (included) or four AA batteries (not included)



TAMITA

NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	Graduation	Price/Each
HX081	KD-200-110	35 oz./1000 g	0.05 oz./1 g	
HX082	KD-200-210	70 oz./2000 g	0.1 oz./2 g	
IA557	KD-200-510	11 lbs./5000 g	0.2 oz./5 g	

Portion Control Scale

- Stainless steel easy wipe top
- Quick response
- Overload indicator
- · 0.1 oz. increments
- Tare
- Auto power off
- Certification : CE and NSF approved
- Powered by 2 x AAA batteries
- Display: LCD 2.17" x 0.83" Accuracy: +/- 0.5%
- Capacity: 5000 g/9 lbs.
- Graduations: 1 g/0.1 oz.
- Platform dimensions: 8 1/4" L x 5 7/8" W

Model No. IB734 Mfg. No. 600SC Price/Each \$



NOT LEGAL FOR TRADE



Low Profile Bench Scales

The ES Series design makes this low profile scale perfect for shipping, receiving and general bench applications. Easy 2-button operation and large display guarantees accurate and unmistakable results. The 3-way mounting bracket (included) allows you to mount the indicator to front of scale base, above the base, or to any vertical surface.

- · Display weight in kg, lbs., oz. or combined lb:oz.
- Stainless steel weighing platform and epoxy painted steel frame
- AC or battery powered operation
- Includes: 3-way mounting bracket and AC adapter
- 1-year warranty on parts and labour





NOT LEGAL FOR TRADE

Model	Mfg.	Capacity	Readability	Platform Dimensions			ns	Price	
No.	No.	lbs./kg/oz.	lbs./g/oz.	L"	x	W"	x	H"	/Each
HN272	ES30R	66/30/1056	0.05/10/0.5	12.2	Х	10.8	Х	1.5	
HN273	ES50R	110/50/1760	0.05/20/1	12.2	X	10.8	X	1.5	
HN274	ES50L	110/50/1760	0.05/20/1	20.5	X	15.7	X	3	
HN275	ES100L	250/100/3520	0.1/50/2	20.5	X	15.7	X	3	
HN276*	ES200L	440/200/7040	0.2/100/5	20.5	X	15.7	X	3	

^{*} lb:oz. display not available on model HN276

Compact Electronic Scales

- Displays results in g or combined lb:oz
- One-button operation
- Full capacity tare
- LCD display
- Operates on three AAA batteries (included) or with an optional AC adapter
- Dimensions: 5.3" W x 7.6" D x 1.5" H
- 1-year warranty on parts and labour
- Weight: 1 lb.





NOT LEGAL FOR TRADE

Model No.	Mfg. No.	Capacity	Graduation	Price/Each	
HN218	CS200	0 lb:7.05 oz./200 g	0.01 oz./0.1 g		
HN219	CS2000	4 lb:6.55 oz./2000 g	0.05 oz./1.0 g		
HN220	CS5000	11 lb:0.4 oz./5000 g	0.1 oz./2.0 g		
IB538	46001724	Optional AC Power Adapter			