



## 1/2" D-Handle Drills

- Heat treated metal gears for quiet performance
- Trigger speed control: 0-500 RPM, reversing
- Can be used with our right angle drive attachment to increase versatility
- Includes: Side handle and chuck key with holder

**Model No. TF058**  
**Mfg. No. 1107-6**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 1/2"  
**Amperage:** 7.0  
**No Load RPM:** 0-500  
**Chuck Type:** Keyed  
**Tool Weight:** 6.8 lbs.



## 1/2" D-Handle Right Angle Drills

- Heat treated metal gears for quiet performance
- All ball and roller bearings
- Head and handle swivel 360°
- Includes: right angle adaptor assembly, side handle, 9/16" open end wrench, 3/16" socket wrench and carrying case

**Model No. TF198**  
**Mfg. No. 3102-6**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 1/2"  
**Amperage:** 7.0  
**No Load RPM:** 335/500/750  
**Chuck Type:** Keyed  
**Tool Weight:** 10.3 lbs.



## VSR Right Angle Drill

- Compact, lightweight design fits into tight areas
- Paddle switch for convenient one-handed operation
- Chuck is shielded to protect workpiece from chuck teeth in confined areas
- 100% ball bearing construction provides durability and longer tool life
- Double gear reduction increases torque performance and decreases gear stress

**Model No. TLV862**  
**Mfg. No. DW160V**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 3/8"  
**Amps:** 4 A  
**Voltage:** 120 V  
**No Load RPM:** 0-1200  
**Chuck Type:** Keyed  
**Tool Weight:** 3.75 lbs.



## 3/8" Angle Drills

- Built-in LED job light and reduced head height (2 5/8")
- Compact (10 5/8" length) design for close quarters
- Paddle switch with speed limiting dial
- Includes: Grip and chuck key with holder

**Model No. TF811**  
**Mfg. No. DA3010F**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 3/8"  
**Amperage:** 4.0  
**No Load RPM:** 0-2400  
**Chuck Type:** Keyed  
**Tool Weight:** 3.1 lbs.



## 1/2" Super Hawg™

- Two operating speeds of 1750 and 450 RPM with a clutch in the low gear range
- Grip Roto-Lok® handle features 3 positions with 90° left-right rotation
- Includes: Side handle

**Model No. TEA124**  
**Mfg. No. 1680-21**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 1/2"  
**Amperage:** 13.0  
**No Load RPM:** 450/1750  
**Chuck Type:** Keyed  
**Tool Weight:** 14.7 lbs.



## 3/8" Close Quarter Angle Drills

- Angled chuck for reaching close quarters
- Large paddle trigger
- Angled cord exit and metal framed gear train
- Includes: Chuck key and holder

**Model No. TLZ155**  
**Mfg. No. 0370-20**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 3/8"  
**Amperage:** 3.5  
**No Load RPM:** 0-1300  
**Chuck Type:** Keyed  
**Tool Weight:** 3.9 lbs.



## VSR Stud & Joist Drill Kit with Bind-Up Control® System

- Perform and Protect™ line of power tools is designed to provide a high level of control, dust containment, or low vibration without sacrificing performance
- Mechanical clutch in low speed delivers increased gear protection
- 2 Variable speed ranges to match appropriate speed to the application
- Metal-gear housing for jobsite durability and increased reliability
- Adjustable front handle and 2-position side handle provide Maximum leverage and control
- 100% ball bearing construction provides durability and longer tool life
- Includes: Chuck key with holder, 2-position side handle, Bail handle, Kit box

**Model No. TLV856**  
**Mfg. No. DWD460K**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 1/2"  
**Amps:** 11 A  
**Voltage:** 120 V  
**No Load RPM:** 0-1300  
**Chuck Type:** Keyed  
**Capacity in Steel:** 1/2" (Twist Bit), 5" (Hole Saw)  
**Capacity in Wood:** 6" (Hole Saw), 1-1/2" (Spade Bit & Auger Bit), 4-5/8" (Self-Feed)



## 1/2" VSR Dual Range Hammer Drills

- High/low speed for high speed drilling or high torque applications
- 8.2 Amp motor provides high performance and overload protection
- 360° side handle with depth rod offers greater control
- Includes: 360° side handle, depth rod and chuck key with holder

**Model No. TKZ841**  
**Mfg. No. DW520K**  
**Price/Each \$**

### SPECIFICATIONS

**Chuck Size:** 1/2"  
**Amperage:** 10  
**No Load RPM:** 0-1200/0-3500  
**No Load BPM:** 0-56000  
**Chuck Type:** Keyed  
**Tool Weight:** 6.0 lbs.

