

5/8" SDS+ Rotary Hammers

- Lightweight, 4.6 lbs, compact, 10 1/4" length: Allows for work in tight spaces
- · Mechanical clutch: Protects tool when bit binds up
- AVS Anti vibration system: Delivers maximum comfort by minimizing vibration
- 2-mode operation: Rotary hammer and rotation only for maximum versatility
 Includes: Side handle
- Includes: Side handle, depth rod and carrying case

Model No. TLV203 Mfg. No. 5263-21 Price/Each \$

SPECIFICATIONS

 Solid Bit Capacity:
 5/8"

 Amperage:
 5.5

 No Load RPM:
 0-3700

 No Load BPM:
 0-4400

 Impact Energy:
 1.5 ft.-lbs.



Milwaukee

Milwaukee

SDS Max Rotary Hammers

- · Thin wall core bit capacity: 4'
- Drilling mode: 2-mode: Rotary hammer and hammer only
- · Heavy-duty 5.5 ft-lbs. of impact energy for solid performance
- Constant Power Technology ensures consistent drilling power for the toughest applications
- A 12-position chipping adjustment lets you maintain the optimum hammer position while chipping in any orientation
- A mechanical clutch protects the motor when the bit binds
- Two-mode operation offers maximum versatility regardless of the application
- · Tool comes with a side handle and carrying case

Model No. TMB675 Mfg. No. 5317-21 Price/Each \$

SPECIFICATIONS

| Solid Bit Capacity: 1 9/16" | Amperage: 10.5 | No Load RPM: 0-450 | No Load BPM: 0-3000 | Impact Energy: 5.5 ft.-lbs. | Tool Weight: 15 lbs.



L-Shape SDS Plus Rotary Hammer

- · Wide optimal drilling range for a single-hammer solution
- SHOCKS Active Vibration Control® technology reduces vibration felt at the handles for less user fatigue and greater productivity
- Factory-set clutch reduces sudden, high-torque reactions if bit jams
- Variable speed trigger for accurate hole starting
- Optimized ergonomic design provides excellent control in all orientations
- OSHA Table 1 Compliant dust extraction compatible
- Includes: Rotary Hammer D25333, Kit Box

Model No. UAD826 Mfg. No. D25333K Price/Each \$

SPECIFICATIONS

 Bit Capacity:
 3/16" - 7/8"

 Amps:
 8.5 A

 No Load BPM:
 0-5200 BPM

 No Load RPM:
 0-1150 RPM

 Impact Energy:
 2.58 ft.-lbs.

 Power Tool Type:
 Corded

 Tool Weight:
 8.16 lbs.



7/8" SDS Plus Rotary Hammer Kit

- · Three modes of operation: Rotary hammer, hammer only and rotation only
- Mechanical clutch: Protects the motor when the bit binds
- Variable position chisel stop: Allows material to be adjusted, regardless of orientation
 - Includes: (1) Carrying case, (1) depth rod, (1) side handle



Milwaukee

Model No. TLV204 Mfg. No. 5262-21 Price/Each \$

SPECIFICATIONS

 Solid Bit Capacity:
 7/8"

 Amperage:
 7.500

 No Load RPM:
 0-1500

 No Load BPM:
 0-5625

 Impact Energy:
 1.8 ft.-lbs.

 Tool Weight:
 5.8 lbs.



SDS Plus Rotary Hammer Kits

- Thin Wall Core Bit Capacity: 3"
- Vibration: 10.6 m/s²
- · Drilling mode: 3-mode: Rotary hammer, hammer only, rotation only
- Get up to 85% faster drilling and 85% harder hitting while reducing vibration
- Equipped with an all metal gear case and mechanical clutch to provide maximum durability
- · Powerful and lightweight
- Kit includes a side handle, depth rod and carrying case

Model No. TYO341 Mfg. No. 5268-21 Price/Each \$

SPECIFICATIONS

 Solid Bit Capacity:
 1 1/8"

 Amperage:
 8.0

 No Load RPM:
 0-1500

 No Load BPM:
 0-5500

 Impact Energy:
 3.6 ft.-lbs

 Tool Weight:
 7.5 lbs.



1 9/16" Spline Rotary Hammers

- Electronic Variable Speed allows the user to control the speed of drilling and chipping
- Spline tool holder is compatible with all spline drive bits
- Includes: 360° side handle, depth rod and heavy-duty kit box

Model No. T\$W672 Mfg. No. D25553K Price/Each \$

SPECIFICATIONS

 Solid Bit Capacity:
 3/8" x 1 1/4"

 Amperage:
 12.0

 No Load RPM:
 490

 No Load BPM:
 3300

 Impact Energy:
 7.3 ft.-lbs.

 Tool Weight:
 14.0 lbs.



Power Scrapers

- · Quick change bit retainer for easy changes
- Motor has auto shut-off feature when brushes must be replaced
- Factory grease packed for approximately 200 hours of maintenance free operation
- Includes: 1 3/16" and 2" scaling chisels, bull point, dust cover and plastic carrying case

Model No. TF850 Mfg. No. HK1820 Price/Each \$

SPECIFICATIONS

Amperage: 5.0
No Load BPM: 0-3200
Impact Energy: 2.9 ft.-lbs.
Tool Weight: 7.5 lbs.



