



Heavy-Duty Dual Temperature Heat Guns

- Increases surface temperature to required working temperature faster than conventional hot air heat guns
- 3-position rocker switch: off, high and low
- Impact resistant heating element
- Support stand enables gun to be stationary for workbench or assembly work

Model No. TF714
Mfg. No. 8975-6
Air volume: 14.8 cu.ft./min.
Air temperatures: 570° F/1000°F
Motor: 120 V AC, 11.6 A
Weight: 1.6 lbs.
Price/Each \$



Heat Guns

- Length: 10 1/2"
- Ergonomic style and powerful heating elements
- The variable temperature adjustment allows you to dial in the proper temperature for your job
- Handle Type: Pistol Grip

Model No. TF715
Mfg. No. 8977-20
Air volume: 20 cu.ft./min.
Air temperatures: 100°F - 1040°F (37°C - 560°C)
Motor: 120 V, 11.6 A
Weight: 1.8 lbs.
Price/Each \$



Accessories



AIR REDUCTION NOZZLE

- Intensified heat in a specific area – soldering

Model No. TF373
Mfg. No. 49-80-0297
Price/Each \$



HOOK NOZZLE

- For surround-bending, soldering pipe or shrinking tubing

Model No. TF370
Mfg. No. 49-80-0292
Price/Each \$



DEFLECTOR

- Deflects air away from glass when stripping paint or softening putty

Model No. TF371
Mfg. No. 49-80-0293
Price/Each \$



AIR SPREADER

- Intensified heat for removing floor coverings, paint burning and vinyl top removal

Model No. TF372
Mfg. No. 49-80-0294
Price/Each \$

ACCESSORY ASSORTMENT

- Includes TF373, TF370, TF371 and TF372

Model No. TF374
Mfg. No. 49-80-0300
Price/Each \$

Heavy-Duty Heat Gun

- Temperature: 120°F - 1100°F (50°C - 600°C)
- Temperature Setting: Variable
- Voltage: 120 V
- Amps: 13 A
- Wattage: 1550 W
- Power Cord Length: 10'
- Tool Weight: 2.1 lbs.

Model No TLV912
Mfg. No. D26950
Price/Each \$



Heavy-Duty LCD Heat Gun

- Temperature: 150°F - 1100°F (65°C - 600°C)
- Temperature Setting: Variable
- Voltage: 120 V
- Amps: 13 A
- Wattage: 1550 W
- Power Cord Length: 10'
- Tool Weight: 2.3 lbs.

Model No TLV913
Mfg. No. D26960
Price/Each \$



Heat Gun

- Variable temperature dial provides stepless electronic temperature adjustment to achieve precise heating requirements
- Ergonomic soft rubber grip design for comfortable operation
- Temperature: 122°F - 1022°F (50°C - 550°C)
- Temperature Setting: Variable
- Voltage: 120 V
- Amps: 13 A
- Air Volume - Switch 1: 7.0 CFM (200 l/min)
- Air Volume - Switch 2: 14.0 CFM (400 l/min)
- Includes: Plastic Carrying Case

Model No TYY270
Mfg. No. HG6031VK
Price/Each \$



Heat Gun

- 2-stage air volume and temperature control provides versatility in a wide range of applications
- Rear housing design with integrated rubber bumpers allows tool to be positioned upright for use as a static heating source during two-handed operations
- Ergonomic soft rubber grip design for comfortable operation
- Temperature: 0°F - 1022°F (0°C - 550°C)
- Temperature Setting: Variable
- Voltage: 120 V
- Amps: 13 A
- Air Volume - Switch 1: 7.0 CFM (200 l/min)
- Air Volume - Switch 2: 14.0 CFM (400 l/min)
- Includes: Plastic Carrying Case (PRO0000060)

Model No TYY269
Mfg. No. HG5030K
Price/Each \$



Accessories



WIDE-ANGLE SLIT NOZZLE

Model No. TD196
Mfg. No. P-71423
Price/Each \$



REFLECTOR NOZZLE

Model No. TD198
Mfg. No. P-71445
Price/Each \$



3/8" REFLECTOR NOZZLE

Model No. TD206
Mfg. No. P-71495
Price/Each \$



AIR REDUCTION NOZZLE

Model No. TD205
Mfg. No. P-71439
Price/Each \$