

Random Orbit Palm Sanders

- Fast random-orbit action for aggressive sanding
- Efficient through the pad dust collection system

5'

3.0

1/8"

High power motor for heavy duty application Includes: 5" abrasive disc, dust bag and pad

Model No. TLY383 Mfg. No. BO5030 Price/Each \$

SPECIFICATIONS

Sandpaper Size: 120 V Voltage: Amperage: **Orbits per Minute:** 12000 **Orbit Diameter: Tool Weight:** 2.9 lbs



Tnakita

Thakita

eita

Milwaukee

Heavy Duty 3" x 24"Belt Sander

Thakita

- All ball and needle bearing construction
- Fast sandpaper changes with lever clamps Includes: Dust bag and 10-pack of abrasive belts

Model No. TF795 Mfg. No. 9924DB Price/Each \$

SPECIFICATIONS

Belt Size:	3" Wx 24" L
Voltage:	120 V
Amperage:	7.8
Surface Feet per Minute:	1300
Tool Weight:	10.5 lbs.



- Powerful motor features increased power input and
- increased cooling for demanding sanding applications Redesigned housing reduces height creating a lower
- centre of gravity to improve handling and maneuverability Large clamping Lever for quick and easy sandpaper changes .
- Rigid aluminum foot with sponge sleeves for durability and effective vibration dampening
- Ergonomic soft rubber grip design for vibration
- absorption and comfortable operation
- Pad Size: 3-5/8"W x 7-1/4"D Overall Length: 10" Includes: Dust bad, Punch plate, pad
- Model No. TDU674 Mfg. No. BO3710 Price/Each \$

SPECIFICATIONS

Sandpaper Size: 1/3 sheet Voltage: 120 V Amperage: 1.7 Orbits per Minute: 11000 **Tool Weight:** 3.5 lbs

3.5 max HP, 7"/9" Sander

- Trigger Lock: Yes
- Includes: (1) flange, (1) nylon washer, (1) side handle
- Spiral bevel gearing for performance and durability Sander may be converted to grinder by using the proper wheel guard

Model No. TF490 Mfg. No. 6065-6 Price/Each \$

SPECIFICATIONS

Sandpaper Size: Q' 120 V Voltage: 15.0 Amperage: **Orbits per Minute:** 5000 **Orbits diameter:** 1" Spindle: 5/8"-11 **Tool Weight:** 12.0 lbs

Sheet Palm Sanders

- Dust bag for clean and efficient sanding with extended sandpaper life by reducing clogging
- All ball bearing construction for smooth operation, engineered
- to operate at low noise level with reduced vibration
- Comes with easy to use clamp lever and hook and loop pad
- Includes: Dust bag, nozzle, dust nozzle, punch plate, three sanding paper and plastic case

Model No. TLY382 Mfg. No. BO4555K Price/Each \$

SPECIFICATIONS

Sandpaper Size: 1/4 sheet Voltage: 120 V Amperage: 2.0 Orbits per Minute: 14000 Tool Weight: 2.4 lbs.

Random Orbit Palm Sanders

- Variable speed dial: 7000-12000 orbits per minute
- Electronic soft start guickly and steadily ramps the motor up in stages
- Integrated vacuum ports fits 1 1/4" or 2 1/4" hoses
- Includes: Dust bag and carrying case

Model No. TLZ441 Mfg. No. 6021-21 Price/Each \$

SPECIFICATIONS

Sandpaper Size: Voltage: Amperage: **Orbits per Minute:** 7000-12000 **Orbit Diameter: Tool** Weight:



IM

Inakita

maki

Milwaukee

Single Speed Random Orbit Sander

Shorter height allows the user to get closer to work piece

5"

120 V

3.0

3/32

3.3 lbs

- Separate counterweight design reduces vibration for improved comfort
- Rubber overmold in all of the critical areas of the sander
- Improved dust-sealed switch to protect against dust ingestion for longer switch life
- Improved dust collection and one-handed locking dust bag
- Dust port is designed to fit directly to the DWV010 or DWV012 dust collectors
- To attach dust port to other vacuum systems with 1-1/4" hoses, use DWV9000 Universal Quick Connector

Model No. NKD609

Mfg. No. DWE6421 Price/Each \$

SPECIFICATIONS

Sand Paper Size:	5"
Voltage:	120 V
Amps:	3 A
Orbits per Minute:	12000
Orbit Diameter:	3/32"
Pad Type:	Hook & Loop
Tool Height:	140 mm
Tool Weight:	2.9 lbs.



Variable Speed Sanders

- Motor is located over platen for maximum performance and perfect balance
 - Variable-speed dial is conveniently placed on the handle,
- allowing belt speed adjustment from 850 to 1300 SFPM Fingertip belt-tracking knob for quick, accurate belt adjustments, quick release belt change lever
- Includes: 100 g ceramic aluminium oxide belt and dust bag assembly

Model No. TF258 Mfg. No. 352VS Price/Each \$

SPECIFICATIONS

Belt Size: Voltage: Amperage: Surface Feet per Minute: **Tool Weight:**

3" x 21' 120 V 8.0 850 - 1300 10.75 lbs

PORTER+CABLE

PORTER·CABLE

1-800-661-2400

www.tenaquip.com