



Oscillating Spindle Sanders

- Designed for intricate contour sanding operations
- Heavy-duty cast-iron table is precision ground
- Rubber drum can be fitted on both ends for full use of the entire spindle
- 4" dust chute for dust collector hook-up
- Comes standard with set of 10 removable spindles, in sizes 1/4" x 5", 3/8" x 6", 1/2" x 6", 5/8" x 6", 3/4" x 9", 1" x 9", 1 1/2" x 9", 2" x 9", 3" x 9" and 4" x 9" included
- Table tilts 45° down, and 20° up
- Includes 3 table inserts

Model No.	TS213
Mfg. No.	KC-OVS-FX3
Oscillations/minute:	72
Oscillations stroke:	1 1/2"
Spindle drum length:	10 (5" to 9")
Spindle drum dia.:	1/4" to 4"
Spindle speed:	1720 RPM
Table size:	25" x 25"
Motor:	11 A @ 110 V, 5.5 A @ 220 V
Voltage:	110/220 V, 1 phase, 60 Hz
Pre-wired at:	110 V
Dimensions:	25" L x 25" W x 35 3/4" H
Weight:	275 lbs.
Price/Each	\$



Oscillating Spindle Sanders

- Table may be tilted front downwards up to a maximum of 45° to allow the sanding of bevelled parts
- Heavy-duty cast iron table is precision ground
- Rubber drum can be fitted on bothends for full use of the entire spindle
- Includes: 3 spindles (1/4", 1/2", 5/8"), 2 drums (1 1/2" and 2"), plastic dust hood, 2" dust outlet and a graduated scale attached to table

Model No.	TS212
Mfg. No.	KC-OVS-TL
Oscillations/minute:	100
Oscillations stroke:	1/2"
Spindle drum diameter:	1 1/2" - 2"
Spindle dia.:	1/4", 1/2", 5/8"
Spindle speed:	1720 RPM
Table size:	14 3/4" x 14 3/4"
Motor:	7.5 A
Voltage:	110 V, single phase, 60 Hz
Dimensions:	14" L x 14 1/2" W x 18 1/2" H
Weight:	67 lbs.
Price/Each	\$



Belt Disc Sanders

- Motors are all sealed ball bearing construction
- Comes with adjustable tilting tables
- Easy belt tracking system for quick changing of belts
- Handles finishing operations including sanding, surfacing, grinding, cleaning and deburring on wood, metal and plastic



Model No.	BV495
Mfg. No.	KC-705L-6
Belt size:	4" x 36"
Belt lift:	0° - 90°
Belt speed:	2000 SFPM
Disc diameter:	6"
Disc speed:	3450 SFPM
Motor:	5.2 A
Voltage:	110 V, 1 phase, 60 Hz
Dimensions:	17" L x 14" W x 11" H
Weight:	42 lbs.
Price/Each	\$



Belt Disc Sanders

- Motors are all sealed ball bearing construction
- Comes with adjustable tilting tables
- Easy belt tracking system for quick changing of belts
- Handles finishing operations including sanding, surfacing, grinding, cleaning and deburring on wood, metal and plastic



Model No.	TBW148
Mfg. No.	KC-702C
Belt size:	1" x 30"
Belt lift:	0° - 45°
Belt speed:	2000 SFPM
Disc diameter:	5"
Disc speed:	2800 SFPM
Motor:	2.5 A
Voltage:	110 V, 1 phase, 60 Hz
Dimensions:	14 1/2" L x 12 1/2" W x 14" H
Weight:	26 lbs.
Price/Each	\$



6" x 48" Belt & 12" Disc Sanders

- Heavy-duty cast iron tables and body
- Steel plate covered with graphite to reduce friction for longer belt life
- Adjustable belt unit operates vertically, horizontally, or at any set angle in between
- Includes: 2 - 4" dust chutes, sturdy cabinet stand, quick belt release mechanism and mitre gauge



Model No.	WK947
Mfg. No.	KC-788FX
Belt size:	6" x 48"
Belt lift:	45° down - 45° up
Belt speed:	1570 SFPM
Disc diameter:	12"
Disc speed:	2000 RPM
Disc adjustment:	45° down - 45° up
Motor:	1.5 HP belt-drive
	13.4 A @ 110 V/6.7 A @ 220 V
Voltage:	110/220 V, 1 phase, 60 Hz
Pre-wired at:	110 V
Dimensions:	30" L x 23" W x 55" H
Weight:	215 lbs.
Price/Each	\$

