



1/4" Air Screwdrivers

- Durable steel body
- Forward-reverse switch
- Low noise, low vibrations
- Overall length: 7 1/2"
- Weight: 2.4 lbs.



Model No.	TLV495
Air Consumption	6 CFM
Air Inlet:	1/4"-18 NPT
Sound Level (dBA)	82
No Load RPM	1800
Torque Range ft.-lbs.	3.75-9.5
Hose Size	3/8" (9.5 mm)
Horse Power	0.5
Vibrations Less than m/s²	0.7
Price/Each	\$



Direct Drive Reversible Screwdriver



Model No.	UAG274
Mfg. No.	GS-1017Q
Clutch Type	Keyless / Direct Drive Reversible
Handle style	Pistol grip
Operation	Trigger start
Torque range	216-312 in.-lbs.
Length	5.6" (142 mm)
Weight	1.98 lbs (0.9 kg)
Air Consumption	28 CFM
Air Inlet	1/4" NPTF
Air Hose Bore	3/8"
Sound Level (dBA)	88
Vibration Level	<2.5 m/s ²
Price/Each	\$



Direct Drive Reversible Screwdrivers

- Suitable for variable torque
- High speed fast screw rundown
- Ergonomic pistol grip improves operator comfort and productivity

Model No.	TLZ339
Mfg. No.	CP2755
Clutch Type	Direct drive reversible
Handle style	Pistol grip
Operation	Trigger start
Free Speed	2200 RPM
Output	Hex. 1/4"
Torque range	124 in.-lbs.
Length	6.3"
Weight	2.27 lbs.
Air Flow	29 CFM
Air Inlet	1/4" NPTF
Air Hose Bore	3/8"
Sound Level	90 dBA
Vibration Level	<2.5 m/s ²
Price/Each	\$



Positive Clutch Reversible Screwdrivers

- Quick change chuck
- Operator can force clutch engagement for higher torque
- Reverse control at the trigger
- Good for prevailing torque applications
- High speed and high torque

Model No.	TLZ340
Mfg. No.	CP2780
Clutch Type	Positive clutch
Handle style	Pistol grip
Operation	Trigger start
Free Speed	2100 RPM
Output	Hex. 1/4"
Torque range	133 in.-lbs.
Length	6.46"
Weight	2.35 lbs.
Air Flow	29 CFM
Air Inlet	1/4" NPTF
Air Hose Bore	3/8"
Sound Level	89 dBA
Vibration Level	26.8 m/s ²
Price/Each	\$



19 Series - Stall Screwdrivers

- Tool weight: 1.16 lbs.
- Tool length: 5.9"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- Trigger start
- "P" handle style
- Interchangeable soft-touch grip sizes
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless



Model No. TYN249
Mfg. No. 19PTS04Q
Price/Each \$



19 Series - Pistol Grip Screwdrivers w/Adjustable Torque Settings

- Tool weight: 1.41 lbs.
- Tool length: 8.0"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Class-leading accuracy and repeatability
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- "P" handle style
- Interchangeable soft-touch grip sizes
- Trigger and Push & Trigger start
- External torque adjustment from 10 - 40 in.-lbs.
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless



Model No. TYN248
Mfg. No. 19PTA04Q
Price/Each \$

