



Utility Hammers

- Ideal for structural maintenance and repair
- Air Consumption: 25 CFM
- Air Inlet: 1/4" NPTF
- Sound Level (dBA): 100



UAG272



UAG273



| Model No. | Mfg. No. | BPM | Bore & Stroke | Cold Rivet Capacity | Head Material | Overall Length | Chisel Shank | Bore Diameter | Price /Each |
|-----------|-----------|------|---------------------------------|---------------------|---------------|-------------------|----------------|--------------------|-------------|
| UAG272 | GS-0809BR | 3000 | 3/4" x 2-5/8" (19.0mm x 66.0mm) | 1/4" (6.4 mm) | Steel | 7-1/2" (190 mm) | 0.401" (Round) | 3/4" ID (19.05 mm) | |
| UAG273 | GS-0809AR | 2200 | 3/4" x 3-5/8" (19.0mm x 92.0mm) | 5/16" (7.9 mm) | Steel | 9-13/16" (250 mm) | 0.401" (Round) | 3/4" ID (19.05 mm) | |

Utility Hammers

For light to medium duty chipping, trimming, riveting, cutting, piercing & peening jobs

- Aluminum body
- 2 5/8" stroke (TG087), 3 1/2" stroke (TG088)
- Piston air-cushioned on return stroke
- 1/4" (NPTF) air inlet
- 3/8" minimum air hose size



TG087



TG088



| Model No. | Mfg. No. | Capacity Cold Rivets in. (mm) | | Bore and Stroke in. (mm) | Blows per Minute | Rivet Set and Chisel Shank | CFM | dBA | Vibration m/s ² | Overall Length in. (mm) | Net Weight lbs. (kg) | Price /Each |
|-----------|----------|-------------------------------|------------|--------------------------|------------------|----------------------------|-----|-----|----------------------------|-------------------------|----------------------|-------------|
| | | Dural | Steel | | | | | | | | | |
| TG087 | CP7111 | 1/4 (6.4) | 3/16 (4.8) | 3/4 x 2 5/8 (19 x 67) | 3000 | 0.401 (10.19 mm) | 25 | 100 | 8.9 | 6 3/4 (171) | 3 1/2 (1.6) | |
| TG088 | CP7150 | 5/16 (7.9) | 1/4 (6.4) | 3/4 x 3 1/2 (19 x 89) | 2300 | 0.401 (10.19 mm) | 25 | 100 | 9.4 | 8 7/8 (225) | 4.2 (1.9) | |

Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

Short Barrel Air Hammer

- Ideal for exhaust and front-end jobs, general bolt cutting, pin driving, and body shearing work
- Anti-vibration feature reduces tool vibration
- Ergonomic grip provides comfort for extended use
- Quick-change retainer allows for faster chisel changeovers
- BPM: 3500



| Model No. | Mfg. No. | Air Consumption | Air Inlet | Sound Level (dBA) | Bore & Stroke | Price /Each |
|------------------|----------|-----------------|-----------|-------------------|----------------------------------|-------------|
| BARE TOOL | | | | | | |
| UAJ235 | 123MAX | 24.1 CFM | 1/4" NPT | 105.7 | 3/4" x 2-5/8" (19.05mm x 66.8mm) | KIT |
| UAJ386* | 123MAXK | 24.1 CFM | 1/4" NPT | 106 | 3/4" x 2-1/2" (19 mm x 89 mm) | |

*Includes: Tool, Quick change retainer, and 5-piece chisel set.

Air Hammer

- Great for exhaust and front-end jobs, general bolt cutting, pin driving and body shearing work
- Optimized for the vehicle repair industry, heavy trucks, and MRO
- BPM: 2530



| Model No. | Mfg. No. | Air Consumption | Air Inlet | Sound Level (dBA) | Bore & Stroke | Price /Each |
|------------------|----------|-----------------|-----------|-------------------|-------------------------------|-------------|
| BARE TOOL | | | | | | |
| UAJ387 | 119MAX | 23.8 CFM | 1/4" NPT | 106 | 3/4" x 3-1/2" (19 mm x 89 mm) | |
| KIT | | | | | | |
| UAJ388* | 119MAXK | 23.8 CFM | 1/4" NPT | 106 | 3/4" x 3-1/2" (19 mm x 89 mm) | |

*Includes: Tool, Quick change retainer, and 5-piece chisel set.