



### Dynastraight® Air Powered Abrasive Finishing Tools

- Ideal set-up for Dynacushion® wheel (not included)
- Threaded arbor (5/8" -11) for exclusive use with Dynacushion® pneumatic wheel
- Shown with optional pneumatic wheel

**Model No.** TGY774  
**Mfg. No.** 13505  
**Abrasive Information:** 15-1/2" long x 3-1/2" wide Dynacushion® belts (394 mm x 89 mm)  
**Air Flow Rate @ 90 PSI:** 44 SCFM  
**Sound Level:** 88 dB (A)  
**Horsepower:** 1.00 HP  
**Free Speed:** 3400 RPM  
**Air Pressure:** 90 PSI  
**Air Inlet Thread:** 3/8 NPT  
**Hose Size (I.D.):** 3/8" (10 mm)  
**Threaded Arbor:** 5/8" - 11 male  
**Tool Spindle Thread:** 1/2" - 20 male  
**Length:** 14 7/8" (378 mm)  
**Height:** 1 7/8" (48 mm)  
**Weight:** 4 lbs. (1.82 kg)  
**Price/Each:** \$



### Dynisher® Finishing Tools

- Excellent for blending and finishing stainless steel and most other metals, leaving an in-line pattern
- Includes: 3/4" dia. arbor for mounting a variety of abrasives & accessories
- Shown with optional Dynacushion® pneumatic wheel not included

**Model No** TGY767  
**Mfg. No.** 13450  
**Abrasive Information:** 3-1/2"(84 mm) x 15-1/2"(394 mm) abrasive belts 4" dia. (102 mm) Abrasive flap wheels 4" (102 mm) dia. conditioning discs  
**Air Flow Rate @ 90 PSI:** 42 SCFM  
**Sound Level:** 80 dB (A)  
**Horsepower:** 1.00 HP  
**Free Speed:** 2800 RPM  
**Air Pressure:** 90 PSI  
**Air Inlet Thread:** 3/8 NPT  
**Hose Size (I.D.):** 3/8" (10 mm)  
**Max. SFPM:** 3665 SFPM  
**Arbor Information:** 3/4" x 2 5/16" (19 mm x 59.5 mm)  
**Length:** 15" (381 mm)  
**Height:** 7" (178 mm)  
**Weight:** 5.7 lbs. (2.59 kg)  
**Price/Each:** \$



### Dynisher® Finishing Tool Versatility Kits

- Excellent for blending and finishing stainless steel and most other metals, leaving an in-line pattern
- Includes: 3/4" dia. Arbor for mounting a variety of abrasives & accessories
- Shown with optional Dynacushion® pneumatic wheel, not included

**Model No** TGY768  
**Mfg. No.** 13460  
**Abrasive Information:** 3 1/2"(84 mm) x 15-1/2"(394 mm) Abrasive belts. 4"(102 mm) dia. Abrasive flap wheels. 4"(102 mm) dia. conditioning discs  
**Air Flow Rate @ 90 PSI:** 41 SCFM  
**Sound Level:** 84 dB (A)  
**Horsepower:** 1.00 HP  
**Free Speed:** 2800 RPM  
**Air Pressure:** 90 PSI  
**Air Inlet Thread:** 3/8 NPT  
**Hose Size (I.D.):** 3/8" (10 mm)  
**Max. SFPM:** 3665 SFPM  
**Arbor Information:** 3/4" x 2 5/16" (19 mm x 59.5 mm)  
**Length:** 15" (381 mm)  
**Height:** 7" (178 mm)  
**Weight:** 5.7 lbs. (2.59 kg)  
**Price/Each:** \$



### 3" 7 Degree Offset Rotary Buffer

**Model No.** TGY961  
**Mfg. No.** 51401  
**Air Consumption:** 24 CFM  
**Sound Level (dBA):** 75  
**No Load RPM:** 5000  
**Diameter of Pad:** 3"  
**Power HP:** 0.4  
**Hose Size (I.D.):** 3/8"  
**Tool Spindle Thread:** 3/8"-24 Male  
**Length:** 8.75"  
**Height:** 4.25"  
**Weight:** 1.716 lbs.  
**Price/Each:** \$



### 3" 7 Degree Offset Disc Sander

- Removable side handle
- Includes Locking-Type Pad (3" diameter)

**Model No.** TGZ137  
**Mfg. No.** 52412  
**Air Consumption:** 36 CFM  
**Sound Level (dBA):** 90  
**No Load RPM:** 20000  
**Diameter of Pad:** 3"  
**Power HP:** 0.7  
**Hose Size (I.D.):** 3/8"  
**Tool Spindle Thread:** 3/8"-24 Male  
**Length:** 6"  
**Height:** 5.5"  
**Weight:** 2.2 lbs.  
**Price/Each:** \$

