

30° Free Angle Fittings

- · Prevents kinking and tangling of hoses
- Reduces operator fatigue by allowing better tool maneuverability
- Reduces tension put on wrist, hand, elbow and shoulder by the heavy hose
- Free angle fittings rotate 360° and up to 30° of deflection of air tool supply line
- Max working pressure 140 PSI



TOPRING

Model No	Mfg. No.	Description	Price/Each
TGA770	62.350C	1/4 (M) NPT x 1/4 (M) NPT	
TGA771	62.355C	1/4 (F) NPT x 1/4 (M) NPT	
TGA772	62.360C	1/4 industrial type x 1/4 (M) NPT	
TGA773	62.365C	ARO 210 type x 1/4 (M) NPT	

Hose Whips

- Easy tool manipulation
- Increases the lifespan of the connector and the main pipe
- Lightweight
- Excellent abrasion resistance

Application

TLV351

 Used between the air tool and quick coupler to act as a "shock absorber" and to prolong the life of the coupler

45 ad to retain	
TLV350	190
RI AND	

TOPRING

1/4

a shoci	(absorber and	a to prolong t	ine me or the	coupici –		
Model	Mfg.	Hose	0.A.	Inlet	Rigid Fitting	Price
No.	No.	I.D."	Length"	(M) NPT	(F) NPT	/Each
TIVZEO	62 522	1//	10	1//	1//	

Air Tool Swivel Connectors

- Improve tool manoeuvrability, minimizes operator's fatigue and extends hose life
- Universal joint that connects portable air tools to an air line
- 360° Swivel at two locations which allows an air hose to drop directly to the floor, no matter how the tool is held

WARNING: Not to be used on percussion tools or in areas of high mechanical abuse

Applications

- For use with most air tools such as: Grinders - Sanders - Staple guns -Drills - Buffers - Spray guns - Glue guns
- Drills Buffers Spray guns Glue gunsMaximum working pressure: 150 PSI



TOPRING

Model No.	Mfg. No.	Port Size NPT	Maximum Air Flow SCFM	Wt. Ibs.	Price /Each
UAD500	62.720	1/4	30	0.28	
TA874	62.704C	1/4	33	0.2	
TA876	62.708	1/2	65	0.8	

Swivel Connectors with Flow Control

- Swivels 360° which allows air hose to drop straight to the floor, no matter how the tool is held
 Integrated air-flow control dial
- Maximum working pressure: 150 PSI

WARNING: Not to be used on percussion tools or in areas of high mechanical abuse



Model No.	Port Size NPT	Price/Each



Air Manifolds

Eliminates the need to connect and disconnect each time the tool is changed.

AIR MANIFOLD (3-IN-1)

- Supplies 3 air tools from a single inlet
- Compact design
- · Aluminum construction



Model No.	Mfg. No.	Inlet	Outlet	Price/Each
TZ246	62.800C	1/4 (F) NPT	1/4 (F) NPT	
TZ247	62.805C	3/8 (F) NPT	1/4 (F) NPT	

TOPRING

AIR MANIFOLD (2-IN-1)

- Supplies 2 air tools from a single inlet
- Compact design
- Nickel brass construction



Model No.	Mtg. No.	Inlet	Outlet	Price/Each
TZ248	62.850C	1/4 (F) NPT	1/4 (F) NPT	
TZ249	62.860C	1/4 (M) NPT	1/4 (F) NPT	

Air Tool Swivel Connectors

- Universal connector that connects portable air tools to an air line
- Improve tool maneuverability, minimize operator fatigue and extends hose life
- Swivel 360° at two pivot points, allowing the air hose to drop directly to the floor



TOPRING

Model No.	Mfg. No.	Thread NPT	Description	Price/Each
TLZ018	62.705C	1/4	Swivel only	

Pneumatic Lockouts

- Prevents fitting from being connected to a pressurized air source
- · Stainless steel construction
- Fits virtually all pneumatic fittings in manufacturing facilities

Model No. TLZ098 Mfg. No. \$3900 Price/Each \$



