



1.6 Continuous HP, 4.5-Gallon Electric Wheeled Portable Compressors

- Vertical stand feature allows a user to transport or store compressor in a vertical position
- 78 dBA (tested per ISO3477) operational noise level for a quieter work environment
- 10" non-flat foam tires allow for easy transportation around the jobsite
- Oil free, maintenance free pump, for convenient use
- High flow coupler allows for maximum nailer performance
- Metal console panel provides gauges, couplers and regulators

Model No. TLV990 Mfg. No. D55146
Price/Each \$

Horsepower: 1.6 HP
Tank Size: 4.5 Gal
Power Supply: 120V
CFM @ 100 PSI: 5.2
Max PSI: 175
Dimensions: 33.5" L x 23" W x 15" H
Weight: 83 lbs.



0.3 Continuous HP 1-Gallon Single Tank Hand Carry Compressors

- 0.75 SCFM delivered @ 90 PSI pump, 1.0 gallon tank and 135 max PSI enables more nails to be fired and provides quicker recovery
- Durable oil-free pump provides extended maintenance-free operation
- Low 71 dBA* allows for quieter operation (*Tested per ISO3744)
- Roll cage and control panel provide protection to key compressor components
- Low 2.6 amp draw motor provides easy start-up and reduces breaker tripping
- Ball valve drain allows for quick and thorough tank draining
- One quick coupler to easily support 1 nailer
- High-flow regulator for increased performance

Model No. TJZ977 Mfg. No. D55140
Price/Each \$

Drive: Belt drive
Horsepower: 0.3 continuous HP
Tank Size: 1.0 gal.
Power Supply: 120 V, 10 A, 60 Hz, universal motor
CFM @90 PSI: 0.75 CFM
Pump Speed: 2200 RPM
Dimensions: 19" L x 14.5" W x 9" H
Weight: 29 lbs.



Continuous Wheeled Air Compressor

- Cast iron cylinder enhances pump life
- High-flow regulator for increased performance
- Oil lubricated pump improves durability
- Dual soft start valves assist in cold weather start-up
- Top load panel with positioning holes allows unit to transport loads up to 100 lbs
- Run multiple tools from dual universal quick couplers
- Ball valve drain allows for quick and thorough tank draining
- Features 10" pneumatic wheels and handle for ease of mobility
- Electric/Gas: Electric



TJZ976



Model No.	Mfg. No.	Horse Power	CFM	Voltage /Phase	Tank Capacity	Max. PSI	Sound Level (dBA)	Pump Speed	Height"	Length"	Width"	Weight lbs.	Wheel Diameter"	Price /Each
TJZ976	D55154	1.1 HP	3.2 at 125 PSI 4 at 90 PSI 4.2 at 60 PSI 4.6 at 40 PSI	120/2	4 Gal. (4.8 US Gal)	125	83	3400 RPM	23	22	18-1/2	87	10	
TLV988	D55167	1.6 HP	4.8 at 100 PSI	120/1	15 Gal. (18 US Gal)	225	78	1750 RPM	30	39.63	16.5	83	2	
TLV989	D55168	1.6 HP	5 at 100 PSI	120/1	15 Gal. (18 US Gal)	225	78	1750 RPM	44-3/4	24-1/2	22	92	2	

Portable Continuous Compressor

- Cast iron cylinder enhances pump life
- High-flow regulator for increased performance
- Oil lubricated pump improves durability
- Lightweight design for easy use and handling in a variety of orientations
- Dual soft start valves assist in cold weather start-up
- Horse Power: 1.1 HP
- CFM: 3.2 at 100 PSI
- Electric/Gas: Electric
- Voltage/Phase: 120/2
- Tank Capacity: 4 Gal. (4.8 US Gal)
- Max. PSI: 125
- Sound Level (dBA): 83
- Tank Configuration: Stacked
- Pump Speed: 3400 RPM
- Height: 16-3/4"
- Length: 18-1/2"
- Width: 15"
- Weight: 53.32 lbs.

Model No. TSW649
Mfg. No. D55151
Price/Each \$



SAFETY PRODUCTS FOR INDUSTRY