



Ultra-Quiet Oil-Free Air Compressor

- Durable oil-free pump with minimal maintenance
- Twin cylinder pump for faster air recovery
- ASME safety valve
- Thermal overload protector
- Dual 1/4" universal 'one touch' quick connect couplers allow user to connect up to 2 air tools
- Air pressure regulator and large easy to read pressure gauges
- 6-3/4" wheels and handle for portability
- Horse Power: 3 HP
- CFM: 4.4 at 90 PSI/5.6 at 40 PSI
- Electric/Gas: Electric
- Voltage/Phase: 120/1
- Tank Capacity: 10 Gal. (12 US Gal)
- Max. PSI: 125
- RPM: 1680
- Assembled Dimensions: 18-1/2" L x 17-3/4" W x 32-5/8" H
- Weight: 86 lbs.

Model No. UAJ180
Mfg. No. KC-10020SQ
Price/Each \$



Ultra-Quiet Oil-Free Air Compressor

- Durable oil-free pump with minimal maintenance
- ASME safety valve
- 1/4" universal 'one touch' quick connect coupler
- Large air pressure regulator and large easy to read pressure gauges
- Horse Power: 0.75 HP
- CFM: 1.2 at 90 PSI/1.8 at 40 PSI
- Electric/Gas: Electric
- Voltage/Phase: 120/1
- Tank Capacity: 1 Gal. (1.2 US Gal)
- Max. PSI: 125
- Sound Level (dBA): 60
- RPM: 1720
- Assembled Dimensions: 13-3/4" L x 12-1/2" W x 13" H
- Weight: 26 lbs.

Model No. UAJ181
Mfg. No. KC-1410A
Price/Each \$



Oil-Free Air Compressor

- Durable oil-free pump with minimal maintenance
- ASME safety valve
- Dual 1/4" universal 'one touch' quick connect couplers allow user to connect up to 2 air tools
- Twin cylinder pump for faster air recovery
- Extra long life pump of over 3000 hours
- Lightweight aluminum tank
- Thermal overload protector
- Large air pressure regulator and large easy to read pressure gauges
- Horse Power: 2 HP
- CFM: 2.35 at 90 PSI/3.8 at 40 PSI
- Electric/Gas: Electric
- Voltage/Phase: 120/1
- Tank Capacity: 2 Gal. (2.4 US Gal)
- Max. PSI: 125
- RPM: 1680
- Sound Level (dBA): 60
- Assembled Dimensions: 17" L x 14-3/4" W x 16-1/4" H
- Weight: 36 lbs.

Model No. UAJ182
Mfg. No. KC-2020A
Price/Each \$



Industrial Compressors

- 2-cylinder cast iron single stage oil lubricated pump
- ASME registered tank and safety valve
- Large intake filters
- Pump with V-style design minimizes vibration, improves cooling and extends compressor life
- Portable units are equipped with 9 1/2" pneumatics wheels and front handle
- Gas units are equipped with a 4-stroke air cooled OHV Honda gas engine
- Gas powered
- Horse Power: 5.5 HP
- CFM: 11.2 at 90 PSI
- Electric/Gas: Gas
- Tank Capacity: 10 Gal. (12 US Gal)
- Max. PSI: 150
- Air Delivery CFM- 40 PSI: 14.1
- Tank Size (gal.): 10(2x5)
- Pump RPM: 3600
- Wt. lbs.: 165
- Remarks: Twin Horizontal

Model No. TLV741
Mfg. No. KC-5510G1
Price/Each \$



Wheelbarrow Air Compressor

- Powerful, 6.5 HP, 4-stroke, air-cooled OHV gas engine
- Engine slow-down control reduces operating costs and unnecessary wear
- 2 cylinders "V" style cast iron single stage oil lubricated pump
- Belt drive with sturdy metal belt guard
- Dual 1/4" universal "one touch" quick-connect couplers
- 10" wheel and carry handles for easy maneuverability
- Horse Power: 6.5 HP
- CFM: 11.2 at 90 PSI
- Electric/Gas: Gas
- Tank Capacity: 10 Gal (12 US Gal)
- Max. PSI: 150
- Engine load speed: 3600 RPM
- Displacement (CC): 196
- Fuel: Unleaded gasoline
- Fuel tank (L): 3.6

Model No. UAD698
Mfg. No. KC-6510G1
Price/Each \$

