



Filters/Regulators/Lubricators (Gauge Included)

- High-flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- **Heavy-Duty:** High-capacity performance featuring rugged design for the most demanding applications

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA689	1/4	31	150	0-125	125	Manual	Polyurethane	1.5	7 1/16	4 25/32	
TA690	1/4	31	150	0-125	125	Auto	Polyurethane	1.5	7 1/16	4 25/32	
TA693	1/4	23	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	
TA694	1/4	23	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	
TA697	3/8	45	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	
TA698	3/8	45	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	
TA701	1/2	60	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	
TA702	1/2	60	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	
TA703	1/2	60	250	0-125	150	Manual	Zinc	3.8	8 1/16	6 35/64	
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA705	1/2	110	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	8 1/16	
TA706	1/2	110	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	8 1/16	
TA709	3/4	125	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	8 1/16	
TA710	3/4	125	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	8 1/16	
HEAVY-DUTY, 5-MICROMETRES FILTRATION											
TA713	1	240	250	0-125**	125	Manual	Zinc	16	11	15 3/4	
TA714	1	240	175	0-125**	125	Auto	Zinc	16	11	15 3/4	
TA717	1 1/2	400	250	0-125**	125	Manual	Zinc	16	11 11/32	16 1/2	
TA718	1 1/2	400	175	0-125**	125	Auto	Zinc	16	11 11/32	16 1/2	

*Also available 0-25 PSI, 0-60 PSI, 0-250 PSI **Also available 0-250 PSI



Compact Design w/Polyurethane Bowl
TA689



Compact Design w/Zinc Bowl
TA703



Heavy-Duty Design w/Zinc Bowl
TA713

Filters/Regulators & Coalescing Filters (Gauge Included)

- High-flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- Lightweight construction for ease of installation

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA743	1/4	20	150	0-125	125	Manual	Polyurethane	1.5	7 3/64	3 13/64	
T2031	1/4	20	150	0-125	125	Auto	Polyurethane	1.5	7 3/64	3 13/64	
TA745	1/4	40	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA746	1/4	40	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA747	1/4	40	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	
TA748	1/4	40	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	
TA749	3/8	43	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA750	3/8	43	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA751	3/8	43	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	
TA752	3/8	43	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	
TA761	1/2	43	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA762	1/2	43	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	
TA763	1/2	43	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	
TA764	1/2	43	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA753	1/2	85	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	5 3/8	
TA754	1/2	85	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	5 3/8	
TA755	1/2	85	250	0-125*	150	Manual	Zinc	8.5	10 21/64	5 3/8	
TA756	1/2	85	175	0-125*	125	Auto	Zinc	8.5	10 21/64	5 3/8	
TA757	3/4	85	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	6 1/16	
TA758	3/4	85	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	6 1/16	
TA759	3/4	85	250	0-125*	150	Manual	Zinc	8.5	10 21/64	6 1/16	
TA760	3/4	85	175	0-125*	125	Auto	Zinc	8.5	10 21/64	6 1/16	

*Also available 0-25 PSI, 0-60 PSI, 0-250 PSI



TA743

Compact Design w/ Polyurethane Bowl



TA745

Compact Design w/Polyurethane Bowl and Guard