



### Hammer-On Lugs

- Manufactured from heavy wall cast copper alloy, annealed for maximum conductivity
- Fast, easy installation, just slide into cable and strike it with hammer for durable connection



Model No.	For AWG Cable Sizes	Price /Each	Qty	Qty Price /Each
NT606	1 - 4			
NT605	1/0 - 2/0			
NT604	3/0 - 4/0			

### Solder/Crimp Lugs

- Manufactured from heavy wall copper alloy, annealed for maximum conductivity
- Long length and flared ends make installation fast and easy



Model No.	For AWG Cable Sizes	Price /Each	Qty	Qty Price /Each
TTU567	1 - 4			
PB131	3/0 - 4/0			

### ToughFlex™ Welding Cable

- Industry's best selling welding cable
- Durable and flexible
- Highly flexible annealed 30 (0.010) gauge bare copper conductor, insulated with an EPDM jacket and paper separator
- Durable jacket resists cuts, tears, abrasion, grease, oil, water and flame
- Operating temperature range: -50°C to 105°C (-58°F to 221°F)
- Rated to 600 V
- Ideal for any welding application that requires leads, grounds, and stinger/whips
- Custom lengths and jacket colours available upon request
- **Sold per spool or boxed**



TLV126



TLV134



### KALAS

#### CABLE SPECS:

Gauge	Stranding	O.D."	Average Wall"	Weight lbs./1000'	Resistance OHMS/1000'
#6	259/0.010	0.320	0.060	113	0.406
#4	364/0.010	0.348	0.060	147	0.287
#2	624/0.010	0.420	0.060	236	0.167
#1	780/0.010	0.503	0.080	313	0.137
1/0	988/0.010	0.533	0.080	378	0.110
2/0	1235/0.010	0.586	0.080	463	0.086
3/0	1539/0.010	0.625	0.080	563	0.070
4/0	2014/0.010	0.720	0.080	734	0.055

#### AMPACITY GUIDE:

GAUGE	50'	75'	100'	125'	150'	175'	200'	225'	250'	300'	350'
#4	100	100	-	-	-	-	-	-	-	-	-
#3	150	-	-	-	-	-	-	-	-	-	-
#2	200	150	100	100	-	-	-	-	-	-	-
#1	250/300	200	150	-	100	-	-	-	-	-	-
1/0	350	250	200	150	-	100	100	-	-	-	-
2/0	400/450	300	250	200	150	-	100	100	-	-	-
3/0	500	350/400	300	250	200	150	150	-	-	100	-
4/0	550/600	450/500	350/400	300	250	200	200	150	150	-	100

DO NOT USE for 600 volt in-line applications. Product for welding applications only. Values are nominal and approximate.

Model No.	Mfg. No.	Gauge	Price /Each
-----------	----------	-------	-------------

300' SPOOL			
TTV126	640069.A4.001	#6	P.O.A.
TTV127	640068.A4.001	#4	P.O.A.
TTV128	640067.A4.001	#2	P.O.A.
TTV129	640066.A4.001	#1	P.O.A.
TTV130	640065.A4.001	1/0	P.O.A.
TTV131	640064.A4.001	2/0	P.O.A.
TTV132	640063.A4.001	3/0	P.O.A.
TTV133	640062.A4.001	4/0	P.O.A.

50' BOXED			
TTV134	06T1050B0000	#6	P.O.A.
TTV135	04T1050B0000	#4	P.O.A.
TTV136	02T1050B0000	#2	P.O.A.
TTV137	01T1050B0000	#1	P.O.A.
TTV138	10T1050B0000	1/0	P.O.A.
TTV139	20T1050B0000	2/0	P.O.A.
TTV140	30T1050B0000	3/0	P.O.A.
TTV141	40T1050B0000	4/0	P.O.A.

100' BOXED			
TTV142	06T1100B0000	#6	P.O.A.
TTV143	04T1100B0000	#4	P.O.A.
TTV144	02T1100B0000	#2	P.O.A.
TTV145	01T1100B0000	#1	P.O.A.
TTV146	10T1100B0000	1/0	P.O.A.
TTV147	20T1100B0000	2/0	P.O.A.
TTV148	30T1100B0000	3/0	P.O.A.
TTV149	40T1100B0000	4/0	P.O.A.

**Need help?**

Have one of our qualified specialists visit you.



### High-Leverage Cable Cutters

- High-leverage jaws with shear-cut blades
- Cuts up to: 4/0 aluminum cable (not ACSR), 2/0 soft copper cable
- Plastic covered, non-slip grips
- Compact cutter fits in most tool pouches
- NOT an insulated tool
- Overall length: 9 1/2"

Model No. TBG092  
Mfg. No. 0890CSJ  
Price/Each \$

**CRESCENT H.K. PORTER**

