

<ul> <li>Insula coatir insula electr</li> <li>Resist acids</li> <li>Excell</li> <li>Oil resist</li> </ul>	D1 Rec llating ting spray for ng, impregnat ting electrica onic work s oil, water, and alkalis ent adhesion bistant per D-115-55	general ing and l and	nish		<ul> <li>Application</li> <li>Fast-(non-(-))</li> <li>Adhee</li> <li>For p tool a mach main</li> </ul>	03 Bli out D ies a smooth for all layout drying, non- etching, wor rres to metal attern-makii and die makii and die makii and die makii and die makii and die makii and control tenance nanicals	ye , even work flaking, n't peel or glass ng,			<ul> <li>Particular</li> <li>Remain of the service of the service</li></ul>	oves layout fli kly and efficie oves light olls ses, lacquer a r markings netal or glass es no residue hlorinated so ool and die m production de	OVET uids antly s, nd Ivents naking		
Model No.	Mfg. No.	Size	Price /Each	Qty Price Qty /Each	Model No.	Mfg. No.	Size	Price /Each	Qty Price Qty /Each	Model No.	Mfg. No.	Size	Price /Each	Qty Price Qty /Each
AA179	SC0601000	15.25 oz.			AA180	SC0603000	12 oz.			AA181	SC0606000	12.75 oz.		

## **Cutting Oil Thread Cutting** Lubricant

- Ideal for use on all types of metals, including brass, copper and aluminum
- NSF Registered P1



# CR©

**Coolcut**<sup>™</sup>

Extends cutting tool life

Produces a better finish

Solvent-free, no chlorine

WALTER Surface Technologies

Liquid

Liquid

Liquid

Liquid

Stick

Aerosol Spray

Trigger Spray

For drilling, sawing, milling,

turning, reaming, broaching

AA471

Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
AF250	73500	340 g		

Suitable for all ferrous and non-ferrous metals

AA468

Size

350 ml

3.78 L

20 L

208 L

300 g

400 ml

500 ml

Price

/Each

## A-9 Aluminum **Cutting Fluids**

- Designed for aluminum,
- non-ferrous metals Forms an effective extreme pressure boundary lubricant between tool and work surface
- Leaves a surface, which requires only ordinary cleaning


#### RELTON

Model		Price	Qty Price
No.	Size	/Each	Qty /Each
AA149	4 oz.		

R

# AluCut<sup>™</sup> Aluminum **Cutting Lubricant**

- High-performance lubricant that extends cutting tool life
- Specially formulated for use with aluminum and other non-ferrous metals
- Clean, precise, stain-free application Ideal for inclined, vertical,
- and overhead surfaces Coats cutting edge or workpiece
- Applications include cutting with circular chopsaws, sawing with jigsaws or portable bandsaws, drilling, nibbling, and tapping



#### Effective on tough-to-drill metals and alloys such as beryllium, molybdenum, stainless steel and stellite

Cutting Fluids

Rapid Tap<sup>™</sup>

- Makes tapping, reaming, drilling and threading operations easier, faster and more accurate
- Not recommended for use with aluminum and its alloys

## RELTON

Model		Price	Qty Price
No.	Size	/Each	Qty /Each
AA160	4 oz.		

## Coolcut<sup>™</sup> S-30 Water-Miscible Cutting Lubricant

- Ready-to-use, high-performance metal cutting lubricant specially designed for automatic and semiautomatic metal removing operations
- Will not gum up slides and glides
- Increases feed, speed, and production
- . Prevents bacterial growth when not in use
- Formulated with extended corrosion protection Contains extreme pressure additives (EP), bacterial control ingredients, and no chlorine
- Can be diluted up to 1:30



WALTER Surface Technologies

Model			Price		<b>Qty Price</b>
No.	Description	Size	/Each	Qty	/Each
AG516	Jug	3.78 L			
AF006	Jug	20 L			
AF007	Drum	208 L			

2020 © TENAQUIP Limited

AA467

Qty

**Qty Price** 

#### www.tenaquip.com

388

Model

AA468

AG673

AA470

AB748

AA471

AA467

AE955

No.



TING FI

