

Tapmatic® Edge Creme

- Excellent for vertical applications
- Biodegradable
- Can be applied to cutting tools before tapping or reaming
- For use when drilling, tapping blind holes, forming, bending, pre-coating fasteners and lubricating rubber seals
- Does not contain any hazardous chemicals
- Safe on all metals





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
ΔΔ923	C43100	11 07		

Stainlesscut™ Extreme Pressure Cutting Lubricant

- Prolongs tool life in stainless and other tough alloys
- Produces a better finish
- · Safe and pleasant to use



WALTER

Model No.	Description	Size	Price /Each	Qty	Qty Price /Each
AA509	Aerosol	400 ml			_
AA510	Squeeze Bottle	350 ml			

Tapcut™ Thread **Cutting Lubricant**

- Specially formulated for thread cutting with taps and dies
- Special anti-wear additives for thread cutting
- Nontoxic and biodegradable
- Produces clean, accurate threads
- Safe for use with alloys, aluminum, brass, copper, stainless steel, and steel



WALTER

Model No.	Description	Size	Price /Each	Qty	Qty Price /Eacl
AA445	Bottle	350 ml			

Tapmatic® #1 Gold **Cutting Fluid**

- Great for steel and aluminum
- Excellent for low speed, high pressure applications
- Minimizes torque increases
- No chlorinated paraffins, water, solvents or inactive fillers
- Aerosol provides a pinpoint stream with foaming action
- Safe on all metals
- Accepted for use in Canadian food processing facilities





Model	Mfg.		Price		ty Price
No.	No.	Size	/Each	Qty	/Each
AA775	C40312	11-oz. Aerosol			
AA776	C40320	16 oz.			
AB565	C40330	1 gal.			
AR563	C40340	5 gal			

Tapmatic® Tricut **Cutting Fluid**

- · Excellent for stainless steel and other hard to machine metals
- Not recommended for aluminum
- Provides, smooth,
- accurate cutting action
- Flows directly to cutting edge
- Extends tool life
- Reduces friction
- Suitable for high and low speed applications
- Non-corrosive to steel





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
AA779	C05316	16 oz.		
AB578	C05328	1 gal.		

Tapmatic® Edge Lube

- White, solid waxy bar
- Excellent for belt, wheel and disc grinding or sawing applications
- Eliminates heat build-up and belt loading
- No hazardous chemicals Extends grinding wheel life
- Low toxicity
- Safe on all metals
- Biodegradable





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
AA922	C43200	13 oz.		

Tapmatic® Aquacut **Cutting Fluid**

- Water-based formula
- Excellent in applications where cooling of the tool is desired
- Does not contain sulfur, chlorinated solvents, chlorine or oils
- Safe on all metals, except magnesium
- Corrosion inhibitors prevent flash rusting
- Provides fine finishes
- Cinnamon scent





Model	Mfg.		Price	Q	ty Price
No.	No.	Size	/Each	Qty	/Each
AA778	C01216	16 oz.			
AB574	C01228	1 gal.			
AB572	C01205	5 gal.			

Tapmatic® Natural **Cutting Fluid**

- Non-toxic and non-hazardous
- Biodegradable
- Does not irritate the skin. eyes or respiratory tract
- Does not contain sulfur, chlorinated solvents, chlorine water, mineral oil or inactive fillers
- Great for steel and aluminum
- High performance lubricating ability eliminates galling and seizing
- Safe on all metals





Model	Mfg.		Price	Qty Price
No.	No.	Size	/Each	Qty /Each
AA777	C44220	16 oz.		
ΔR577	C44230	1 nal		

Cimtap® II Liquid Tapping Compound

- Water-soluble, formulated for blind holds, deep vertical holes and high production operations requiring quick application
- For ferrous and non-ferrous metals



CIMCOOL

Model No.	Size	Price/Each
AB792	16-oz. Bottle	
AB789	4-L Jug	