



Workhorse™ Bender Mounting Kit

- Includes: (2) "U" brackets, (1) Bar, (2) Hook brackets



Model No.	Mfg. No.	Description	Price /Each
NIG987	555C	Workhorse™ Bender Mounting Kit	
NIF001	28008	Rigid Electric Bender Shoe Group	
NIE172	12586	PVC Electric Bender Shoe Group	
NIK260	SG4	Electric Bender Shotgun™ Shoe	
NIC909	01323	Classic Electric Bender Roller Support	
NIE841	23803	EMT Electric Bender Shoe Group	

CX Electric Bender with No Shoes

- Features simple relay controls for easy field repairs, and compact handle design to prevent interference with conduit when bending
- Conduit Size: 1/2" to 2" Rigid, EMT, IMC, & PVC Coated Rigid
- Voltage Rating: 120 VAC
- Amperage Rating: 20 Amp GFCI-Protected Receptacle
- Storage/Operating Temperature: -5° to 120° F
- Relative Humidity: 0 - 98%



Model No.	Mfg. No.	Description	Price /Each
NIG988	555CX	CX Electric Bender with No Shoes	
NIF001	28008	Rigid Electric Bender Shoe Group	
NIE296	13856	IMC Combination Form Roller Unit for Electric Bender	
NIE358	13934	EMT Electric Bender Shoe Group	
NIE172	12586	PVC Electric Bender Shoe Group	
NIK260	SG4	Electric Bender Shotgun™ Shoe	

Single Shoe Electric Conduit Bender

- Single versatile shoe bends 1/2" to 2" EMT, IMC and Rigid conduit
- Absolute encoder stops bending at precise angles
- Solid state electronics rated for 1 000 000+ bends
- Simple switching between vertical and horizontal bending configurations
- Digital pendant sets angle and monitors process
- Solid state system eliminates arcing and prevents damage from temporary power loss
- Features 1/2" - 2" rigid/EMT/IMC shoe, roller support, and digital pendant
- Bend Radius: 4-1/4" - 9"
- Amperage Rating: 20 A GFCI-Protected Receptacle
- Voltage Rating: 120 VAC



Model No.	Mfg. No.	Description	Price /Each
NIH772	854DX	Single Shoe Electric Conduit Bender	
NID311	02840	PVC Electric Bender Shoe Group	
NIK261	SG4-854	Electric Bender Shotgun™ Shoe Group	

Programmable Electric Conduit Bender

- Easy to use LCD interface programs 7 different bends with ability to save 3 locally, or unlimited number to USB memory stick
- Bend 3/4" Rigid & 1 - 2" EMT/IMC/Rigid with no loose parts
- Quick pivot for changing between vertical and horizontal orientations
- Avoid scrap and speed bending with the patent pending auto conduit size and conduit type smart sensors
- Superior portability, stability and on-board storage via fork tubes, hoist bar, large wheels, wheel brake bar, storage box and tray
- Voltage Rating: 120 VAC
- Amperage Rating: 20 A



Model No.	Mfg. No.	Description	Price /Each
NIH773	855GX	Programmable Electric Conduit Bender	
NIE169	12582	PVC Electric Bender Shoe Group	

Need help?

Have one of our qualified specialists visit you.

