



Leak Detectors

- The UT-300 transmits an ultrasonic signal for non pressurized applications
- Tests the "air-tightness" of weather seals, tanks, ovens, refrigerators, etc.
- Locating leaks in duct work
- Finds the ends of buried PVC pipes
- Detects any pressurized gas leak regardless of type CFC's, HFC's, Nitrogen, etc. (unaffected by contaminants)
- **HN256** comes with a detector and a transmitter



HN256



Model No.	Mfg. No.	Description	Price /Each
HN256	TMULD-300	Leak Detector Kit	
HK991	ULD-300	Ultrasonic Leak Detector	
HN258	UT-300	Ultrasonic Transmitter	

BatCam 2.0 Ultrasonic & Sound Detection Cameras

- Measurement of 96 000 samples per second
- Includes distance range sensor, adjustable lighting, real-time visualization of sound, desired frequency range filtering, image averaging function and video and image storage
- Sensor (Microphone): 112 Channel Digital MEMS
- Effective Frequency Range: 2 k to 48 kHz
- Microphone Sensitivity: -41 dBFS
- Signal-To-Noise Ratio: 66 dB(A)
- Camera Frame Speed: 25 FPS
- Detection Distance: More than 0.98' (0.3 m)
- Display Type: 5" Mono-Colour LCD
- Operating Temperature: -4 to 122°F (-20 to 50°C)



Model No.	Mfg. No.	Description	Price /Each
IC545	BATCAM	Ultrasonic & Sound Detection Camera	

Ultrasonic Leak Detectors

- Locates leaks generated by pressure, vacuum, water, gas or air
- Visible (LED) and Audible (ticking) alarms assist in pinpointing leaks
- Earphone jack for loud environments (earphones included)
- User adjustable sensitivity wheel
- Ultrasonic Transmitter generates a 40 kHz signal
- Includes a reference table displaying pH vs. temperature
- Includes: Leak Detector, transmitter, headphones, carrying case and batteries
- Alert Type: Light & Sound
- Earphone Jack: Yes (Earphones included)
- Power Supply: 2 x 9V Batteries
- Operating Temperature: 32 to 104°F (0 to 40°C)



Model No.	Mfg. No.	Description	Price /Each
IB944	R9100	Ultrasonic Leak Detector	

Tru Pointe® Ultra Ultrasonic Leak Detectors

- Detects leaks of any gas type, but can also be used for thermal expansion valves, steam traps, bearings and more
- Visual and audible indicators include an LED scale and a headphone jack
- Includes: Instrument, Probe wrench, Touch probe, 6" wave guide, Folding headset, 9 V battery, User manual, Hard carrying case
- Gases Detected: All Gases
- Sensitivity: Continually Variable Slide Adjustment
- Response Time: Instantaneous
- Manufacturer's Warranty: 1 Year

IC426



Model No.	Mfg. No.	Description	Price /Each
IC426	0028-8010	Ultrasonic Leak Detector with Sound Blaster	
IC424	0028-8000	Ultrasonic Leak Detector	

Refrigerant Leak Detectors

- This refrigerant leak detector is capable of pinpointing small leaks quickly and accurately with audible and visual indicators
- Features a tricolour LED bar indicator with high and low sensitivity functions
- Features a 15" (390 mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- Features high and low sensitivity settings, a low battery indicator, and auto shut off
- User replaceable sensor
- Requires no field calibration
- Measures CFC, HCFC and HFC refrigerants
- Quick response and high accuracy detects small leaks
- Uses (4) AA batteries
- Detected Gases: CFC's (R11, R12, R13), HCFC's (R22, R502, R500), HFC's (R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds)
- Includes: (1) Refrigerant leak detector, (1) Reference leak source, (4) Batteries, (1) Hard carrying case



Model No.	Mfg. No.	Description	Price /Each
IA450	C-380	Refrigerant Leak Detector	
NJW086	C-380-NIST	Refrigerant Leak Detector w/ISO Certificate	
IB742	R8888	Carrying Case	

Informant®2 Dual Purpose Leak Detectors

- Detects refrigerants and combustible gases with respective sensor installed, changing sensors takes only seconds
- Sensor located in the probe tip for ultimate sensitivity, fast response and easy changing
- Visual and audible indicators include dual LED scales, flashing LED in probe tip and a speaker with mute option
- CE approved, SAE J1627 (refrigerant sensor only), UL 913 Class 1, Division 1, Group D (combustible sensor only)
- Includes: (1) Set of refrigerant and combustible gas sensors, (1) Set of colour-coded probe tips, (1) Rubber boot, (1) Instruction manual, (4) AA batteries, (5) Filters, (1) Hard carrying case
- Refrigerants Detected: All CFC, HFC and HCFC Refrigerants
- Combustible Gases Detected: All Hydrocarbons/Combustible Gases



Model No.	Mfg. No.	Description	Price /Each
IC417	0019-8038	Dual Purpose Leak Detector	