



## M12™ Infrared Camera Kit

- 2-Stage trigger activates lasers for easy scanning or quickly captures images
- Multiple color palettes available include rainbow, grayscale and ironbow
- Fully compatible with Milwaukee® Thermal Imager Reporting Software available at Milwaukeeeetool.com
- DUAL SENSE™ pixels are ultra-responsive, adjusting individually to eliminate blurring of hot and cold details
- Dual lasers frame on-screen temperature area
- Temperature Range: 14°- 626°F (-10°-330°C)
- Spot Size Ratio: 83:1
- Emissivity: Fixed
- Voltage: 12 V
- Data Storage: SD Card up to 32 GB
- Display Resolution: 320 x 240 pixels
- 2-Stage trigger activates lasers for easy scanning or quickly captures images
- Multiple color palettes available include rainbow, grayscale and ironbow
- Fully compatible with Milwaukee® Thermal Imager Reporting Software available at Milwaukeeeetool.com
- DUAL SENSE™ pixels are ultra-responsive, adjusting individually to eliminate blurring of hot and cold details
- Dual lasers frame on-screen temperature area



Model No.	Mfg. No.	Description	Price/Each
UAE222	2258-21	Infrared Camera Kit	

## Infrared/Contact Temp-Gun™

- Includes: 30:1 Infrared/Contact Temp-Gun™ (2269-20), NIST Certification, Manual, K-Type Thermocouple, 9V Battery
- Additional contact measurement from -40°F to 1022°F for use in a variety of applications
- Premium LCD display for clear readings
- 1/4-20 thread for mounting to tri-pods or other accessories
- Spot Size Ratio: 30:1
- Emissivity: Adjustable, 0.1-0.99 by 0.01
- Data Storage: 99 Measurements
- Spot Size Ratio: 30:1
- Emissivity: Adjustable
- Emissivity: 0.1-0.99 by 0.01
- Data Storage: 99 Measurements
- Includes: 30:1 Infrared/Contact Temp-Gun™ (2269-20), NIST Certification, Manual, K-Type Thermocouple, 9V Battery
- Additional contact measurement from -40°F to 1022°F for use in a variety of applications
- Premium LCD display for clear readings
- 1/4-20 thread for mounting to tri-pods or other accessories



Model No.	Mfg. No.	Description	Price/Each
UAE223	2269-20NST	Infrared Temperature Gun	

## Infrared Temperature Guns

- Detect surface hot-spots and help locate electrical problems with this Milwaukee 12:1 Infrared Temp-Gun
- Boasts a high temperature range for electrical, mechanical, and MRO applications
- Max/Min/Avg/Dif modes
- High/low alert
- Raised over-molding protects lens and screen from direct impact
- Simplified buttons and setup for faster scanning
- Temperature Range: -22-1022°F (-30-550°C)



Model No.	Mfg. No.	Description	Price/Each
IB744	2268-20	Infrared Temperature Gun	

## Infrared Temperature Calibrators

- Temperature Range: Up To 500°C (932°F)
- This portable infrared temperature calibrator is as easy to use, just point and shoot;
- For calibrating non-contact infrared thermometers up to 500 °C (932 °F);
- Temperature controlled black-body target with a diameter of 2.25" (57 mm);
- Wide field of view to compensate for optical variations in individual infrared thermometers;
- Simply set the desired temperature in increments of 0.1 °, wait for the calibrator to attain equilibrium, point the infrared thermometer at the target and measure the radiated energy;
- Contact RTD reference well is located directly behind the blackbody target to assure even higher accuracies of ± 0.1 °C
- Display: Digital
- No. of outputs: 2



Model No.	Mfg. No.	Price/Each
IA548	BX-500	

## Infrared Video Thermometer

- Dual lasers identify exact measuring spot where they converge
- Optical Resolution: 50:1 (Distance: Spot size)
- Fast 150ms response time
- 2.2" TFT colour LCD and built-in 640 x 480 pixels camera
- Supports image (JPEG) and video (AVI) capture alerts
- Transmit images and videos via USB interface
- 72MB internal memory with MicroSD memory card extension
- Datalogging capabilities with date and time
- Includes type K thermocouple probe, AC adapter, USB adapter, mini-tripod, and hard carrying case



IA977

### SPECIFICATIONS:

- IR Temp. Range:** -58 to 3992°F (-50 to 2200°C)
- Spectral Response:** 8 to 14µm
- Type K Temp. Range:** -58 to 2498°F (-50 to 1370°C)
- Air Temp. Range:** 32 to 122°F (0 to 50°C)
- Dew Point & Wet Bulb Temp. Range:** 32 to 122°F (0 to 50°C)
- Humidity Range:** 0 to 100% RH



Model No.	Mfg. No.	Description	Price/Each
IA977	R2020	Infrared Video Thermometer/Datalogger	
OM464	SD-MINI (8GB)	8GB Micro SD Memory Card	

# Contact us now to receive our latest flyers

