LV355



Bulldog® Utility Duty Electric Winches

- Circuit breakers automatically shut off the winch to prevent motor overheating
- Limited lifetime warranty on mechanical parts, one year on electrical components'
- Rope Included/Not Included: Included
- Remote Included/Not Included: Included
- Power in and power out for powerful retraction and rapid rope pay-out
- High-torque motor for a higher pull at a lower amp
- Easy transition between gear engagement & free spooling

Lusy truits	ition between gear e	ngagement a nee spooming					
Model	Mfg	Working	Max. Cable	Rope Storage	Motor		Price
No.	No.	Load Limit	Diameter	Capacity	HP	Motor	/Each
LV355	500400	2500 lbs. (1136 kg)	3/16"	50' (15 m)	0-4/5	12V DC, 600 W	
LV356	500401	3500 lbs. (1591 kg)	7/32"	50' (15 m)	1-1/5	12V DC, 900 W	
LV357	500402	4500 lbs. (2054 kg)	1/4"	50' (15 m)	1-3/5	12V DC, 1200 W	
LV353	500600	9000 lbs. (4091 kg)	21/64"	95' (29 m)	5-4/5	12V, 4,63 KW	
LV354	500601	12 000 lbs. (5455 kg)	13/32"	83.7' (25,5 m)	7-1/5	12V, 5,4 KW	

Bulldog® Heavy Duty Electric Winches


- 3-stage gear train for reliable, durable performance in tough conditions, and maximum mechanical efficiency
- Pull-and-turn T-handle clutch lever for easy transition between gear engagement & free spooling
- Limited lifetime warranty on mechanical parts, one year on electrical components
- Durable heavy duty motor delivers superior torque output & faster line speed
- Heavy-Duty sealed contactor for sound, waterproof protection
- Thermometric sensor provides overheating indication

Model Mf No. No LV358 500	-	Working Load Limit 6000 lbs. (2727 kg)	Max. Cable Diameter 9/32"	Rope Storage Capacity	Motor HP	Motor	Rope Included /Not Included	Remote Included /Not Included	Gear Ratio	Price /Each
IV358 50		, ,,,	9/32"	001 (24)						/ Lucii
E1330	0424			80' (24 m)	3-1/5	12V DC, 2390 W	Included	Not Included	216:1	
LV359 50	0 12 1	9000 lbs. (4091 kg)	3/8"	82' (25 m)	4-3/5	12V DC, 3430 W	Included	Not Included	156:1	
LV360 50	0426	12 000 lbs. (5455 kg)	3/8"	82' (15 m)	4-3/5	12V DC, 3430 W	Included	Not Included	211:1	
LV361 50	0403	6000 lbs. (2727 kg)	9/32"	80' (24 m)	3-1/5	12V DC, 2390 W	Not Included	Not Included	216:1	
LV362 50	0404	9000 lbs. (4091 kg)	3/8"	82' (25 m)	4-3/5	12V DC, 3430 W	Not Included	Not Included	156:1	
LV363 50	0405	12 000 lbs. (5455 kg)	3/8"	82' (25 m)	4-3/5	12V DC, 3430 W	Not Included	Not Included	211:1	
LV364 50	0406	12 000 lbs. (5455 kg)	3/8"	125' (38 m)	5-3/5	12V DC, 4180 W	Not Included	Not Included	261:1	
LV365 50	0407	15 000 lbs. (6818 kg)	7/16"	90' (27 m)	5-3/5	12V DC, 4180 W	Not Included	Not Included	315:1	
LV366 50	0408	18 000 lbs. (8181 kg)	1/2"	82' (25 m)	6	12V DC, 4474 W	Not Included	Not Included	315:1	

Heavy-Duty Hand Winches


Completely load activated braking is standard on all models and sizes. The brake responds automatically when the handle is released, recoil is prevented and the load is held in any position.

Model No.		LB439	LB440	LB441
Mfg. No.		CMA440	CMA1100	CMA1760
Wkg Load Limit	lbs.	440	1100	1760
	kg	200	500	800
Rope Dia.	in.	3/16	1/4	5/16
	mm	4	6	7
Rope Storage	ft.	131	164	256
Capacity	m	40	50	78
Price/Each		P.O.A.	P.O.A.	P.O.A.



Model No.		LB442	LB444	
Mfg. No.		GS275	GS1100	
Wkg Load Limit	lbs.	275	1100	
	kg	125	500	
Rope Dia.	in.	1/8	1/4	
4	mm	3	6	
Rope Storage	ft.	171	46	
Capacity	m	52	14	
Price/Each		P.O.A.	P.O.A.	

Model No.		LB445	LB446*	LB447*
Mfg. No.		CMG770	CMG1450	CMG2000
Wkg Load Limit	lbs.	770	1450	2000
	kg	350	659	909
Rope Dia.	in.	3/16	1/4	5/16
	mm	4	6	7
Rope Storage	ft.	79	66	46
Capacity	m	24	20	14
Price/Each	,	P.O.A.	P.O.A.	P.O.A.









Jeamar Winches

www.tenaquip.com


Heavy-Duty Electric Winches

Specify required voltage when ordering, pricing may vary, we are not held responsible for incorrect voltage chosen

Unit comes with standard voltage in Canada of 575 V


HAULING SERIES

Model No.		LB273	LB047	LA761
Mfg. No.		NHT550	NHT1100	NHT1900
Wkg Load Limit	t lbs.	550	1100	1900
(1st Layer)	kg	249	499	862
Line Speed	ft/min.	27	28	31
(1st Layer)	m/min.	8.2	8.5	9.1
Rope Dia.	in.	1/8	3/16	1/4
	mm	3	5	6
Rope Capacity	ft.	113	117	226
(4th Layer)	m	34	36	69
Motor	HP	1/2	1	2
	kw	0.4	0.7	1.5
Weight	lbs.	94	146	229
	kg	93	66	104
Price/Each		P.O.A.	P.O.A.	P.O.A.



LIFTING SERIES

Model No.		LA767	LB310	LA763
Mfg. No.		NLT400	NLT800	NLT1400
Wkg Load Limit	t lbs.	400	800	1400
(1st Layer)	kg	181	363	635
Line Speed	ft/min.	22	22	24
(1st Layer)	m/min.	6.7	6.7	7.3
Rope Dia.	in.	1/8	3/16	1/4
	mm	3	5	6
Rope Capacity	ft.	175	220	250
(4th Layer)	m	53	67	76
Motor	HP	1/2	1	1 1/2
	kw	.4	.7	1.1
Weight	lbs.	130	212	322
	kg	59	96	146
D: /E !				



Note: Numerous options such as grooved drums, controls, free spooling, limit switches and explosion-proof motors are sold separately and are not included in these models. Electric motors can be supplied at any voltage at 50 or 60 hertz.

Also available in stainless steel. Note: Cables not included.

LB273

LB310