



Pilot Sleeve™ Wheel Centering Sleeves

- Centering sleeve takes up the gap between the 22 mm stud and the 26 mm wheel opening, realigning the wheel to the true center of the hub bearing

PILOT SLEEVE™ ZIP TOOL

- Installation and removal tool for Pilot Sleeve™ Wheel Centering Sleeves



FLT178



FLT179



Model No.	Mfg. No.	Description	Price /Each
FLT179	30631	Package of 6	
FLT180	30632	Bucket of 100	
FLT181	30633	Bucket of 1000	
FLT178	30630	Zip Tool	

Double End Truck Wrench

- Use on trucks, buses, farm, and off-road vehicles
- Great for on-the-road service
- Forged from 1" alloy steel for long lasting strength



FLT331



Model No.	Mfg. No.	Description	Socket Sizes	Weight lbs.	Price /Each
FLT331	32502	TR2	1" with 5/8" square x 1-1/4"	4.3	
FLT180	30632	TRM2	24 mm x 33 mm	4.4	
FLT181	30633	TRM7	30 mm x 33 mm	4.6	

T119 Portable 2-Bar Magnum Tire Cage

- Designed to accept the new generation of super single and super wide-base truck tires with their higher inflation pressures and air volumes
- Height: 49-1/2"
- Width: 24-1/2"
- Base (Closed): 7" x 30"
- Weight: 80 lbs.

Model No. FLT356
Mfg. No. 36019
Price/Each \$



2-Bar Tire Inflation Cage

- Will hold super singles and super wide radial tires
- Made from heavy-gauge steel tubing welded to a steel base
- Guards against blown lock rings and rims
- Designed to meet OSHA regulation requirements for medium, heavy-duty truck, OTR, tractor, and super singles
- Mandatory for any shop working with tubeless and multi-piece rims
- OSHA reg. 29-CFR Part 1910.177

FLT343



Model No.	Mfg. No.	Dim. W" x H"	Base (Closed)"	Price /Each
FLT345	36001	16 x 41	7 x 21-1/2	
FLT343	36007	20-1/2 x 43-1/2	7 x 27	

T68 Standard Wheel Cover Puller & Replacer

- Removes hub caps quickly and easily without gouging or scratching them
- Rubber head prevents damage to hub cap and is replaceable
- Length: 14" (36cm)
- Stock: 7/16" (11.1mm)
- Weight: 1.3 lbs.

Model No. FLT185
Mfg. No. 31568
Price/Each \$



TPMS Sentry™ Tire Pressure Monitoring System Tool

- Designed to keep the sensor in a safe and secure position after the mounting nut has been removed and the sensor is released from the wheel
- Protects valuable valve stem sensors that mount through the valve hole
- T-shaped tool attaches to sensor to keep it from dropping in to tire cavity when mounting or demounting tire
- Knurled surfaces provide positive grip even when coated with water or bead lubricant
- Fits through all valve stem holes
- Material: Hardened Steel

Model No. FLT168
Mfg. No. 30209
Price/Each \$



TX9 Porkchop™ Budd Nut Wrench

- Holds outer cap nut on dual wheels while the inner nut is turned
- Lip fits in hole to secure wrench in place
- Fits Cap Nut Size: 1-1/2"
- Weight: 0.73 lbs.

Model No. FLT173
Mfg. No. 30609
Price/Each \$



Tire Inflation Cage

- Made from heavy-gauge steel tubing welded to a steel base
- Guards against blown lock rings and rims
- Designed to meet OSHA regulation requirements for medium, heavy-duty truck, OTR, tractor, and super singles
- Mandatory for any shop working with tubeless and multi-piece rims
- OSHA reg. 29-CFR Part 1910.177



FLT335



Model No.	Mfg. No.	Number of Bars	Dim. W" x H"	Base"	Price /Each
IDEAL FOR PASSENGER & LIGHT TRUCK TIRES					
FLT347	36003	3	16 x 30	21-1/2 x 22	
IDEAL FOR SUPER SINGLES & SUPER WIDE RADIAL TIRES					
FLT346	36002	4	20-1/2 x 43-1/2	31-1/2 x 26	
FLT355	36005	5	20-1/2 x 43-1/2	41 x 26	
IDEAL FOR TRUCK TIRES					
FLT349	36008	7	29 x 46	34 x 56	