



Blowers

- X-Torq® engine design reduces harmful exhaust emissions by up to 60% and increases fuel efficiency by up to 20%
- Air Purge removes air from carburetor and fuel system for easy starting
- Offset handle makes the blow forces easier to control by preventing the arm from being pulled downwards



| SPECIFICATIONS | 525Bx | 560BTs | 570BTs | 580BTs |
|---------------------|--------------|--------------|--------------|--------------|
| Displacements (CC) | 25.4 | 65 | 65 | 75.6 |
| Engine Power (HP) | 1.14 | 4 | 4 | 4.3 |
| Air Speed (CFM/MPH) | 459/157 | 632/236 | 770/236 | 936/212 |
| Harness | Integrated | Integrated | Integrated | Integrated |
| Nozzle Type | Round | Round | Round | Round |
| Vacuum Kit | - | - | - | - |
| Weight (lbs./kg) | 9.5/4.3 | 23.4/10.6 | 24.5/11.1 | 26.3/11.9 |
| Model No. | NL865 | NL921 | NM889 | NN313 |
| Mfg. No. | 967 28 42-02 | 966 63 11-02 | 966 62 94-02 | 967 85 13-01 |
| Price/Each | \$ | \$ | \$ | \$ |

| SPECIFICATIONS | 125B | 125BVx | 130BT | 350BT | 320LiB * | 436LiB ** |
|---------------------|--------------|----------------|--------------|--------------|--------------|--------------|
| Displacements (CC) | 28 | 28 | 29.5 | 50 | - | - |
| Engine Power (HP) | 1.1 | 1.1 | 1.3 | 2.1 | - | - |
| Air Speed (CFM/MPH) | 425/170 | 425/170 | 360/145 | 494/180 | 412/103 | 388/105 |
| Harness | - | Single Harness | Integrated | Integrated | - | - |
| Nozzle Type | Round + Flat | Round + Flat | Round | Round | Round | Round |
| Vacuum Kit | - | Yes | - | - | - | - |
| Weight (lbs./kg) | 9.4/4.3 | 9.6/4.4 | 14.8/6.7 | 22.5/10.2 | 5.29/2.4 | 5.29/2.4 |
| Model No. | NL855 | NL873 | TYX949 | NL906 | NL890 | NM890 |
| Mfg. No. | 952 71 19-25 | 952 71 19-02 | 965 10 22-08 | 965 87 75-02 | 967 09 42-02 | 967 68 02-02 |
| Price/Each | \$ | \$ | \$ | \$ | \$ | \$ |

* Battery and charger included ** Unit only, battery and charger sold separately

Power Cutters

- Husqvarna power cutters are robust, reliable and powerful machines
- Compact and powerful machine with superior power-to-weight ratio
- Dust-sealed starter device and the durable starter cord, assures the saw will be ready for work whenever you want



| SPECIFICATIONS | K 760 - 12" | K 760 - 14" | K 970 - 14" | K 970 III - 14" Rescue Saw | K 1270 - 16" |
|-------------------------------------|--------------|--------------|--------------|----------------------------|--------------|
| Displacements (CC) | 73.5 | 73.5 | 94 | 93.6 | 118.8 |
| Engine Power (HP) | 4.9 | 5 | 6.5 | 6.5 | 7.9 |
| Max Cutting Depth (in.) | 5 | 4.92 | 5 | 5 | 6 |
| Vibration Front (m/s ²) | 2.4 | 2.4 | 3.7 | 3.8 | 6.9 |
| Vibration Rear (m/s ²) | 2.4 | 2.4 | 4.5 | 4.2 | 6.3 |
| Active Air Filtration™ | Yes | Yes | Yes | Yes | Yes |
| X-Torq® | No | Yes | Yes | No | Yes |
| Sound Level (dB(a)) | 115 | 115 | 116 | 115 | 117 |
| Weight excl. acc. (lbs. / kg) | 21.2/9.6 | 22.3/10.1 | 24.2/11.0 | 24.2/11.0 | 31.7/14.4 |
| Model No. | NM891 | NN014 | NM572 | NM892 | NM893 |
| Mfg. No. | 967 18 10-01 | 967 68 21 01 | 967 34 80-01 | 967 63 56-01 | 967 05 42-01 |
| Price/Each | \$ | \$ | \$ | \$ | \$ |

Cutting Blades

| Model No. | Mfg. No. | Specifications | Diameter" | Thickness" | Arbor Size | Price/Each |
|------------------------|--------------|-------------------------------------|-----------|------------|--------------------|------------|
| ABRASIVE BLADES | | | | | | |
| NM895 | 542 75 15-04 | General Concrete, Asphalt and Brick | 14 | - | 1" | |
| NM896 | 542 75 15-10 | Steel | 14 | - | 1" | |
| NM897 | 542 75 15-16 | Ductile Iron/Aluminum | 14 | - | 1" | |
| NM898 | 542 75 15-11 | Steel | 14 | - | 20 mm | |
| NM899 | 542 75 15-12 | Steel | 16 | - | 1" | |
| PREMIUM BLADES | | | | | | |
| NM900 | 542 77 45-41 | HI-5 Premium Diamond Blade | 14 | 0.125 | 1"- 20 mm Knockout | |
| NM901 | 542 77 65-04 | HI-8 Premium Diamond Blade | 14 | 0.125 | 1"- 20 mm Knockout | |
| CHOICE BLADES | | | | | | |
| NL869 | 542 77 87-35 | EH-5 Choice Diamond Blade | 14 | 0.125 | 1"- 20 mm Knockout | |
| NM902 | 589 71 93-01 | EH-5 Choice Diamond Blade | 16 | 0.140 | 1"- 20 mm Knockout | |
| NM903 | 542 77 55-98 | EH-8 Choice Diamond Blade | 16 | 0.140 | 1"- 20 mm Knockout | |