## **FALL PROTECTION**

## First<sup>™</sup> Harnesses Welders Harnesseses Fundamental fall protection Heat and flame resistant webbing made with exceptional value from modacrylic over Kevlar® and polyester One adjustable dorsal D-Ring High durability and resistance to abrasion Supple back plaque Alloy steel connectors and D-rings 1.75" wide polyester web for durability Specifically designed for welding Zinc-plated stamped steel hardware applications to provide char resistance Pass-thru leg and chest closures Lightweight design to improve comfort Universal size Web and lanyard storage keepers reduce potential entanglement hazards Weight capacity: Char temperature: 700°F 310 lbs. (141 kg) Certified to CSA Pass-thru chest connectors standard Z259.10 SEB372 . Weight capacity: 420 lbs. (190 kg) Certified to CSA standard Z259.10 Size: Medium/Large\* PROTECT/ Fall Protection Model Mfg. PROTEČTA No. No. **D-Rings** SEJ400 1191379C Back Fall Protection SEJ403 11913810 Back and Side 11913890 Back/Front/Shoulder Model Mfg. CSA Price SEJ406 No. No. **D-Rings** Description Class /Each SEJ409 11913830 Back 3-Point Adjustment SEB371 AB17510C Back A SEJ412 1191385C Back and Side SEB372 AB175300 Back 5-Point Adjustment A

CSA Leg Price Connections Class /Each Pass-Thru A Pass-Thru A.P Pass-Thru A, D, E **Tongue Buckle** А A, P **Tongue Buckle** SEJ415 1191392C Back/Front/Shoulder Tongue Buckle A, D, E

**SEJ400** 

\*Small and X-Large available on request



Mfg. No. 9501403C Price/Each \$



## **AirCore™ Harnesses**

- Designed with breathable, open-core padding technology that provides optimal air flow, while reducing heat and moisture entrapment, keeping a worker drier and cooler
- Patented Miller DuraFlex® stretchable webbing provides greater flexibility and increased comfort Easy adjustment with cam buckles on shoulder straps
- Contoured ergonomic padding design minimizes contact around a worker's neck,
- lower back, and inner thighs to reduce chaffing and irritation Stand-up back D-ring
- Quick-connect chest strap buckles for easy donning
- Lightweight materials and components reduce fatigue for all-day endurance and increased productivity •
- Durable knitted mesh back shield minimizes moisture absorption and maintains optimal air circulation
- Weight capacity: 400 lbs. (181.4 kg)
- Certified to CSA standard 725910

1220

• cerune		aru 2239.10
Model	Mfg.	

Model No.	Mfg. No.	D-Rings	Leg Connections	Additional Features	CSA Class	Price /Each
STEEL	HARDWARE					
SEJ642	AC-TB/UGN	Back	Tongue Buckle	-	Α	
SEJ643	AC-TB-D/UGN	Back and Side	Tongue Buckle	-	Α, Ρ	
SEJ644	AC-TB-BDP/UGN	Back and Side	Tongue Buckle	Lumbar Pad and Removable Belt	Α, Ρ	
SEJ645	AC-QC/UGN	Back	Quick Connect	-	A	
SEJ646	AC-QC-D/UGN	Back and Side	Quick Connect	-	Α, Ρ	
SEJ647	AC-QC-BDP/UGN	Back and Side	Quick Connect	Lumbar Pad and Removable Belt	Α, Ρ	
ALUMI	NUM HARDWA	RE				
SEJ648	ACA-TB/UGN	Back	Tongue Buckle	-	Α	
SEJ649	ACA-TB-D/UGN	Back and Side	Tongue Buckle	-	Α, Ρ	
SEJ650	ACA-TB-BDP/UGN	Back and Side	Tongue Buckle	Lumbar Pad and Removable Belt	Α, Ρ	
SEJ651	ACA-QC/UGN	Back	Quick Connect	-	Α	
SEJ652	ACA-QC-D/UGN	Back and Side	Quick Connect	-	Α, Ρ	
SEJ653	ACA-QC-BDP/UGN	Back and Side	Quick Connect	Lumbar Pad and Removable Belt	Α, Ρ	



## Honeywell MILLER

2020 © TENAQUIP Limited

1-800-661-2400

SEJ647

www.tenaquip.com