

### Comfort Grip Connector

- Transverse load rated self-locking/closing aluminum Comfort Grip connector
- Built-in connector for single-leg SRL direct attachment to
- Extremely compact, lightweight design
- Tough and impact-resistant thermoplastic housing
- Swiveling anchorage loop
- · Quick-activating speed-sensing brake system
- High-capacity external energy absorber and impact indicator
- i-Safe™ equipped
- Certification: CSA standard Z259.12
  - for transverse loading
- Note that this connector pairs with many of 3M lanyards and SRLs so multiple configurations are available

Model No. SGJ693 Mfg. No. 1246415 Price/Each \$





#### **Saflok<sup>tm</sup> Carabiners**

- Steel carabiners
- Self locking/closing 3600-lb. gate

Model







Mfg.



NO.	NO.	opening	
SEH168	2000117	11/16	
SEE719	2000113	1 3/16	

#### Concrete **Detent Anchors**

- · Reusable detent pin assembly allows a user to tie-off anywhere a socket is pre-installed with a push of a button
- Lightweight and portable
- Socket can be installed vertically or
- overhead into a concrete wall, floor, or ceiling
- Rugged, corrosion resistant stainless steel

Model No. SEJ623 Mfg. No. 2101004 Price/Each \$





**Fall Protection** for Tools

### **Cable Tie-Off Adaptors**

- 1/4" coated galvanized cable
- Lightweight and extremely durable
- Stands up to harsh environments
- Snap hook at one end, O-ring at the other
- · Length: 6'

Model No. SEB470 Mfg. No. AJ408CG-6 Price/Each \$



Model

SEB389

SEB390





#### Tie-Off Adaptors

Pass-thru style polyester web tie-off adaptor

## **Anchorage Connecting Carabiners**

- · Zinc plated, 3600-lb. anchorage point
- Easy one-hand operation
- Self-locking
- 3/4" gate opening
- Meets OSHA 1926 and ANSI SZ359 standards

Model No. SEB926 Mfg. No. AJ514A Price/Each \$









# **Concrete D-Ring Anchors**

- Reusable D-ring assembly
- Rugged design for harsh environments
- Safe "hook-up" indicator notifies user of proper installation
- Install into 11/16" or 3/4" holes only standard drill bits needed

Model No. SEB438 Mfg. No. 2104568 Price/Each \$















- · Can be bolted or welded to a structure, offering a compact, reliable connection point
- Two 1/2" diameter attachment holes
- Cadmium plated steel D-ring
- 304 stainless steel anchorage plate
- Plate size: 1/4" x 2" x 4 1/2" Model No. SEB449

Mfg. No. 2101639

Price/Each \$

