

#### **Fixed Beam Anchors**

- Installs in seconds to the beam structure in any orientation

Final tightening using a built-in adjustment handle Fits up to 1 1/2" thick beam flange, 2 1/2" to 12" wide

Model No. SEE808 Mfg. No. 2108406 Price/Each \$







#### Freestanding Counterweight Anchors

 Freestanding system is easily placed on top of the roof surface to provide tie-off point for one worker

Model No. SEE809 Mfg. No. 2100185 Price/Each \$







# Rollgliss™ Rescue Pole

- · Allows assisted rescue of worker after a fall
- Extension pole adjusts from 4 ft to 16 ft (1.2 m to 4.9 m)
- · Does not require special tools or training
- · Enables faster and more efficient rescues
- · Oversized connection hook
- · Compact and lightweight design
- Colour: Red & Silver

Model No. SHA876 Mfg. No. 8900298 Price/Each \$





#### Cobra™ Mobile/ Manual Rope Grab with Lanyard

- Mobile design automatically follows user
- Manual option allows user to fix in place
- · Cam locking system for safety
- Integral 2 ft. (0.6 m) PRO™ shock absorbing lanyard
- · Detachable anywhere along the lifeline
- Durable and lightweight corrosion- resistant construction
- For use with 5/8" (16 mm) diameter polyester/ polypropylene blend rope lifeline
- Rope Diameter: 5/8"

Model No. SEP896 MFG No. AC202C-SA2 Price/Each \$







### **Sliding Beam Anchor**

- · Versatile size ranges to fit a variety of beams
- Replaceable wear pads
- 360-degree swiveling D-ring anchor point
- Integrated dual ratcheting system
- High-strength, lightweight steel and aluminum construction
- 5000 lb. strength and up to 420 lb. (189 kg) capacity
- Type: Temporary
- Style: I-Beam

Model No. SGJ699 Mfg. No. 2104710 Price/Each \$







#### **Door/Window Jamb Anchors**

- Fits door or window sizes ranging from 21 1/2" to 51 1/2" in width
- Non-penetrating design ensures no damage to structure
- Fast and easy installation with built-in adjustment knob – no tools or drilling are required
- · Lightweight and extremely portable design

Model No. SEJ618 Mfg. No. 2100080 Price/Each \$









#### **Beam Trolley Anchorage Connectors**

- Installs easily and quickly overhead with no tools necessary at ends or midpoint on beams
- Non-corrosive double-shielded wheel bearings provide smooth and effortless operation
- Trolley guards protect the wheels from damage and keep the beam ahead of the trolley clear of debris

  Trovides added
- Provides added maneuverability, improved safety, and increased productivity
- Fits flat or tapered beam flanges 3" to 8" wide, and up to 11/16" thick

Model No. SEJ617 Mfg. No. 2103143 Price/Each \$







## **Rope Lifelines**

- 16 mm (5/8") diameter, polyester sheath with polypropylene core
- · Tensile strength: 2540 kg (5600 lbs.)
- · Zinc plated stamped steel hook
- Net weight: 5.6 lbs. (25 kg)







Model	Mfg.		Price
No.	No.	Length'	/Each
SEB381	SSR100-50	50	
SEB382	SSR100-100	100	