

Classes of Fire:

Fires are classified according to the material that is burning. Fire extinguishers are rated by the area each will cover for a particular class of fire. The higher the number, the bigger the fire area you can fight.

Note: Maintenance and recharging of all fire extinguishers should be performed by a qualified service company.



CLASS A fires are the most common. They involve ordinary combustibles such as wood, paper, cloth, rubber, a number of plastics, and other ordinary materials.



CLASS B fires are caused by gasoline, grease, oil, paint and other flammable liquids. Commonly strikes in warehouses and manufacturing plants.



CLASS C for live electrical equipment. Often occurs in computers, monitors, wiring and appliances.

Dry Chemical ABC Fire Extinguishers

- Steel cylinder complete with cylinder skirt
- Industrial-strength cylinder has high corrosion and impact-resistant polyester powder paint finish
- Waterproof stainless steel gauge
- Anodised aluminum valve
- Strong polyester powder-coated steel handles
- Completely rechargeable
- Full hand grip for ease of operation



• OL/OLC listed												
Model No.	Mfg. No.	Cap. lbs.	Rating	Range Feet	Discharge Time Sec.	PSI	Н"	Dia."	Included Bracket	Wt. Ibs.	Price /Each	
SAQ814	SFABC110STVB	2.5	1A:10BC	8 - 10	12-14	150	15 1/2	3 1/8	Vehicle	4 1/4		
SA445	WBDL-ABC310LV	5	3A:10BC	8 - 10	13 - 14	195	16	4 1/4	Wall	10 1/2		
SC946	SFABC310VB	5	3A:10BC	8 - 10	13 - 14	195	16	4 1/4	Wall & Vehicle	10 1/2		
SED109*	SFABC340VB	5	3A:40BC	8 - 10	13 - 14	195	16	4 1/4	Wall & Vehicle	10 1/2		
SA443	SFABC680	10	6A:80BC	10 - 15	14 - 16	235	21 1/4	5 1/8	Wall	19 1/4		
SA444	SFABC1020	20	10A:120BC	10 - 15	20 - 22	235	24	7 1/8	Wall	35 1/4		
SED110	SFABC30	30	10A:120BC	10 - 15	28	195	30 3/4	7 1/8	Wall	50 1/3		



ACCESSORIES

Model No.	Mfg. No.	Description	Fits	Price/Each	Model No.	Mfg. No.	Description	Fits	Price/Each
SC951	C160738	Wall Hook	5 lbs.		SA442	UP2	Vehicle Bracket	2.5 lbs.	
SC952	C160752	Wall Hook	10 lbs.		SC955	UB5	Vehicle Bracket	5 lbs.	
SC953	C160791	Wall Hook	20 lbs.		-	-	-	-	-

Aluminum Cylinder Carbon Dioxide (CO₂) Fire Extinguishers

- Well suited for corrosive environments
- Industrial-strength aluminum cylinder is up to 30% lighter than steel
- Stainless steel hose band
- Strong impact-resistant horn
- Bar-coded label
- Easy to service
- Comes with wall hook
- **ULC** listed

)
Price /Fach

Model No.	Mfg. No.	Cap. Ibs.	Rating	Range Feet	Discharge Time Sec.	Н"	Dia."	Wt. Ibs.	Price /Each
SAJ098	SF-5C02	5	5BC	6-12	10	17 1/4	5 3/4	13 1/4	
SAJ099	SF-10C02	10	10BC	6-12	10	19 3/4	6 3/4	27	
SAJ100	SF-15C02	15	10BC	6-12	15	26 3/4	6 3/4	37	
SAL344	SF-20C02	20	10BC	6-12	20	26 3/4	8	48 1/8	



HDVB-4

ACCESSORIES Model No. Price/Each Model No. Mfg. No. Description Price/Each Description SAM953 SF5WH Wall Hook 5 lbs. SAP900 HDVB-2 Vehicle Bracket 5 lbs. SAM954 SF1015WH Wall Hook 10-15 lbs. SAM957 HDVB-3 Vehicle Bracket 10 lbs.

Included

Bracket

Wall

H"

21 1/2

Dia.'

PSI

K Class Wet Chemical Extinguishers

Wall Hook

Brass valve construction

Mfg.

No.

SF6K

SED438

Specially designed and tested to address fires in restaurants and commercial fryers

Range

Feet

10-12

Very effective on cooking oil and grease fires

Liters

6

- Ideal for restaurants, kitchens, cafeterias, food courts, and other locations with high temperature cooking materials
- Nozzle designed to prevent splashing
- Designed to be used in conjunction with a kitchen suppression system

Rating

1-A:K



Wt.

lbs.

25



Vehicle Bracket

15 lbs.

Discharge

Time Sec.

60

^{*}Meets requirements for forklifts