



Dynamic Lift™ Magnets

- Lifting Capacity: 150 lbs.
- Weight: 6.1 lbs.
- Powerful rare earth permanent lift magnets
- Top rotating locking On/Off handle
- Lifts flat or round loads horizontally
- Lifts flat loads vertically
- Heat resistant up to 180° F (82° C)
- 3:1 Design factor
- **Conforms to ASME B30.20 standards**

LU436



Model No.	Overall Dimensions			Lift lb	Wt. lb	Price /Each
	L" x W" x H"					
LU436	5 x 2 x 9			150	6.1	
LU437	6 1/2 x 4 x 9 1/4			334	13.3	

Creative Lift® Magnets

- Permanent lift magnets are ideal for handling steel plates, die castings, forgings etc.
- They eliminate the need for clamping devices, slings or chains
- One person can perform operations previously calling for two or more people
- Non-marring roller cam release
- Durable stainless steel casing
- 3:1 design factor
- **Conforms to ASME B30.20 standards.**



Model No.	Dimensions			Magnet		Holding Capacity lbs.	Price /Each
	L" x W" x H"	H" L"					
LS708	7 3/4 x 7 1/4 x 6 3/4	2 1/2	4		400		
LS709	10 3/4 x 7 1/4 x 6 3/4	2 1/2	7		1000		
LS710	14 3/4 x 7 1/4 x 6 3/4	2 1/2	10 1/2		1500		
LT271	15 x 10 1/2 x 7	2 1/2	11 1/4		2200		
LS711	19 1/4 x 10 1/2 x 7	2 1/2	15 1/4		3000		

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	3/16"		1/4"		1/2"		1"		2"	
	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length
LS708	400	6	400	6	400	8	400	10	400	10
LS709	600	6	900	6	1000	8	1000	10	1000	10
LS710	800	6	1000	6	1500	8	1500	10	1500	10
LT271	800	6	1064	6	2000	8	2200	10	2200	10
LS711	800	6	1100	6	2700	8	3000	10	3000	10

Winch Operated Truck Jib Crane

- Lift items from ground to truck bed height
- Install in pick up truck beds
- Telescopic boom design with manual hydraulic hand pump to pivot boom up and down
- Manual cable winch to lift and lower loads
- Friction brake winch locks automatically when operator turns the handle counter clockwise to lower load
- Unit comes with one fixed hook, one chain slot lock, and one cable hook with latch



Model No.	Boom Extended Capacity lbs.	Boom Retracted Capacity lbs.	Cable Winch Capacity lbs.	Boom Reach		Lift Range		Finish	Cable Usage Length	Price /Each
				Extended	Retracted	Extended	Retracted			
LU494	500	1000	500	51	34-3/4	0-102	10-89-1/2	Yellow Coated	9'	
LU495	1000	2000	500	44	30	0-86-1/2	13-1/2-77-1/2	Yellow Coated	9'	
LU496	500	1000	500	52	30-1/2	0-99	13-1/2-84	Galvanized	20' w/Dia. 1/4"	
LU497	1000	2000	500	52	31	0-97	13-1/2-86	Galvanized	20' w/Dia. 1/4"	

Powerlift® Magnets

- Compact yet powerful rare earth lift magnets can be used on flat or round surfaces and contain an internal release on/off device that does not contact or damage the surface of the part being lifted
- Permanent magnetic lifts eliminate the fear of dropping the load being lifted due to power failures
- 3:1 design factor
- **Conforms to ASME B30.20 standards**



Model No.	Capacity lbs.		Minimum Diameter"	Dimensions			Handle"	Wt. lbs.	Price /Each
	Flat	Round		L" x W" x H"					
LS712	250	125	2	5 x 2 5/8 x 6 5/8	5 7/8	7			
LS713	800	400	3	7 7/8 x 3 5/8 x 8 7/8	6 7/8	22			
LS714	1600	800	4	10 3/4 x 4 7/8 x 8 7/8	6 3/4	53			
LS715	2500	1250	5	12 5/8 x 7 1/8 x 8 7/8	10 1/8	110			

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	1/4"		1/2"		3/4"		1"		3"	
	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length
LS712	180	6	250	6	250	6	250	10	250	10
LS713	270	6	615	6	800	6	800	10	800	10
LS714	N/A	-	800	6	1600	6	1600	10	1600	10
LS715	N/A	-	N/A	-	N/A	-	1300	10	2500	10

Basiclift Magnets

- Permanent lift magnet for a broad range of lifting applications
- Full width cam release
- Large lift lug
- Light weight design
- Durable stainless steel casing
- Heat resistant up to 300°F (148°C)
- 2:1 design factor



Model No.	Overall Dimensions			Lift lb	Wt. lb	Price /Each
	L" x W" x H"					
LT372	7 1/2 x 5 5/8 x 5 1/2			400	13	
LT373	11 x 5 5/8 x 5 1/2			1000	18	
LT374	14 1/2 x 5 5/8 x 5 1/2			1500	28	

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	3/16"		1/4"		1/2"		3/4"		1"	
	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length	Cap. lbs.	Length
LT372	375	6	400	6	400	8	400	8	400	10
LT373	725	6	800	6	975	8	1000	8	1000	10
LT374	875	6	1000	6	1400	8	1500	8	1500	10



GX Lifting Clamps

- Entirely drop forged and heat treated
- Strong, yet lightweight
- Ideal for both vertical and horizontal-to-vertical lifting
- Feature a patented wear indicator system
- 100% proof tested



Campbell®

Model No.	Capacity Ton	Grip Range"	Wt. lbs.	Price /Each
LB606	1/2	1/16-5/8	4	
LB607	1	1/16-3/4	8	
LB608	3	1/16-1	17	

Beam Clamp

- Caution: Never exceed work load limit



Model No.	Capacity	Jaw Opening"	Price /Each
LU561	2000 lbs. (1 ton)	0-10-1/4	
LU562	4000 lbs. (2 tons)	0-10-1/4	
LU563	6000 lbs. (3 tons)	0-13-15/16	
LU564	10 000 lbs. (5 tons)	0-13-15/16	
LU565	20 000 lbs. (10 tons)	0-14-3/8	