

## **Hydra-Lift Drum Handlers**

- A safe way to lift, move, tilt and drain 45 imp. gal./55 US gal. drums
- Manual control; pump-handle lifts drum, maximum extension is 45 strokes
- Hand crank controls tilt angle of drum up to 360° in either direction for controlled pouring of contents, chain wheel controls tilt for 72" and higher lift models
- 800 lbs. full drum capacity; 500 lbs. half-full capacity
- Rugged, heavy-duty welded frame; 8" polyolefin wheels and 4" swivel casters; screw-down floor lock
- Power lift and power tilt with a choice of motors is optional
- 60" and 72" manual lift and tilt units ship partially disassembled
- Powered models eliminate the manual effort of drum raising and tilting; increases productivity and safety
- Optional MORStop™ tilt brake holds drum tilt position constant even when tension from the pull chain is removed

MANUAL LIFT - For the 60" dispensing height unit, the tilt function is controlled by a hand crank. The 72" and 96" tilt control is with a chain wheel.

POWER LIFT - Moving valve handle to up, down or hold position controls drum height; 15 - 20 seconds lifting time.

**POWER LIFT & TILT** - One valve controls lifting, another controls tilt angle. Ideal when hand crank or chain drop is out of reach.

Dispensing Height"	H"	L"	R"	0.D."	I.D."
60	55	60	12	44	37
72	55	60	6	44	37
96	69	72 1/2	4	49	42

Di-		i ula				
60" Model No.	pensing He 72" Model No.	96" Model No.	Description	60" Price /Each	72" Price /Each	96' Price /Each
DA138 DA139 <sup>†</sup> DA141	DA143 DA144 <sup>†</sup> DA146	DA153 DA154 <sup>†</sup> DA156	Manual hydra lift and tilt Hydra lift c/w air power lift and power tilt Hydra lift c/w air power lift and manual tilt*	72	, =====	/
OPTIC DC077	ON		MORStop™ Tilt Brake Option			

<sup>\*</sup> Filter, regulator and lubricator not included \*\* Battery and charger included

### **Grip+Go Power-Grip Fork Mount Drum Handler**

- Control the drum tilt function all the
- way from upright to fully inverted
- Adjustable grip pressure for handling various sized steel drums
- The battery and charger are included
- The sufficiently low weight of the Grip+Go helps for a minimal lost load of your equipment
- Engage drum with heavy-duty jaws
- Use with the wireless control for a
- 300 foot operating range (DC679) Easy to handle various sized drums
- Drum Capacity: 15 55 US Gal. (12.5 45 Imperial Gal.)
- Working Load Limit: 1500 lbs./680 kg
- Battery Type: 12V
- Drum sizes: 14" to 24" diameter

Model No. DC678 Mfg No. 290F Price/Each \$

### **GRIP+GO FACTORY INSTALLED WIRELESS CONTROL ON MODEL 290F**

Model No. DC679 Mfg No. 6149i-F Price/Each \$



DC278

Top Rim

Clamp

DC279

**Bracket** 

# MORCINCH™ Options & Accessories

### **TOP RIM CLAMP**

- Can be added to most of our Morse drum lifting equipment
- Grips the upper rim of your drum to prevent it from slipping through the drum holder
- Add this option to handle a 55 gallon (208 L) rimmed plastic drum
- Can also be used with a rimmed fiber or steel drum
- Weight: 11 lbs.

Model No. DC278 Mfg No. 4560-P Price/Each \$

### **BRACKET ASSEMBLY**

- Can be added to most of our Morse drum lifting equipment
- Add this option to handle your fibre drums or rimless plastic drums
- The bracket braces the top and bottom of your drum to prevent it from slipping in the holder
- Adjustable to handle drums from 31" to 39" tall
- Weight: 20 lbs.

Model No. DC279 Mfg No. 4556-P Price/Each \$



MORSE

**MORStop**\*
















**MORSE** 

### **DIAMETER ADAPTORS**

- Can be added to most of our Morse drum lifting equipment
- Designed to fit a smaller diameter drum and it easily fits inside the drum holder
- No tools required to install
- Adaptor for 18 1/2" to 19" diameter drums
- Weight: 24 lbs.

Model No. DC280 Mfg No. 55/30-19 Price/Each \$

<sup>†</sup> MORStop™ tilt brake option not needed