



Dual Purpose Pumps

- Operates submersed or in-line (water-fed via pipe/hose)
- Cast aluminum housing with protective epoxy coating
- Threaded intake and discharge
- Nylon pumping head and impeller
- Thermal overload protection
- For use with water only
- 10' power cord
- Nylon screen
- UL listed, CSA certified



Model No. DA328

- 3/8" FNPT intake and 1/4" MNPT discharge
- Buna-N seal
- 1.7 amps
- 100 watts
- 5 1/2" L x 3 1/2" W x 4 3/4" H

Model No. DA329

- 1/2" FNPT intake and 1/2" MNPT discharge
- Viton® Seal
- 3.2 amps
- 200 watts
- 7" L x 4 1/2" W x 5 1/2" H



Automatic Condensate Removal Pumps - VCMA Series

- Vertical type pump unit
- 1/2 gallon leak proof, rustproof, ABS tank with mounting tabs
- Stainless steel motor shaft
- Three drain holes
- 3/8" O.D. barbed discharge adapter and removable 3/8" barbed check valve
- Snap-action safety switch
- Thermal overload protected
- Suitable for high-efficiency, gas furnace condensate
- 15' shut-off head
- 6' power cord
- Weight: 4.40 lbs.
- UL/CSA listed



Construction

- Motor:** 1/50 HP high performance
- Intermittent liquid temperature:** Up to 120°F
- Discharge:** 3/8" OD barbed
- Housing:** ABS
- Cover:** ABS
- Volute:** ABS
- Impeller:** Glass filled polypropylene

Model No. DC294

Price/Each \$



| Model No. | HP | Volts | Gallons/Hour | | | Shut Off' | PSI | Wt. lbs. | Price /Each |
|-----------|------|-------|--------------|-----|-----|-----------|------|----------|-------------|
| | | | 1' | 3' | 5' | | | | |
| DA328 | 1/40 | 115 | 300 | 255 | 205 | 70 | 11.8 | 5.1 | 4 |
| DA329 | 1/15 | 115 | 500 | 435 | 337 | 210 | 17.3 | 7.5 | 8 |

Non-Submersible, Self-Priming Plated Brass Transfer Pumps

- 1/10 HP, 115 V, 60 Hz, 1.6 Amps motor
- 360 GPH @ 1"
- Self-priming for instant delivery or de-watering up to 6'
- Non-submersible plated brass pump body
- Rugged metallic handle for easy portability
- Dual threaded intake and discharge with both 3/4" male garden hose thread and 3/8" FNPT
- Includes: pump, hose, strainer and suction adapter

Model No. DC293

Price/Each \$

PUMP ONLY

Model No. DC196

Price/Each \$



Contraflex Water Discharge Hoses

- Extremely durable hose
- Layflat design for easy handling
- 25' and 50' lengths with C and E cam and groove fittings assembled



| Model No. | Size | Price /Each |
|-----------|------------|-------------|
| TEB656 | 1.5" x 25' | |
| TEB651 | 1.5" x 50' | |
| TEB657 | 2" x 25' | |
| TEB652 | 2" x 50' | |
| TEB658 | 2.5" x 25' | |

| Model No. | Size | Price /Each |
|-----------|------------|-------------|
| TEB653 | 2.5" x 50' | |
| TEB659 | 3" x 25' | |
| TEB654 | 3" x 50' | |
| TEB660 | 4" x 25' | |
| TEB655 | 4" x 50' | |

Aluminum Cam & Groove Fittings

- Simple to use quick connect fittings
- Very reliable and durable



| Size" | Part A | Price /Each | Part B | Price /Each | Part C | Price /Each | Part D | Price /Each | Part E | Price /Each | Part F | Price /Each |
|-------|--------|-------------|--------|-------------|--------|-------------|--------|-------------|--------|-------------|--------|-------------|
| 1 | WL016 | | WL027 | | WL038 | | WL049 | | WL060 | | WL071 | |
| 1 1/4 | WL017 | | WL028 | | WL039 | | WL050 | | WL061 | | WL072 | |
| 1 1/2 | WL018 | | WL029 | | WL040 | | WL051 | | WL062 | | WL073 | |
| 2 | WL019 | | WL030 | | WL041 | | WL052 | | WL063 | | WL074 | |
| 2 1/2 | WL020 | | WL031 | | WL042 | | WL053 | | WL064 | | WL075 | |
| 3 | WL021 | | WL032 | | WL043 | | WL054 | | WL065 | | WL076 | |
| 4 | WL022 | | WL033 | | WL044 | | WL055 | | WL066 | | WL077 | |

PVC Suction & Discharge Hoses

- Excellent weather and abrasion resistance
- Perfect for construction pumps, trash pumps, mining and quarry use
- 25' lengths with C Cam, Groove fitting and combination nipple fully assembled
- Hoses 1 1/2" and over come with an assembled basket strainer



| Model No. | Size" | Price/Each |
|-----------|-------|------------|
| TEB644 | 1 | |
| TEB645 | 1.25 | |
| TEB646 | 1.5 | |
| TEB647 | 2 | |
| TEB648 | 2.5 | |
| TEB649 | 3 | |
| TEB650 | 4 | |