



Iron Guard® Acrylic Enamel Industrial Coatings™



- High gloss, 100% acrylic, waterborne coating for light to moderate industrial use
- Designed for new construction or maintenance use, can be used directly over prepared substrates, including metal
- Chemical and corrosion resistant, fast drying and outstanding early moisture, flash rust and early rust resistance
- Low odour, outstanding adhesion
- VOC: < 100 g/L (0.83 lbs./gal)
- Can be used on steel, iron, aluminum, galvanizing, concrete, masonry, wood and over zinc-rich primers in applications such as tank and cylinders, steel fabricated parts, equipment, machinery, metal buildings, select marine structures, piping, handrails and ornamental iron



NI814

| Colour | Model No. 1 Gallon | Price/Each | Model No. 5 Gallon | Price/Each |
|-------------------------------|--------------------|------------|--------------------|------------|
| Gloss White | NI813 | - | KP259 | - |
| Gloss Black | NI814 | - | KP260 | - |
| Semi-Gloss Black | NI816 | - | - | - |
| Flat Black | KP262 | - | - | - |
| Safety Yellow (OSHA) | NI815 | - | - | - |
| Safety Red (OSHA) | NI818 | - | - | - |
| Safety Blue (OSHA) | KP263 | - | - | - |
| Safety Green (OSHA) | KP264 | - | - | - |
| Light Machinery Grey (ASA-61) | NI822 | - | - | - |
| Safety Orange (OSHA) | KP266 | - | - | - |
| Dark Machinery Grey (ASA-49) | KP267 | - | - | - |
| New Cat Yellow | KP268 | - | - | - |

Rust Tough® 250 Acrylic Alkyd Enamel



- For interior/exterior industrial, institutional, commercial and maintenance use in moderate to severe environments
- Rust inhibitive, corrosion resistant alkyd enamel can be applied directly to metal
- Protects against mild chemicals, fumes, oil and grease stains and atmospheric corrosion
- Excellent hide, colour & gloss retention, and superior chip, crack and peel resistance
- Low VOC, CARB compliant < 250 g/L
- Can be used on previously painted surfaces, iron, steel, aluminum, galvanized metal or wood
- Acceptable for use in Canadian food processing facilities
- Size: 1 gallon



AD349

| Model No. | Colour | Price /Each |
|-----------|----------------------|-------------|
| AD350 | Safety Yellow | - |
| AD358 | Safety Orange | - |
| AD359 | Safety Blue | - |
| AD355 | Safety Red | - |
| AD345 | Gloss White | - |
| AD349 | Black | - |
| AD352 | Dark Machinery Grey | - |
| AD353 | Light Machinery Grey | - |
| AD356 | Equipment Yellow | - |
| PRIMER | | |
| AD347 | Grey Primer | - |
| AD357 | Red Oxide Primer | - |

Sierra Metalmax® DTM Acrylic

- This water-based formula contains no VOCs, HAPs or solvent odor and is ideal for schools and settings where paint fumes are an issue
- Superior resistance to corrosion and humidity; excellent color retention
- Fast, convenient, single-component system
- Results in a smooth, washable, professional finish
- Applies direct-to-metal (DTM), including galvanized steel and aluminum; for interior/exterior use
- For use on: Anywhere paint odors or VOC is a concern, food/beverage plants, schools, healthcare, warehouses, metal structures, line equipment
- Size: 1 Gal.
- Surface coverage: 180-545 sq. ft./gal. (4.4-13.4 m²/L)



KP481

RUST-OLEUM

| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|---------------|-------------|
| KP481 | 210475 | Safety Red | - |
| KP482 | 210477 | Safety Yellow | - |
| KP483 | 238752 | White | - |
| KP484 | 238753 | Safety Blue | - |

Epoxy Floor Coating

- Low VOC, low HAP, two component suitable for use on both floors and vertical surfaces
- Can be used on steel, non-ferrous, concrete, masonry, and previously coated surfaces
- Low odour coating ideal for use in schools, healthcare facilities, food service areas, office buildings, hotels or in any area where odors are an issue
- Resistant to most chemicals and abrasion
- Easy-to-use, two-component system—order base and activator separately
- Container Type: Gallon
- Container Size: 1 gal.
- Net Volume: 1 gal.
- Finish: Gloss



RUST-OLEUM

| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|-------------|-------------|
| KP899 | 248280 | Osha Yellow | - |
| KP901 | 208072 | Gloss Grey | - |
| KP873 | 248284 | Activator | - |

5600 Acrylic Urethane Floor Paint

- Convenient, high-gloss, water-based coating is ideal for use in mild industrial or commercial setting
- Protects concrete floors from dusting, water damage, staining and mildew
- Paint and go — no measuring or mixing; minimal surface prep
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- Dries fast — accepts next-day foot traffic; easy brush, spray or roller application
- For use on: Interior/exterior concrete floors, walkways, decks/patios
- Surface Coverage: 170-270 sq.ft./gal. (4.2-6.6 m²/L)
- Accepted for use in Canadian food processing facilities



KP490

RUST-OLEUM

| Model No. | Mfg. No. | Colour | Container Size | Price /Each |
|-----------|----------|---------------|----------------|-------------|
| KP490 | 251286 | Safety Yellow | 1 Gallon | - |
| KP491 | 251291 | Silver Grey | 1 Gallon | - |
| KP492 | 251293 | Silver Grey | 5 Gallons | - |

5500 Acrylic Dustproof Floor Sealer

- Water-based coating seals concrete and prevents dusting in mild industrial or commercial settings
- Seals bare concrete or provides a protective top coat; makes maintenance easy; low-gloss finish
- Excellent coverage over new and previously coated surfaces; for interior/exterior use
- For use on: Floor coating for warehouses, walkways, over strained and painted concrete, retail/commercial
- Size: 1 Gal.
- Accepted for use in Canadian food processing facilities
- Surface Coverage: Rough (Broom Finish) - First Coat - 150 sq. ft./gal., Second Coat - 250 sq. ft./gal. Smooth (Float Finish) - First Coat - 200 sq. ft./gal., Second Coat - 300 sq. ft./gal. Very Smooth (Trowel Finish) - First Coat - 300 sq. ft./gal., Second Coat - 400 sq. ft./gal.



Model No. KP493
Mfg. No. 251282
Price/Each \$

RUST-OLEUM