Instant Adhesives (Cyanoacrylates)

- Widest selection of high-performance, application-specific, instant adhesives
- Available in a variety of viscosities, cure speeds, gap-filling capabilities and substrate compatibilities
- Ultra-high performance Loctite Prism® family offers toughened formulations, low odor, low blooming and thermally resistant formulations

Adhesive

Designed for bonding

Gap fill: 0.006"

Viscosity: 22 cP

Colour: Clear

Mode

AD414

AD415

No

metal, rubber and plastics

on metals, plastics and rubbers

Typical use: General purpose

-65°F to 240°F (-54°C to 115°C)

Cure speed: fixture 30 sec., full 24 hrs.

Shear strength: 2700 PSI

Temperature range:

Mfg.

840057

840071

No

435[™] Clear Surface

Insensitive Instant

The first true clear, surface insensitive,

elastomer-modified instant adhesive

room temperature cure instant adhesive

Excellent peel, impact and sheer strength

Low viscosity, clear, rubber toughened, one part,

431[™] Surface Insensitive Instant Adhesive

- Medium viscosity, clear, gap filling, surface insensitive, one part, room temperature cure instant adhesive
- Designed for the assembly of difficult-to-bond materials which require uniform stress distribution
- Particularly suited for bonding a wide range of materials, including metals,
- plastics, and elastomers
- Typical use: Gap filling
- Gap fill: 0.008"
- Viscosity: 1 000 cP
- Shear strength: 2300 PSI Temperature Range: -65°F to 180°F (-54°C - 82°C)
- Cure speed: Fixture – 15 sec., full: 24 hrs.
- Colour: Clear

LOCTITE

Model	Mfg.		Price
No.	No.	Size	/Each
AD406	868350	3 g Tube	
AD407	868371	20 g Bottle	
AD408	868372	1 lb. Bottle	

410[™] Instant Adhesive Black/Toughened

- High viscosity, black, rubber toughened, one part, room temperature cure, gap filling instant adhesive
- Designed for bonding metal, rubber and selected plastics
- Excellent peel, impact and sheer strength
- Typical use: Gap filling
- Gap fill: 0.008"
- Viscosity: 3500 cP Shear strength: 3200 PSI
- Temperature range: -65°F to 225°F (-54°C to 107°C)
- Cure speed:
- Fixture 90 sec., full 24 hrs. Colour: Black

LOCTITE

Model	Mfg.		Price
No.	No.	Size	/Each
AD410	233757	3 g Tube	
AD411	135444	20 g Bottle	
AD412	135445	1 lb. Bottle	

495[™] Super Bonder[®] Instant Adhesive

- A medium viscosity, high temperature product for all metals, and most plastics and rubbers
- Resists temperatures to 223°F
- continuous or up to 250°F intermittent Ideal for gap distances up to 0.004"
- Fixtures in 20 seconds, full in 24 hrs.
- Provides a shear strength of 2750 PSI
- Colour: Clear
- Improved formula
- LOCTITE

209591

AB366

752

Mode Mfg. No. Size AA456 234072 3 a Tube AA487 135467 1 oz. Bottle

1 lb. Bottle

LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA493	232834	3 g Tube	
AA494	135423	1 oz. Bottle	
AF080	135424	1 lb. Bottle	

Fast, two-part CA bonds gaps up to 0.200" (5 mm)

LOCTITE

- Good for bonding plastics,
- High precision dispensing tips
- Includes a 10 gram syringe with 3 mix nozzles



LOCTITE

Price

/Fac

Model	Mfg.	Size	Price
No.	No.		/Each
AE630	1807961	10 g	/

401™ General Purpose Instant Adhesive

Size

20 g Bottle

1 lb. Bottle

- A general purpose adhesive for difficult-to-bond surfaces
- For bonding porous or absorbent materials, such as wood, paper, leather or fabric
- Ideal for gap distances up to 0.005"
- Fixtures in 15 seconds, full in 24 hrs. Provides a shear
- strenath of 3200 PSI
- Withstands temperatures to 250°F Colour: Clear
- Improved formula

LOCTITE


410

Model No.	Mfg. No.	Size	Price /Each
AA544	233641	3 g Tube	
AA545	135429	20 g Bottle	
AD987	135430	1 lb. Bottle	

380[™] Black Max[®] Toughened

- Bonds metal, rubber, and plastic
- For use in difficult environments
- Ideal for gap distances up to 0.006"
- Fixtures in 90 seconds, full in 24 hrs. Provides a shear strength of 3750 PSI
- Withstands temperatures to 225°F
- Colour: Black

3092[™] Two-Part Instant Adhesive





454[™] Prism[®] Instant Adhesive Gel

- A general purpose, no-run clear gel
- Excellent for almost all surfaces Ideal for porous substrates
- and rough and acidic surfaces
- Ideal for gap distances up to 0.010"
- Fixtures in 15 seconds, full in 24 hrs.
- Provides a shear
- strength of 3200 PSI Withstands temperatures to 250°F
- Colour: Clear
- Improved formula

LOCTITE

Model	Mfg.		Price
No.	No.	Size	/Each
AA548	233998	3 g Tube	
AB343	135462	20 g Tube	
AF079	234004	200 g Tube	
AA549	88525	300 g Cartridge	

Quicktite[®] Instant Adhesive Gel

- A general purpose instant adhesive
- Precision flow
- control applicator

LOCTITE

Mfg.

680522

No

Designed to be clog-free



Size

0.14 oz bottle

/Eac

1-800-661-2400

Pric

/Eacl

AB950 www.tenaquip.com

