

402™ Instant Adhesive

- Medium viscosity, high temperature, durable, & fast-setting
- Ideal for a wide range of substrates
- Provides reliable performance under extreme operating temperatures up to 135°C
- Bonds quickly and strongly to a wide range of plastic, rubber, & metal substrates, including difficult-to-bond materials
- Ideally suited for the joining of small parts in high-speed production applications as well as quick, on-the-go repairs
- Unique, patented formula with reduced hazardous ingredients
- Colour: Clear
- Type: Moisture Cure
- Gap Fill: 0.15 mm
- Operating Temperature: -40 135°C
- Technology: Cyanoacrylate
- Viscosity: 110 mPa·s (cP)
- Fixture Time (Grit Blasted Steel): 20 sec.



7452 Accelerator

- Aggressive cleaning properties, promote the cure speed of all Loctite Cyanoacrylate Adhesives
- Colour Family: Yellow
- One-Part Life Time: 1 Minute
- Dry Time: 30 Seconds



LOCTITE.

Model No.	Mfg. No.	Size	Price /Each
AH189	2714628	20 g Bottle	
AH170	2712746	500 g Bottle	

LOCTITE

White Glue

Safe and non-toxic Pourable

· Washable no-run glue; easy to clean up

bonding non-porous substrates (i.e. plastic or metal)

paper, cardboard, leather, fabric and cork

Recommended for wood, wood compositions, veneer,

Not recommended for joints that require gap filling,

Model	Mfg.		Price
No.	No.	Size	/Each
AH100	2765220	946 ml Can	

Ten Bond Contact Cement

- Brush-able, neutral-colored contact adhesive for bonding many decorative laminates, aluminum, steel, plywood, panels, wood and wood veneer, masonry, rubber, canvas and other porous and non-porous materials
- Air drying adhesive which bonds immediately and permanently upon application of contact pressure
- No clamping or fixturing required





• Colour: w
ELMER'

Model	Mfg.		Price
No.	No.	Size	/Each
AE606	60307W8	120 ml	
AE607	60310Q	225 ml	
AE608	6155060331	950 ml	
AE609	6155060341	3,8 L	

Model No.	Mfg. No.	Size	Price /Each
AMC295	10-1L	1L	
AMC294	10-1GAL	1 gal.	

Carpenter's® Wood Glue

- Made for furniture repair and general indoor household projects
- Best for soft and hardwoods, particle board and porous materials
- Cleans up with soap and water when wet, and scrape and sand when glue is dry
- Open time: 10-15 minutes before clamping
- Clamp time: 12 hours
- Light colour for natural and light stained woods
- Pourable
- Colour when dry: Yellow



Model	Mfg.		Price	
No.	No.	Size	/Each	
AE610	60615TR	118 mL		
AE611	60613TR	236 mL		
AE612	60617TR	473 mL		
AE614	6155060619	3.8 L		

Probond® Max Wood Glue

- Made for furniture repair and general indoor and outdoor household projects
- Best on wood
- Contains real wood fibers for superior staining, painting, and sanding
- Open time: 10-15 minutes before clamping
- Clamp time: 12 hours
- Easy to clean-up with water
- Pourable and waterproof
- · Colour when dry: Beige





