



## 10" Dual Sliding Compound Mitre Saws w/Laser



- Sliding rail mechanism incorporating three linear ball bearings
- Sliding fence (left side) can be adjusted outwards when bevel cutting or inwards for increased support of small or delicate materials
- Battery operated, factory calibrated Class 2 laser
- Bevel capacity of 45° left or right
- Mitre capacity of 47° left or 60° right with positive stops at 0°, 15°, 22.5°, 31.6° and 45°
- 2-stage safety switch for increased operator safety
- Includes: 10" mitre saw blade 40CT, box wrench, dust bag, vertical vise, triangle rule, 2 ea. holder

**Model No. TLV225**  
**Mfg. No. LS1018L**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 13.0  
**No Load RPM:** 4300  
**Arbor:** 5/8"  
**Mitre Range:** 47° Left to 60° Right  
**Bevel Range:** 45° Left to 45° Right  
**Soft Start:** Yes  
**Tool Weight:** 43.7 lbs.



## 12" Double-Bevel Compound Mitre Saws

- Stainless steel mitre detent plate with 14 positive stops delivers repeatable accuracy and worksite durability
- Double-bevel design allows saw to bevel 0° - 48° to the left and right with positive stops at 0°, 22.5°, 33.9°, and 45°
- Cam lock mitre handle with detent override delivers quick and accurate mitre angles
- Tall sliding fences support crown molding up to 6-5/8" nested and base molding up to 6-1/2" vertically against fence
- High-efficiency dust duct
- Lightweight design and built-in carry handle provide portability
- **UAG298:** Cutline™ LED work light system provides adjustment-free cut line indication for accuracy and visibility

### SPECIFICATIONS

**Blade Diameter:** 12"  
**No Load RPM:** 3800  
**Amps:** 15 A  
**Mitre Range:** 50° Left/50° Right  
**Bevel Range:** 48° Left/48° Right  
**Arbor Size:** 5/8" or 1"  
**Weight:** 41 lbs.



Model No.	Mfg. No.	Description	Price /Each
UAG297	DWS716	Saw without Worklight	
UAG298	DWS716XPS	Saw with Worklight	

## 12" Sliding Compound Mitre Saws

- Rail forward design
- Integrated guide fence and lower fence
- Front bevel knob
- Constant speed control maintains constant speed under heavy load
- Soft start feature gradually
- Electric brake
- Easy-to-operate mitre angle lock
- Horizontal handle design with 2-stage safety switch for increased operator safety
- Ergonomic horizontal soft rubber grip design for vibration absorption and comfortable operation
- Includes: 12" C.T. Blade 60T, Dust Bag, Vertical Vise, Triangle Rule, Two Holder 200, Holder 90, Hex Wrench 6

**Model No. UAD702**  
**Mfg. No. LS1219**  
**Price/Each \$**

### SPECIFICATIONS

**Blade Diameter:** 12"  
**No Load RPM:** 3200  
**Amps:** 15 A  
**Voltage:** 120 V  
**Mitre Range:** 60° Left/60° Right  
**Bevel Range:** 60° Left/60° Right  
**Arbor:** 1"  
**Vibration Level:** 2.5 m/s<sup>2</sup>  
**Noise Level:** 91 dB(A)



## 10" Sliding Compound Mitre Saws

- Rail forward design
- 3-stage gear reduction system greatly increases capacity when cutting vertical baseboard or nested crown molding
- 1-3/16" guide rail diameter provides increased stability and cutting precision
- Integrated guide fence and lower fence
- Front bevel knob
- Electronic speed control maintains constant speed under heavy load
- Soft start feature
- Easy-to-operate mitre angle lock with free spin lever a
- Horizontal handle design with 2 stage safety switch for increased operator safety
- Ergonomic horizontal soft rubber grip design for vibration absorption and comfortable operation
- Includes: 10" C.T. Blade 60T, Hex Wrench 6, Dust Bag, Vertical Vise, Triangle Rule, Dust Nozzle, Two Holders, Wrench Holder

**Model No. UAD701**  
**Mfg. No. LS1019**  
**Price/Each \$**

### SPECIFICATIONS

**Blade Diameter:** 10"  
**No Load RPM:** 3200  
**Amps:** 15 A  
**Voltage:** 120 V  
**Mitre Range:** 60° Left/60° Right  
**Bevel Range:** 60° Left/60° Right  
**Arbor:** 5/8"  
**Vibration Level:** 2.5 m/s<sup>2</sup>  
**Noise Level:** 91 dB(A)



## 10" Compound Mitre Saws

- Positive stops at nine settings; 15°, 22.5°, 31.6°, 45°, left and right and 0° mitre cuts
- Precision machined aluminum base
- Shaft lock for easy blade changes
- Includes: Cross-out blade, dust bag, triangular rule and socket wrench

**Model No. VK963**  
**Mfg. No. LS1040**  
**Price/Each \$**

### SPECIFICATIONS

**Positive mitre detents:** 0°, 15°, 22.5°, 31.6° and 45° left and right  
**Mitre range:** 45° left, 52° right  
**Bevel range:** 45° left, 45° right  
**Vertical cap.:** 2 3/4"  
**Horizontal cap.:** 5 1/8"  
**No load speed:** 4600 RPM  
**Arbor Size:** 5/8"  
**Motor:** 120 V AC, 15.0 A  
**Weight:** 24.2 lbs.  
**Blade Diameter:** 10"

