



1/2" Corded Drill

- Variable speed feature enables operator to adjust speed to suit various materials and applications
- Ideal for mixing thin-set mortar, drywall compound, masonry, paint and more!
- Increased continuous input rating, rated amperage and no load speed for added improved motor cooling for added durability and operational efficiency
- Aluminum gear housing
- Conveniently located forward / reverse switch
- Lock-on button enables easy continuous operation
- Rear handle rotates 360° with 24 locking positions
- Removable side handle
- Lanyard loop provides secure attachment of safety / security lanyards
- Ergonomic soft rubber grip for vibration absorption and comfortable operation

Model No. TYL192
Mfg. No. DS4012
Price/Each \$



SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 8.5
No Load RPM: 600
Chuck Type: Keyed
Tool Weight: 6.2 lbs.

1/2" VSR Dual Range Hammer Drills

- High/low speed for high speed drilling or high torque applications
- 8.2 Amp motor provides high performance and overload protection
- 360° side handle with depth rod offers greater control
- Includes: 360° side handle, depth rod and chuck key with holder

Model No. TKZ841
Mfg. No. DW520K
Price/Each \$



SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 10
No Load RPM: 0-1200/0-3500
No Load BPM: 0-56 000
Chuck Type: Keyed
Tool Weight: 6.0 lbs.

Power Scrapers

- Quick change bit retainer for easy changes
- Motor has auto shut-off feature when brushes must be replaced
- Factory grease packed for approximately 200 hours of maintenance free operation
- Includes: 1 3/16" and 2" scaling chisels, bull point, dust cover and plastic carrying case

Model No. TF850
Mfg. No. HK1820
Price/Each \$



SPECIFICATIONS

Amperage: 5.0
No Load BPM: 0-3200
Impact Energy: 2.9 ft.-lbs.
Tool Weight: 7.5 lbs.

1/2" VSR Hammer Drills

- Lightweight design for less user fatigue
- Dual mode hammer drill/drill for wood, steel or masonry applications
- Variable speed allows for precise hole placement on work surface
- Includes: 360° side handle, depth rod and chuck key with holder

Model No. TSW576
Mfg. No. DW511
Price/Each \$



SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 6.7
No Load RPM: 0-2700
No Load BPM: 0-46 000
Chuck Type: Keyed
Tool Weight: 4.3 lbs.

1/2" VSR Dual Range Hammer Drills

- High/low speed for high speed drilling or high torque applications
- Lightweight design for less user fatigue
- 360° side handle with depth rod offers greater control
- Includes: Side handle, chuck key and plastic carrying case

Model No. TD944
Mfg. No. DW505K
Price/Each \$



SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.8
No Load RPM: 0-1100/0-2700
No Load BPM: 0-19 000/0-46 000
Chuck Type: Keyed
Tool Weight: 4.8 lbs.

1" D-Handle SDS Rotary Hammer

- SHOCKS - Active Vibration Control® reduces vibration felt by the user at the handles
- Variable speed trigger allows user to instantly control speed
- Mode selector allows for usage in rotary hammer, rotary only, and chiseling applications
- Reversing feature helps release tool from bind up situations, and assists with removal of fasteners
- 360 degree side handle adjusts easily for preference or use in tight spaces

Model No. TLV939
Mfg. No. D25263K
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 5/32" - 5/8"
Amperage: 8.0
No Load RPM: 0-1150
No Load BPM: 0-4300
Impact Energy: 2.1 ft.-lbs.
Tool Weight: 7.0 lbs.

