



Heavy-Duty Extendable Mobile Bases

- Heavy-duty steel construction
- Fully adjustable, 8 "U" shaped bars offer a wide range of configurations and sizes
- Minimum dimensions: 14" x 17"
- Maximum dimensions: 27 3/4" x 32 1/2" or 25" x 35 1/4"
- Capacity: 700 lbs.
- Cam lift pedals with swivel casters
- Adjustable leveling feet



Model No.	Mfg. No.	Price /Each
TMA064	KMB-1290	

Extendable Universal Mobile Bases

- Minimum square dimension: 11" x 11"
- Maximum square dimension: 35.2" x 35.2"
- Minimum rectangular Dimension: 17.1" x 11"
- Maximum rectangular Dimension: 51" x 19"



Model No.	Mfg. No.	Price /Each
WK981	KMB-1250	

Heavy-Duty Air Impact Wrench

- Pin-clutch hammer mechanism
- Built-in regulator to prevent over-torquing
- Low noise, low vibration
- Forward-reverse switch and high-low speed regulator
- Vibration Level: Less Than 3.1 m/s²
- Torque Range: 25-320 ft.-lbs.
- Hose Diameter: 3/8" (9.5 mm)
- Bolt Capacity: 5/8" (15.9 mm)
- Net Weight: 2 lbs.



Model No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
UAK133	12 CFM	1/4" NPTF	94	1/2	7000	

Omni-Directional & Roller Stands

- Can be used with any sander, bandsaw, planer, jointer and other machine to feed material
- Height adjustable from 27" to 44"
- Folds flat for storage



Model No.	Description	Price /Each
BT705	Roller Stand	
TZ755	Omni-Directional Stand	

Extendable & Flexible Conveyor Roller Tables

- Extends from 19" to 52"
- Raises from 24" to 39" from ground
- Can be manually flexed to a curved position
- 9 solid 2" x 20" conveyor rollers
- 4" heavy-duty wheels with locking casters
- Capacity: 300 lbs.



Model No.	Mfg. No.	Price /Each
TEX194	KRRS-109	

Heavy-Duty Air Impact Wrench

- Delivers 4500 ft.-lb of max reverse torque powered by Ingersoll Rand's finely tuned warm forged twin-hammer impact mechanism
- Fully adjustable auxiliary handle position allows the tool to be configured for the operator or application
- Steel hammer case and endplates, and aluminum motor housing and handle deliver unmatched durability in the most rugged applications
- 6-vane motor with optimized air flow
- Drive Type: Square, Ring/Thru-hole
- Forward Torque: 4500 ft.-lb (6100 Nm)
- Reverse Torque: 4500 ft.-lb (6100 Nm)
- BPM: 700
- Weight: 3.5 lbs.
- Length: 16.5"
- Manufacturer's Warranty: 1 Year



Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	Drive"	No Load RPM	Price /Each
UAV628	2955B2	138 CFM	1/2" NPTF	103.3	1-1/2	3300	