



3" Air Cut-Off Tools

- Polyurethane handle reduces operator fatigue and vibration
- Power/speed regulator allows for easy PSI adjustment
- Twin-bearing design for smooth operation and cut off powerfully
- Wrench and Allen Key included to lock/unlock the disc
- Cut off wheel dimensions compatible with tool is 3" diameter x 0.060" thick (or thicker) x 3/8" arbour

Model No. THZ677



Model No.	Cutting Wheel		Free Speed RPM	Average Air Consumption CFM		Air Inlet	Hose Size		Horsepower HP	Vibration Less Than m/s^2	Sound Pressure Level dB(A)	Net Weight		Price /Each
	in	mm		in	mm		in	mm				lbs.	kg	
THZ677	3	76.2	21 000	3	1/4"-18 NPT	3/8	9.5	0.45	0.2	81	1.8	0.82		

Heavy-Duty Pistol Grip Air Shear

- For maximum performance we recommend 90 PSI air pressure
- Professional air shear for heavy duty applications
- Features a two gear, heavy duty planetary system for increased torque
- Popular pistol grip design for ease of operation
- Handle exhaust directs exhaust air away from the work piece and the operator
- Ideal for shearing steel, aluminum and most types of plastic
- Shear cuts maximum steel thickness: Regular Steel, Aluminum, Stainless Steel 1.24 mm
- Keep blades sharp for extended service life
- Air Inlet: 1/4" NPT
- Sound Level (dBA): 85
- Cutting Capacity: 18 Gauge
- Air Inlet: 1/4"
- Min. Hose Size: 3/8"
- Aluminum Cutting Capacity: 13 Gauge
- HP: 0.35
- Strokes Per Minute: 2200

Model No. UAV944

Mfg. No. 404163

Price/Each \$



5" Pneumatic Angle Grinders

- Polyurethane grip reduces operator fatigue and vibration
- 5/8" x 11 UNC spindle
- Powerful twin-chamber motor-delivers much higher torque
- Side handle and wrenches included

Model No. THZ674



Model No.	Grinding Wheel		Spindle Thread		Free Speed RPM	Average Air Consumption CFM		Air Inlet	Hose Size		Vibration Less Than m/s^2	Sound Pressure Level dB(A)	Net Weight		Price /Each
	in	mm	in	mm		in	mm		in	mm			lbs.	kg	
THZ674	5	127	5.8	15.9	10 000	5	1/4" - 18 NPT	3/8	9.5	3.1	83	3.1	1.41		