



Hose Reels

REELS CONTRIBUTE TO AN IMPROVED WORK ENVIRONMENT WHICH SAVES TIME, EQUIPMENT & MONEY



Standard features Include:

- Durable, corrosion-resistant powder coat paint
- Heavy-duty, reinforced steel stampings for increased strength
- Permanently lubricated for long, trouble-free service
- Multi-position guide arms for versatile mounting options
- Kinkless, high quality hoses
- Spring rewind features long life spring with declutching arbor



FH494



FH502



FH504



TN315

HEAVY-DUTY INDUSTRIAL STEEL REELS

Model No.	Mfg. No.	Drive Type	Hose I.D."	Hose Length'	Max PSI	Hose Outlet (M)NPT"	Reel Inlet (F)NPT"	Reel Outlet (F)NPT"	Dimensions				Wt. lbs.	Price /Each
AIR or WATER reels for manufacturing plants, body shops, workshops, service stations, fabricators, spray booths - sold with hose														
TN315	4435-OLP	Spring	1/4	35	300	1/4	3/8	-	5 5/8	x	12 3/8	x	12 7/8	19
TN317	4625-OLP	Spring	3/8	25	300	1/4	3/8	-	5 5/8	x	12 3/8	x	12 7/8	20
TN316	5635-OLP	Spring	3/8	35	300	1/4	3/8	-	6 1/8	x	14	x	14 3/8	25
TN318	7650-OLP	Spring	3/8	50	300	1/4	1/2	-	7	x	19 3/4	x	20 1/4	43
TN319	7850-OLP	Spring	1/2	50	300	3/8	1/2	-	7	x	19 3/4	x	20 1/4	47
FI058	5450-OLP	Spring	1/4	50	300	1/4	3/8	-	6 1/8	x	14	x	14 3/8	26
NN152	5650-OLP	Spring	3/8	50	300	1/4	3/8	-	5 7/8	x	16 1/2	x	17 5/8	36
FH534	81100-OLP	Spring	3/8	100	300	3/8	1/2	-	10 1/2	x	24	x	25 3/8	82
FH490	82100-OLP	Spring	1/2	100	300	1/2	1/2	-	10 1/2	x	24	x	25 3/8	95
FH491	83050-OLP	Spring	3/4	50	250	3/4	3/4	-	10 1/2	x	24	x	25 3/8	88
FH492	D83075-OLP	Spring	3/4	75	250	3/4	3/4	-	13	x	24	x	25 3/8	102
FH493	D84050-OLP	Spring	1	50	250	3/4	1	-	15 3/4	x	24	x	25 3/8	103
FH494	E9350-OLP	Spring	3/4	50	250	3/4	3/4	-	16 3/4	x	26 1/4	x	26 3/8	140
FH495	E9450-OLP	Spring	1	50	250	3/4	1	-	16 3/4	x	26 1/4	x	26 3/8	157
OIL - medium pressure - furnished standard with S.A.E. 100 RT1 one wire braid hose - sold with hose														
TN323	7850-OMP	Spring	1/2	50	3250	1/2	1/2	-	7	x	19 3/4	x	20 1/4	57
GREASE or HYDRAULIC OIL- high pressure reel - furnished standard with S.A.E. 100 R2T two wire braid hose - sold with hose														
TN325	7650-OHP	Spring	3/8	50	4800	1/4	1/2	-	7	x	19 3/4	x	20 1/4	60
WASHDOWN - high pressure reel with maximum product delivery - equipment cleaning, pressure washing - sold without hose														
FI059	PW7600-OHP	Spring	3/8	50	5000	-	1/2	3/8	7	x	19 3/4	x	20 1/4	43
FH496	PW81000-OHP	Spring	3/8	100	5000	-	1/2	10 1/2	10 1/2	x	24	x	25 3/8	86
DUAL HYDRAULIC - medium pressure reel ideal for operating hydraulic cylinders, tools and equipment - sold with hose														
FH497	TH88050-OMP	Spring	1/2	50	2000	1/2	1/2	-	13	x	24	x	25 3/8	114
FUEL DELIVERY - low pressure equipped with Viton® seals & fuel grade hose for mobile & permanent mount applications - sold with hose														
FH498	F7925-OLP	Spring	3/4	25	250	3/4	3/4	-	7	x	19 3/4	x	20 1/4	47
FH499	F83050-OLP	Spring	3/4	50	250	3/4	3/4	-	10 1/2	x	24	x	25 3/8	89
FH500	FD84050-OLP	Spring	1	50	250	1	1	-	15 3/4	x	24	x	25 3/8	120
WELDING REELS - used for a wide variety of gases such as acetylene, Mapp gas, propane gas, natural gas and fuel gases - sold with hose														
FH501	TW7450-OLPT	Spring	1/4	50	200	note 1	1/4	-	7 3/8	x	19 3/4	x	20 1/4	50
FH502	TW84100-OLPT	Spring	1/4	100	200	note 1	note 2	-	13	x	24	x	25 3/8	101
STAINLESS STEEL for AIR, WATER or OIL - corrosion-resistant reels - swivels include Viton® O-rings - sold without hose														
FH503	5600-OLS	Spring	3/8	35	500	-	3/8	3/8	6 1/8	x	14	x	14 3/8	22
FH504	7800-OLS	Spring	1/2	50	500	-	1/2	1/2	7	x	19 3/4	x	20 1/4	41
FH505	7800-OMS	Spring	1/2	50	3000	-	1/2	1/2	7	x	19 3/4	x	20 1/4	45
HAND CRANK for AIR or WATER - designed for medium-duty applications requiring longer lengths of hose - sold without hose														
FH506	CA32106L	Manual	1/2	100	1000	-	1/2	1/2	19 3/4	x	17 3/4	x	20 1/4	40
FH507	CA32112L	Manual	1/2	200	1000	-	1/2	1/2	25 3/4	x	17 3/4	x	20 1/4	46
FH508	CA33112L	Manual	3/4	100	1000	-	3/4	3/4	19 3/4	x	17 3/4	x	20 1/4	46
HOSE REEL CART FOR 12" HAND CRANK REELS - 8" semi-pneumatic rubber tires, adjustable handle, rugged 1" square tubular steel frame														
FH509	600741-2	-	-	-	-	-	-	-	23 3/4	x	27	x	44 1/2	-



TN318



FH509

2-Year Limited Warranty - Note 1: 9/16" - 18 UNF Female Note 2: 9/16" - 18 UNF Male Note 3: 1" NPTM
 Note 4: Handle height adjustable to 35 5/8", 38 5/8", 41 1/2", 44 1/2" Standard colour as shown - powder coat paint red