



CFC Free Electro Contact Cleaner

- Fast evaporation
- No residue
- Low odour
- Non-conductive
- Safe on plastics
- Inverta spray valve allows you to spray in an upright or inverted position
- NSF registered category code K2



Model No.	Mfg. No.	Size	Price /Each
AA784	C03116	11 oz.	
AB546	C03101	1 gal.	
AB544	C03105	5 gal.	
AB545	C03155	55 gal.	

CFC Free NU Contact Cleaner

- Reduced VOC's (Volatile Organic Compounds) content and conforms to CARB (California Air Resources Board), OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium) VOC regulations
- Removes dirt, flux, moisture, dust, and other contaminants from electrical equipment
- Fast evaporating, safe on plastics
- Will not leave a residue
- NSF registered category code K2



Model No.	Mfg. No.	Size	Price /Each
AD177	C05416	11 oz.	

Revo 66® Contact Cleaner

- Ideal for removing dirt, moisture, flux or oxides from the internal components of electronic equipment
- Non-flammable precision cleaning
- Does not contain brominated solvents
- Fast evaporating
- Non-conductive
- Quick penetration
- No rinsing and no residue
- Safe to use on most surfaces
- NSF registered category code K2
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AD010	C04416	12 oz.	

Electro 140° Contact Cleaner

- Flash point above 140°F (60°C)
- Superior wetting and penetrating action
- Controlled evaporation
- No residue
- Non-conductive
- Safe to use on most surfaces
- Inverta spray valve allows you to spray in an upright or inverted position



Model No.	Mfg. No.	Size	Price /Each
AA836	C00916	11 oz.	

Electro Contact Cleaner

- No ozone depletion potential
- Fast penetration
- Quick evaporation
- Penetrates into minute spaces
- Cleans/degreases delicate mechanisms
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt and organic soils
- No rinsing and no residue
- Safe to use on most surfaces



Model No.	Mfg. No.	Size	Price /Each
AA858	C00416	14 oz.	

Micro-X Fast Evaporating Contact Cleaner

- Fast evaporation
- Quick penetration
- No residue
- Low odour
- Safe on plastics
- No rinsing
- Inverta spray valve allows you to spray in an upright or inverted position



Model No.	Mfg. No.	Size	Price /Each
AA837	C04516	11 oz.	

QB Precision Duster

- Quick blast precision duster removes contaminants, dirt, dust and other soils
- Moisture free
- No residue
- No flash point
- Odourless



Model No.	Mfg. No.	Size	Price /Each
AA918	C05710	12 oz.	

PSC Plastic Safe Cleaner

- Formulated for contact cleaning
- Fast evaporation
- No flash point
- No rinsing and no residue
- Displaces moisture
- Very low odor
- No CFC's



Model No.	Mfg. No.	Size	Price /Each
AB700	C04620	18 oz.	

Lectra Clean® Heavy-Duty Electrical Parts Degreaser

- A chlorinated based degreaser that quickly removes grease, oil and dirt from motor parts and other similar equipment
- NSF Registered K2



Model No.	Mfg. No.	Size	Price /Each
AF103	72018	539 g	

QD™ Contact Cleaner

- Plastic safe: Yes
- Flashpoint: Less than -18°C
- Very fast evaporation rate
- Suitable for cleaning sensitive electronics and electrical equipment
- Use where lower flashpoint cleaners are acceptable
- Accepted for use in Canadian food processing facilities
- NSF Registered K2



Model No.	Mfg. No.	Size	Price /Each
MLN874	72130	312 g	

Freeze Spray

- Plastic Safe: Yes
- No flashpoint
- Very fast evaporation rate
- Aerosol coolant system that instantly freezes surfaces to -60°F, dissipating heat and cooling equipment
- Assists in locating thermal intermittent components, failures and shorts
- Safe to use on sensitive components and all surfaces finishes



Model No.	Mfg. No.	Size	Price /Each
AE971	74086	284 g	

Silicone Lubricant

- Safely lubricates, waterproofs and protects metal and non-metal surfaces, including rubber, plastic and vinyl
- Dries fast and leaves a clear, non-staining film that doesn't stick or make a mess
- Ideal for use on cables, pulleys, guide rails, valves, linkages, hinges, locks and more
- Container Type: Aerosol Can
- Effective Temperature Range: -100°F to 500°F
- Film Type: Dry



Model No.	Mfg. No.	Size	Price /Each
AF172	1079	311 g	