

## **Food Plant** Penetrating Oil

- General purpose lubricant for use on food processing equipment
- Penetrates and loosens rust, scale, corrosion, and dirt to free corroded parts and fasteners
- Does not contain silicones
- Approved for use in Canadian food processing facilities
- NSF Registered H1



CR®

Model	Mfg.	Size	Price
No.	No.		/Each
AF203	73086	312 a	

# **Food Plant Chain Lube**

- Keeps roller drive and
- conveyor chains lubricated Blend of synthetic
- lubricants and mineral oil
- Penetrates, lubricates and protects moving parts by reducing friction and wear
- Approved for use in Canadian food processing facilities

No. 73056

NSF Registered H1





340 g

Size

11 oz.

## **Di-Electric** Grease

- Non-curing silicone compound used for electrical sealing
- Waterproofs electrical
- connections and components Improves electrical performance
- NSF Registered H1

**Multi-Purpose** 

**Food Plant** 

Appearance: White

Flash Point: 221°C

NSF Registered H1

Semi-Solid/Solid Grease

**Effective Temperature Range:** 

-5°F - 370°F (-20.6°C to 187.8°C)

Base Type: Aluminum Complex

Grease



CRG

Grease

NSF H1

Graisse à

usages multiples

Our usine

CR®

Model No.	Mfg.		Price /Each
	No.	Size	
AF248	73082	284 g	

# **Detex® Food Grade Extreme Temp Grease**

- · Premium, fully synthetic grease performs well in extreme temperature applications (-75°F - 510°F)
- NSF H1 grease can be used anywhere within a facility where incidental food contact may occur
- Non-melting formula is suitable for extended high temperature exposures
- Dye-free grease will not stain product or equipment
- Fortified with PTFE for enhanced lubrication and corrosion resistance
- Resists water washout through multiple wash cycles
- Metal and X-ray detectable plastic cap
- Accepted for use in Canadian food processing facilities





Model No.	Mfg. No.	Size	Price /Each
AH206	C51014	369 g	
AH207	C51055	55 Gal.	

#### **Clear Penetrating** Grease

- · Features high tack, quick penetrating action, metal detectable plastic components, and clear lubricating gel
- High performance, versatile lubricant fortified with PTFE additives for enhanced lubrication
- Resists water washout
- Protects against corrosion
- Colour: Beige
- Odour: Acetone
- Appearance: Gas
- Boiling Point/Range: 132.8 °F (56 °C)
- Flash Point: 132.8 °F (56.0 °C)
- Tag Closed Cup
- Vapor Density: 2
- Viscosity: 260 cP @ 75°F (Concentrate) Heat of Combustion: > 30 kJ/g
- Temperature Range:
- 0°F (-18°C) to 400°F (204°C)

C06716



/Eac



CR©				
Model	Mfg.	61-1	Price	
No.	No.	Size	/Each	
AF202	73600	397 g	, and the second	

# **Detex® Food Grade Electronic** Cleaner

- Removes dirt, moisture, and oxides from electronic equipment
- NSF K6 electronic cleaner can be used anywhere within a facility where incidental food contact may occur
- Plastic-safe formula can be used on a variety of surfaces
- Fast drying and residue-free for efficient maintenance cycles
- VOC Compliant in all 50 states
- Metal and X-ray detectable packaging



Model No.			Williams Space of Marie Control of the Control of t	
	Mfg. No.	Size	Price /Each	
AH215	C58116	312 g		

#### **LU210 Food Grade** Silicone Lubricant

- 5% silicone formula
- Colourless, odourless low-viscosity lubricant
- Prevents sticking without transferring to end products
- Will not attack delicate surfaces such as styrene or urethane
- For slides, guide rails, knives, slicers, saws, grinders, dough mixers, guards, conveyors, food racks, ovens, bottling machines, heat sealing equipment, all food
- and drug processing equipment NSF registered category code H1





Model	Mfg.	Size	Price
No.	No.		/Each
AA110	SC0210000	10 oz.	

## **Synthetic Food Grade Oil**

- Includes PTFE, for added lubricity
- Does not emulsify with water
- Waterproof
- Biodegradable
- Clear, non-staining
- Kosher approved
- For pumps, gear boxes, bearings, hydraulic systems, motors, chains, conveyors, general purpose lubrication
- NSF registered category code H1



Model	Mfg.	Size	Price
No.	No.		/Each
AA525	TF23010	12 oz.	

