Red & Redi Multi-Purpose Red Grease

- Delivers excellent lubricationPrevents rust, corrosion
- Prevents rust, corrosion and oxidation
 Remains effective at
- extremely high temperatures
- Reduces friction and vibration
- Resists shock
- Red colour allows easy visual inspection
- Penetrates quickly
- Non-melting





White Lithium Grease w/PTFE

- Rapidly forms into a pure white grease
- Heat and water resistant
- Produces a long lasting,
- Produces a long lasting protective film against rust and corrosion
- White colour allows easy visual inspection
- Does not contain any chlorinated solvents
- Accepted for use in Canadian food processing facilities



Model	Mfg.	Size	Price
No.	No.		/Each
ΔΔ914	C03816	10.07	

LU100 White Lithium Grease

- · Inhibits corrosion on unpainted metal surfaces
- High-solids, non-staining white grease
- Excellent for metal-to-metal applications
- Will not drip or run on vertical surfaces
- Effective from -20°F to 275°F
- For chains, gears, drives, hinges and other vertical or overhead surfaces
- Recommended for use on knockout pins on mould equipment
- NSF registered category code H2



Model	Mfg.	Size	Price
No.	No.		/Each
ΔΔ103	SC0100000	11 07	

ViperLube™ High Performance Synthetic Grease

- Grease provides superior protection against equipment exposed to a wide range of operating temperatures and environments
- Use as a lubricant and protective anti-rust film on bearings, machine parts, equipment, or as a release agent on gaskets and seals
- Temperature resistance: 400°F (204°C) continuous
- NLGI Grade: 2/Severe Duty GC-LB
- NSF registered category code H1
- Accepted for use in Canadian food processing facilities



Dielectric Grease

- Moisture proof barrier that lubricates and protects electrical equipment from salt, dirt, and corrosion
- High dielectric strength
 Good thormal evidation
- Good thermal, oxidation and chemical stability
 Temperature resistance:
- Iemperature resistance: 400°F (204°C) continuous



White Lithium Grease

- For metal-to-metal and metal-to-plastic applications
- Corrosion protection
- No ODC's
- Temperature resistance: 380°F (193°C) dropping point



RUST-OLEUM

LOCTITE.

Model	Mfg.		Price
No.	No.	Size	/Each
AB505	457456	3 oz.	
AB508	457457	14 oz.	
AB507	457458	400 g.	
AB509	459782	30 lbs.	

LOCTITE.

Model	Mfg.	Size	Price
No.	No.		/Each
AC365	270640	0.33 oz.	

LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA611	270638	1.5 oz. tube	
AE854	1906122	10.75 oz. Aerosol	

LU103 Rust Breaker™ Heavy Duty Rust Penetrant

- Quickly loosens rust while penetrating grease and dirt
- Transparent, non-staining oil
- Light film displaces moisture and acts as a corrosion preventative
- Jet stream sprays up to two feet for safe, accurate application
- Flashpoint: 205°F
- Will not harm painted surfaces
- For releasing rusted or frozen lugs and bolts, lubricating tight-fitting parts, general overhaul, repair work, food plant equipment

SC0103000



RUST-OLEUM

Model No.	Mfg. No.	Size	Price /Eacl
KP497	257395	9 oz.	
KP498	257397	Replacement Static Mixers - 3 Pack	

Multi-Purpose Concrete Repair & Adhesive

- Excellent for bridging horizontal or vertical cracks, even under water
- · Twice as strong as concrete
- Works on concrete, masonry, brick, steel and more
- For indoor or outdoor use
- Colour: Light Gray

Turbokrete Concrete Patch Compound Kits

- Easily repair deep holes and cracks
- 100%-solids epoxy patch kit is designed for floors exposed to heavy traffic and intermittent chemicals
- Protects against abrasion, impact and most chemicals—no sealer required
- Creates an extremely hard surface –
 3-4 times stronger than concrete
- For interior/exterior use on damaged or severely spalled floors, curbs, ramps, etc.
- Odorless
- Easy-mix kit includes base, activator and aggregate
- Colour: Light Gray

RUST-OLEUM

Model No.	Mfg. No.	Size	Price /Each
KP495	253479	2 gal.	,
KP496	5494323	3.5 gal.	

AA113

Size