



## Magnetic Strips


- Conforms to any contour
- Holds many times its weight
- Can be cut, drilled or shaped
- Available with or without adhesive backing



Thick"	Width"	Length'	Max. Pull per Lin. Ft. (lbs.)	Model No. w/o Adhesive	Price /Roll	Model No. w/Adhesive	Price /Roll
1/32	1/2	200	2	TGY640		TGY648	
1/32	3/4	200	3	TGY641		TGY649	
1/32	1	100	4	TGY642		TGY650	
1/32	1	200	4	TGY643		TGY651	
1/16	1/2	100	3	TGY644		TGY652	
1/16	3/4	100	5	TGY645		TGY653	
1/16	1	50	6	TGY646		TGY654	
1/16	1	100	6	TGY647		TGY655	

## Magnetic Tool Holders

- Mount to walls, work benches, ladders, etc.
- 3/16" mounting holes and screws provided
- **TLY308** and **TLY309**: holes on 16" centres
- Holds a 10-lb. hammer!



Model No.	Thickness"	H"	L"	Pull lbs.	Wt. lbs.	Price /Each
TLY307	1 1/8	2	12	120	2.0	
TLY308	1 1/8	2	18	180	3.0	
TLY309	1 1/8	2	24	240	4.0	

## Advantagelift™ Rare Earth Lifting Magnet

- Handle moves laterally instead of pulling, pressing buttons or levers
- Locking lifting bail(s) prevents accidental load release during lift
- Recessed (protected) labels for extended life
- Lifts flats both horizontally and vertically with Vertical Lift Bail
- RFID Enabled with embedded RFID chip
- Supports custom pole shoes (1/4"-20 Tapped Holes, 1/2" deep)
- Swiveling Lift Bail(s)
- Operating temperature range of -10°F (-23°C) to 180°F (82 °C)
- 3:1 Design Factor
- ASME B30.20 BTH-1 Design Category B Service Class 3



Model No.	Mfg. No.	Strength lbs.	Dimensions				Price /Each
			L"	x	W"	x H"	
UAV698	AL1000	1000	13-1/4	x	5-7/16	x 4-5/8	
UAV699	AL1500	1500	13-5/16	x	6-7/8	x 6	
UAV700	AL2000	2000	16-5/16	x	6-7/8	x 6	

## Vertical Lug Adapter for Rare Earth Advantage Lift™ Magnets

- Adapter for "on/off" permanent rare earth lift magnet
- Locking lifting bail(s) prevents accidental load release during lift
- Lifts flats both horizontally and vertically with Vertical Lift Bail
- 3:1 design factor
- ASME B30.20 BTH-1 Design Category B Service Class 3
- For Use With: AL0500 & AL1000 Magnets
- Operating Temperature Range: -10°F (-23°C) to 180°F (82 °C)



Model No.	Mfg. No.	Dimensions				Bail Thickness"	Bail Height"	Bail Width"	Price /Each
		L"	x	W"	x H"				
UAV701	ALLUG1	4-11/16	x	4-3/8	x 3-9/16	1/2	1-7/8	1-1/2	
UAV702	ALLUG2	5-3/4	x	5-3/4	x 4-3/4	5/8	2-7/32	1-3/4	

Control spills with confidence

