



EL601 Red Insulating Varnish

- Insulating spray for general coating, impregnating and insulating electrical and electronic work
- Resists oil, water, acids and alkalis
- Excellent adhesion
- Oil resistant per ASTM-D-115-55



Model No.	Mfg. No.	Size	Price /Each
AA179	SC0601000	15.25 oz.	

SP603 Blue Layout Dye

- Applies a smooth, even coat for all layout work
- Fast-drying, non-flaking, non-etching, won't peel
- Adheres to metal or glass
- For pattern-making, tool and die making, machining and maintenance mechanicals



Model No.	Mfg. No.	Size	Price /Each
AA180	SC0603000	12 oz.	

SP606 Layout Dye Remover

- Removes layout fluids quickly and efficiently
- Removes light oils, greases, lacquer and other markings on metal or glass
- Leaves no residue
- No chlorinated solvents
- For tool and die making and production departments



Model No.	Mfg. No.	Size	Price /Each
AA181	SC0606000	12.75 oz.	

Cutting Oil Thread Cutting Lubricant

- Ideal for use on all types of metals, including brass, copper and aluminum
- NSF Registered P1



Model No.	Mfg. No.	Size	Price /Each
AF250	73500	340 g	

A-9 Aluminum Cutting Fluids

- Designed for aluminum, non-ferrous metals
- Forms an effective extreme pressure boundary lubricant between tool and work surface
- Leaves a surface, which requires only ordinary cleaning



Model No.	Size	Price /Each
AA149	4 oz.	

Rapid Tap™ Cutting Fluids

- Effective on tough-to-drill metals and alloys such as beryllium, molybdenum, stainless steel and stellite
- Makes tapping, reaming, drilling and threading operations easier, faster and more accurate
- Not recommended for use with aluminum and its alloys



Model No.	Size	Price /Each
AA160	4 oz.	

Coolcut™

- Extends cutting tool life
- Suitable for all ferrous and non-ferrous metals
- Produces a better finish
- Solvent-free, no chlorine
- For drilling, sawing, milling, turning, reaming, broaching



Model No.	Description	Size	Price /Each
AA468	Liquid	350 ml	
AG673	Liquid	3.78 L	
AA470	Liquid	20 L	
AB748	Liquid	208 L	
AA471	Stick	300 g	
AA467	Aerosol Spray	400 ml	
AE955	Trigger Spray	500 ml	

AluCut™ Aluminum Cutting Lubricant

- High-performance lubricant that extends cutting tool life
- Specially formulated for use with aluminum and other non-ferrous metals
- Clean, precise, stain-free application
- Ideal for inclined, vertical, and overhead surfaces
- Coats cutting edge or workpiece
- Applications include cutting with circular chapsaws, sawing with jigsaws or portable bandsaws, drilling, nibbling, and tapping



Model No.	Description	Size	Price /Each
AA191	Stick	300 g	

Coolcut™ S-30 Water-Miscible Cutting Lubricant

- Ready-to-use, high-performance metal cutting lubricant specially designed for automatic and semi-automatic metal removing operations
- Will not gum up slides and glides
- Increases feed, speed, and production
- Prevents bacterial growth when not in use
- Formulated with extended corrosion protection
- Contains extreme pressure additives (EP), bacterial control ingredients, and no chlorine
- Can be diluted up to 1:30



Model No.	Description	Size	Price /Each
AG516	Jug	3.78 L	
AF006	Jug	20 L	
AF007	Drum	208 L	