Red Beam Self-Leveling Horizontal & Vertical Rotary Laser

- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically Laser beam modes include dot, two adjustable line
- lengths and two rotational speeds
- Includes: 1 Rotary Laser, 1 Remote Control, 1 Detector with Clamp, 1 Tinted Glasses, 1 Target, 1 Multi-Function Mount, 1 NiMH rechargeable battery pack, 1 6.4V battery adapter, 1 Alkaline battery compartment (batteries not included), 1 Hard-Shell Carrying Case, 1 Instruction Manual

|OHNSON 🛒



TECHNICAL SPECIFICATIONS

Model No.	IB940
Mfg. No.	40-6534
Laser Wave Length:	635 Nm
Laser Class:	Class 111
Accuracy:	±1/8"/100 ft.
Interior Range:	Up to 200 ft. diameter depending upon light conditions
Exterior Range:	Up to 1500 ft. diameter with detector
Remote Range:	Up to 200 ft. diameter
Power Supply:	NiMH rechargeable battery pack and 6.4V adapter included
Working Temperature:	14°F-113°F
Scanning Modes:	0°, 30°, 60°
Rotational Speeds:	200 and 500 RPM
Price/Each	\$

Interior & Exterior Rotary Laser Level Kits

- Horizontal self-leveling automatically aligns the laser to centre
- Protected rotary head and weatherproof design deliver
- interior and exterior jobsite durability Standby mode allows the user to pause the laser while
- transitioning from horizontal to vertical Equipped with leveling vial for manual leveling in vertical mode
- Includes: (2) D batteries, (1) Detector and clamp, (1) Wall mount, (1) Target card, (1) Contractor's bag, (1) 9-Volt battery



TECHNICAL SPECIFICATIONS

Limited

2024 © TENAQUIP

Model No. Mfg. No. Laser Beam Colour: Laser Wave Length: Laser Class: Accuracy per 100': Interior Range: Range with Detector: **Rotation Speeds:** Self-Leveling Range: Price/Each

TLY375 DW074KD Red 635 Nm Class IIIA 1/4" 100' 600' 0, 60, 600 RPM ±5°

\$

Green Beam Self-Leveling Horizontal & Vertical Rotary Laser

- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically Laser beam modes include dot, two adjustable line
- lengths and two rotational speeds
- Includes: 1 Rotary Laser, 1 Remote Control, 1 Detector with Clamp, 1 Tinted Glasses, 1 Target, 1 Multi-Function Mount, 1 NiMH rechargeable battery pack, 1 6.4V battery adapter, 1 Alkaline battery compartment (batteries not included), 1 Hard-Shell Carrying Case, 1 Instruction Manual

|OHNSON<u>||</u>#



TECHNICAL SPECIFICATIONS

Model No.	IB941
Mfg. No.	40-6544
Laser Wave Length:	532 Nm
Laser Class:	Class 111
Accuracy:	+/-1/8"/100 ft.
Interior Range:	Up to 400 ft. diameter depending upon light conditions
Exterior Range:	Up to 1200 ft. diameter with detector (not included)
Remote Range:	Up to 200 ft. diameter
Power Supply:	NiMH rechargeable battery pack and 6.4V adapter (included)
Working Temperature	32°F-104°F
Scanning Modes:	0°, 30°, 60°
Rotational speeds:	200 and 500 RPM
Price/Each	\$

3 Beam Self-Leveling Line Laser

- 3 Beam Line Laser to aid in 90° layout
- 2x Brighter diode to increase visibility in bright job site conditions
- Built-in magnetic pivot bracket mounts easily on metal surfaces
- 1-button operation and control panel for ease of use
- Micro adjust knob for precise alignment of 90° intersecting lines over greater distances
- Includes: 4 AA batteries for 30 hours of run-time, Ceiling Mount and Kit Box



Power:

Run Time:

Price/Each



TECHNICAL SPECIFICATIONS Model No. Mfg. No. Accuracy:

TMB038 DW089K ±1/8" @ 30' 6 V. 4-AA Batterv 30 hours \$

www.tenaquip.com