

### Defender<sup>™</sup> 6000 Washdown Bench Scale

- Specifically designed for food, chemical and pharmaceutical applications, including production and packaging
- 100-240 VAC / 50/60 Hz universal power supply, hardwired
- Easy access communication ports including RS232 and USB host (included)
- · Ethernet and Wi-Fi/Bluetooth
- 316 stainless steel platform and frame, hermetically-sealed, stainless steel load cell
- IP68/IP69K 316 stainless steel housing indicator and mounting bracket
- Knife-resistant front panel
- Features 150% overload capacity protection, bar matrix check light, customizable print templates, menu and key lock, selectable environmental and auto-print settings, stability indicator, overload/underload indicators, auto shut-off, auto tare, and adjustable non-slip rubber feet
- 6-digit, 7-segment white LED, 20 mm high digits display
- Defender 6000 meets metrological approvals, NSF listing, and supporting HACCP systems
- Platform Dimensions: 19-7/10" L x 15-7/10" W



NOT LEGAL FOR TRADE



Model No.	Mfg. No.	Capacity Ibs.	Graduations	Price /Each
IC793	30575566	100	5 g	
IC794	30575567	300	10 a	

## Cyclone Bench and Platform Scale

- Durable thick stainless steel platter allows for heavy loads without bending
- 2 scales in one Dual range- always the right sensitivity no matter how light or heavy the load
- Back support Ideal for weighing products in bags or that which require extra support.
- Post mounted indicator -Makes it easy to see the screen
- · Three weighing modes: lb., kg, pcs
- Ideal for shipping, receiving, check weighing or counting
- · Battery or adapter operated





#### **NOT LEGAL FOR TRADE**

NOT LEGAL FOR TRADE							
Model No.	Capacity Range 1	Graduation Range 1	Capacity Range 2	Graduation Range 2	Price /Each		
15-3/4	4" L X 19-7/10" V	V					
IB770	0-60 kg/0-150 lbs.	20 g/0.05 lbs.	60-150 kg/150-300 lbs.	50 g/0.1 lbs.			
17-3/4	ł" L X 23-3/5" W						
IB771	0-150 kg/0-300 lbs.	50 g/0.1 lbs.	150-300 kg/300-600 lbs.	100 g/0.2 lbs.			

### D32XW15VR Defender® 3000 Wash-Down Bench Scale

- Features a NEMA 4X/IP66 stainless steel indicator built to endure tough industrial elements
- Durable construction with a 304 stainless steel platform, stainless steel tubular frame, column and indicator bracket, and IP67 stainless steel load cell
- Easy-to-read display & basic counting mode allow for simple operation for everyday basic industrial applications
- The 58-hour rechargeable battery offers continuous operation for multi-day operations
- Capacity: 33 lbs.
- Graduations: 0.005 lbs.
- Platform Dimensions: 14" L x 12" W

  Platform Dimensions: 14" L x 12" W
- Power Supply: AC Power (Included) or Rechargeable Battery (Included)

Model No. IC151 Mfg. No. 30369114 Price/Each \$







# **Top Gun Electronic Platform Scales**

- For use in dry environments and areas with low humidity
- · Counting function (secondary)
- Hi/Target/Lo (check weighing)
- Accumulation function
- Removable stainless steel platter (1.2 mm gauge) 12" W x 18" D (30.5 x 45.7 cm)
- Built-in level
- · Adjustable lockable anti-slip leveling feet
- Predefined capacity settings eliminate installation errors
- Mobile installation
- Choice of ABS or stainless steel indicators





Model No.	Mfg. No.	Indicator*	Frame**	Capacity	Graduation	Price/Each
<b>NOT LE</b>	GAL FOR TR	ADE				
IB011	KPLMS 1218-60	KIN 1000 (ABS)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs	
IB012	KPLMS 1218-60	KIN 2000 (WR)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs	
IB013	KPLMS 1218-150	KIN 1000 (ABS)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs	
IB014	KPLMS 1218-150	KIN 2000 (WR)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs	
LEGAL	FOR TRADE					
IB015	KPLMS 1218-60	KIN 1000 (ABS)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs	
IB016	KPLMS 1218-60	KIN 2000 (WR)	MS	60 kg/150 lbs.	0.02 kg/0.05 lbs	
IB017	KPLMS 1218-150	KIN 1000 (ABS)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs	
IB018	KPLMS 1218-150	KIN 2000 (WR)	MS	150 kg/300 lbs.	0.05 kg/0.1 lbs	

\*Indicator

ABS = ABS Plastic WR = Stainless Steel

\*\* Frame MS = Mild Steel